

Functionally recursive groups

Self-similar groups

Version 0.857142p8

\$Date: 2008/12/02 12:04:31 \$

Laurent Bartholdi

Groups generated by automata or satisfying functional recursions

Laurent Bartholdi — Email: laurent.bartholdi@gmail.com
— Homepage: <http://www.uni-math.gwdg.de/laurent/>

Address: Mathematisches Institut, Bunsenstraße 3-5, D-
37073 Göttingen
D-37073 Göttingen
Germany

Abstract

This document describes the package FR, which implements in GAP the basic objects of Mealy machines and functional recursions; and handles groups that they generate.

Groups defined by a recursive action on a rooted tree can be defined in GAP via their recursion. Various algorithms are implemented to manipulate these groups and their elements.

For comments or questions on FR please contact the author; this package is still under development.

Copyright

© 2006-2008 by Laurent Bartholdi

Acknowledgements

Part of this work is supported by the "Swiss National Fund for Scientific Research"

Colophon

This project started in the mid-1990s, when, as a PhD student I did many calculations with groups generated by automata, and realized the similarities between all calculations; it quickly became clear that these calculations could be done much better by a computer than by a human.

The first routines I wrote constructed finite representations of the groups considered, so as to get insight from fast calculations within GAP. The results then had to be proved correct within the infinite group under consideration, and this often involved guessing appropriate words in the infinite group with a given image in the finite quotient.

Around 2000, I had developed quite a few routines, which I assembled in a GAP package, that dealt directly with infinite groups. This package was primitive at its core, but was extended with various routines as they became useful.

I decided in late 2005 to start a new package from scratch, that would incorporate as much functionality as possible in a uniform manner; that would handle semigroups as well as groups; that could be easily extended; and with a complete, understandable documentation. I hope I am not too far from these objectives.

Contents

1	Licensing	10
2	FR package	11
2.1	A brief mathematical introduction	11
2.2	An example session	12
3	Functionally recursive machines	16
3.1	Types of machines	16
3.2	Products of machines	17
3.3	Creators for FRMachines	17
3.3.1	FRMachineNC (family,free,listlist,list)	17
3.3.2	FRMachine ([list],list,list)	17
3.3.3	UnderlyingFRMachine	18
3.3.4	AsGroupFRMachine	19
3.3.5	ChangeFRMachineBasis	20
3.4	Attributes for FRMachines	21
3.4.1	StateSet (FR machine)	21
3.4.2	GeneratorsOfFRMachine	21
3.4.3	Output (FR machine,state)	22
3.4.4	Transition (FR machine,state,input)	22
3.4.5	WreathRecursion	22
3.5	Operations for FRMachines	23
3.5.1	StructuralGroup	23
3.5.2	\+	23
3.5.3	*	24
3.5.4	TensorSumOp (FR Machines)	24
3.5.5	TensorProductOp (FR Machines)	24
3.5.6	DirectSumOp (FR Machines)	25
3.5.7	DirectProductOp (FR Machines)	25
3.5.8	TreeWreathProduct (FR machine)	26
3.5.9	SubFRMachine	26
3.5.10	Minimized (FR machine)	27
3.5.11	Correspondence (FR machine)	27

4	Functionally recursive elements	28
4.1	Creators for FRElements	28
4.1.1	FRElementNC (family,free,listlist,list,assocword)	28
4.1.2	FRElement ([list,]list,list,list)	29
4.1.3	FRElement (machine/element,list)	30
4.1.4	ComposeElement (elementcoll,perm)	30
4.1.5	VertexElement	31
4.1.6	DiagonalElement	31
4.1.7	AsGroupFRElement	32
4.2	Operations and Attributes for FRElements	33
4.2.1	Output (FR element)	33
4.2.2	Activity	34
4.2.3	Transition (FR element,input)	34
4.2.4	Portrait	35
4.2.5	DecompositionOfFRElement	35
4.2.6	StateSet (FR element)	35
4.2.7	State	36
4.2.8	States	36
4.2.9	FixedStates	37
4.2.10	LimitStates	37
4.2.11	IsFiniteStateFRElement	37
4.2.12	InitialState	38
4.2.13	\^ (POW)	38
4.2.14	* (PROD)	39
4.2.15	\[\] (ELMLIST)	39
5	Mealy machines and elements	40
5.1	Creators for MealyMachines and MealyElements	40
5.1.1	MealyMachine ([list,]listlist,list)	40
5.1.2	MealyMachine (domain,domain,function,function)	41
5.1.3	MealyMachineNC (family,listlist,list)	42
5.1.4	AllMealyMachines	42
5.2	Operations and Attributes for MealyMachines and MealyElements	43
5.2.1	Draw	43
5.2.2	Minimized (Mealy machine)	44
5.2.3	DualMachine	44
5.2.4	IsReversible	45
5.2.5	IsMinimized	45
5.2.6	AlphabetInvolution	45
5.2.7	IsBireversible	46
5.2.8	StateGrowth	46
5.2.9	Degree (FR element)	46
5.2.10	IsFinitaryFRElement	47
5.2.11	Depth (FR element)	47
5.2.12	IsBoundedFRElement	47
5.2.13	IsPolynomialGrowthFRElement	48
5.2.14	Signatures	48

5.2.15	VertexTransformationsFRMachine	49
5.2.16	FixedRay (FR element)	49
5.2.17	IsLevelTransitive (FR element)	49
5.2.18	AsMealyMachine (FR machine)	50
5.2.19	AsMealyMachine (List)	50
5.2.20	AsMealyElement	51
5.2.21	AsIntMealyMachine	51
5.2.22	TopElement	52
5.2.23	ConfinalityClasses	52
5.2.24	Germes	53
5.2.25	HasOpenSetConditionFRElement	53
5.2.26	LimitMachine	53
5.2.27	NucleusMachine (FR machine)	54
5.2.28	GuessMealyElement	54
6	Linear machines and elements	56
6.1	Methods and operations for LinearFRMachines and LinearFRElements	56
6.1.1	VectorMachine	56
6.1.2	AlgebraMachine	57
6.1.3	Transition (Linear machine)	58
6.1.4	Transitions	58
6.1.5	NestedMatrixState	59
6.1.6	ActivitySparse	59
6.1.7	Activities	60
6.1.8	IsConvergent	60
6.1.9	TransposedFRElement	60
6.1.10	LDUDecompositionFRElement	61
6.1.11	GuessVectorElement	62
6.1.12	AsLinearMachine	62
6.1.13	AsVectorMachine	63
6.1.14	AsAlgebraMachine	63
6.1.15	AsVectorMachine (Linear machine)	64
6.1.16	AsAlgebraMachine (Linear machine)	64
7	Self-similar groups, monoids and semigroups	65
7.1	Creators for FR semigroups	65
7.1.1	FRGroup	65
7.1.2	SCGroup	67
7.1.3	Correspondence (FR semigroup)	68
7.1.4	FullSCGroup	68
7.1.5	FRMachineFRGroup	69
7.1.6	IsomorphismFRGroup	70
7.1.7	IsomorphismMealyGroup	71
7.1.8	FRGroupByVirtualEndomorphism	72
7.1.9	TreeWreathProduct (FR group)	73
7.1.10	WeaklyBranchedEmbedding	73
7.2	Operations for FR semigroups	73

7.2.1	PermGroup	73
7.2.2	PcGroup	74
7.2.3	TransMonoid	75
7.2.4	TransSemigroup	75
7.2.5	EpimorphismGermGroup	76
7.2.6	StabilizerImage	76
7.2.7	LevelStabilizer	77
7.2.8	IsStateClosedFRSemigroup	77
7.2.9	StateClosure	78
7.2.10	IsRecurrentFRSemigroup	78
7.2.11	IsLevelTransitive (FR group)	78
7.2.12	IsInfinitelyTransitive	79
7.2.13	IsFinitaryFRSemigroup	79
7.2.14	Degree (FR semigroup)	79
7.2.15	HasOpenSetConditionFRSemigroup	80
7.2.16	IsContracting	80
7.2.17	NucleusOfFRSemigroup	80
7.2.18	NucleusMachine (FR semigroup)	81
7.2.19	BranchingSubgroup	81
7.2.20	FindBranchingSubgroup	81
7.2.21	IsBranched (FR group)	82
7.2.22	IsBranchingSubgroup (FR semigroup)	82
7.2.23	TopVertexTransformations	82
7.2.24	VertexTransformations (FR semigroup)	83
7.2.25	VirtualEndomorphism	83
7.2.26	EpimorphismFromFpGroup	84
7.2.27	IsomorphismSubgroupFpGroup	84
7.3	Properties for infinite groups	85
7.3.1	IsTorsionGroup	85
7.3.2	IsTorsionFreeGroup	85
7.3.3	IsAmenableGroup	86
7.3.4	IsVirtuallySimpleGroup	86
7.3.5	IsResiduallyFinite	86
7.3.6	IsSQUniversal	86
7.3.7	IsJustInfinite	86
8	Algebras	88
8.1	Creators for FR algebras	88
8.1.1	FRAlgebra	88
8.1.2	SCAlgebra	89
8.1.3	BranchingIdeal	89
8.2	Operations for FR algebras	89
8.2.1	MatrixQuotient	89
8.2.2	ThinnedAlgebra	90
8.2.3	Nillity	90

9	Iterated monodromy groups	91
9.1	Creators and operations for IMG FR machines	91
9.1.1	IMGFRMachine (FR machine)	91
9.1.2	IMGRelator	91
9.1.3	Mating	92
9.1.4	PolynomialFRMachine	92
9.1.5	DBRationalIMGGroup	93
9.1.6	ValueRational	94
9.1.7	CriticalValuesQuadraticRational	94
9.1.8	CanonicalQuadraticRational	94
9.1.9	PostCriticalMachine	95
9.2	Spiders	95
9.2.1	RationalFunction	95
9.2.2	IMGFRMachine (rational function)	96
10	Examples	97
10.1	Examples of groups	97
10.1.1	FullBinaryGroup	97
10.1.2	BinaryKneadingGroup	97
10.1.3	BasilicaGroup	98
10.1.4	AddingGroup	98
10.1.5	BinaryAddingGroup	99
10.1.6	MixerGroup	99
10.1.7	SunicGroup	100
10.1.8	GrigorchukMachines	100
10.1.9	GrigorchukMachine	101
10.1.10	GrigorchukOverGroup	101
10.1.11	GrigorchukEvilTwin	101
10.1.12	BrunnerSidkiVieiraGroup	102
10.1.13	AleshinGroups	102
10.1.14	AleshinGroup	102
10.1.15	BabyAleshinGroup	103
10.1.16	SidkiFreeGroup	103
10.1.17	GuptaSidkiGroups	103
10.1.18	GuptaSidkiGroup	104
10.1.19	NeumannGroup	104
10.1.20	FabrykowskiGuptaGroup	104
10.1.21	OtherSpinalGroup	104
10.1.22	GammaPQMachine	104
10.1.23	HanoiGroup	105
10.1.24	DahmaniGroup	105
10.1.25	MamaghaniGroup	105
10.1.26	WeierstrassGroup	105
10.1.27	FRAffineGroup	106
10.1.28	CayleyGroup	107
10.2	Examples of semigroups	108
10.2.1	I2Machine	108

10.2.2	I4Machine	108
10.3	Examples of algebras	108
10.3.1	PSZAlgebra	108
10.3.2	GrigorchukThinnedAlgebra	109
10.3.3	GuptaSidkiThinnedAlgebra	109
10.3.4	SidkiFreeAlgebra	109
10.4	Bacher's determinant identities	109
10.5	VH groups	112
10.5.1	VHStructure	113
10.5.2	VerticalAction	113
10.5.3	VHGroup	113
10.5.4	IsIrreducibleVHGroup	113
10.5.5	MaximalSimpleSubgroup	114
11	FR implementation details	115
11.1	The family of FR objects	115
11.1.1	FRMFamily	115
11.1.2	FREFamily	115
11.1.3	AlphabetOfFRObjct	115
11.1.4	AsPermutation (FR object)	116
11.1.5	AsTransformation (FR object)	116
11.2	Filters for FRObjcts	116
11.2.1	IsGroupFRMachine	116
11.2.2	IsFRMachineStrRep	116
11.2.3	IsMealyMachine	116
11.2.4	IsMealyElement	117
11.2.5	IsMealyMachineIntRep	117
11.2.6	IsMealyMachineDomainRep	117
11.2.7	IsVectorFRMachineRep	117
11.2.8	IsAlgebraFRMachineRep	117
11.2.9	IsLinearFRMachine	117
11.2.10	IsLinearFRElement	118
11.2.11	IsFRElement	118
11.2.12	IsFRObjct	118
11.2.13	IsFRMachine	118
11.2.14	IsInvertible	118
11.2.15	IsFRGroup	119
11.2.16	IsFRAlgebra	119
11.3	Some of the algorithms implemented	119
11.3.1	FRMachineRWS	119
11.3.2	Order of FR elements	119
11.3.3	Membership in semigroups	120
11.3.4	Order of groups	120
11.3.5	Images and preimages of some groups in f.p. and l.p. groups	120
11.3.6	Comparison of FR, Mealy, vector, and algebra elements	121
11.3.7	Inverses of linear elements	121

12	Miscellanea	123
12.1	Helpers	123
12.1.1	maybe	123
12.1.2	ReturnMaybe	123
12.1.3	TensorSum	123
12.1.4	TensorProductX	123
12.1.5	DirectSum	123
12.1.6	PeriodicList	124
12.1.7	CompressPeriodicList	124
12.1.8	IsConfinal	125
12.1.9	ConfinalityClass	125
12.1.10	LargestCommonPrefix	125
12.1.11	WordGrowth	125
12.1.12	ShortGroupRelations	127
12.1.13	ShortGroupWordInSet	128
12.1.14	SurfaceBraidFpGroup	128
12.1.15	CharneyBraidFpGroup	128
12.1.16	ArtinRepresentation	129
12.1.17	StringByInt	129
12.1.18	PositionTower	129
12.1.19	CoefficientsInAbelianExtension	129
12.1.20	MagmaEndomorphismByImagesNC	129
12.1.21	MagmaHomomorphismByImagesNC	129
12.1.22	NewFIFO	130
12.1.23	ProductIdeal	130
12.1.24	DimensionSeries	130
12.1.25	Trans	131
12.2	User settings	131
12.2.1	InfoFR	131
12.2.2	FR_SEARCH	132

Chapter 1

Licensing

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program, in the file COPYING. If not, see <http://www.gnu.org/licenses/>.

Chapter 2

FR package

2.1 A brief mathematical introduction

This chapter assumes that you have no familiarity with groups generated by automata. If you do, and wish to see their usage within GAP through a sample session, please skip to Section 2.2. For a more thorough introduction on self-similar groups see [BGN03] or [BGŠ03].

We shall here be interested in groups G defined by their action on a regular rooted tree. Let X be a finite set; and let X^* denote the set of words (free monoid) over X . Then X^* naturally has the structure of a regular rooted tree: the root is the empty word, and vertex $v \in X^*$ is connected to vertex vx for all choices of $x \in X$. Each vertex except the root therefore has $\#X + 1$ neighbours.

Let W denote the automorphism group of the graph X^* . Given $a \in W$, we may restrict its action to $X \subset X^*$, and obtain a permutation π_a on X , called the *activity* of a . We may also obtain, for all $x \in X$, a tree automorphism $a_x \in W$, called the *state of a at x* , by the formula

$$(v)a_x = w \quad \text{if} \quad (xv)a = x^{\pi_a}w.$$

The data (a_x, π_a) determine uniquely the automorphism a , and any choice of a_x and π_a defines a tree isometry. We therefore have a group isomorphism

$$\phi : W \rightarrow W \wr \text{Sym}(X),$$

called the *Wreath recursion*. The image of ϕ is the permutational wreath product $W^X \rtimes \text{Sym}(X)$.

The state a_x should be interpreted as the restriction of the action of a on the subtree xX^* ; the automorphism a is defined by acting first on each of the subtrees of the form xX^* by its respective state, and then permuting these subtrees according to π_a . The wreath recursion can be iterated on the states of a , to define states a_v for any $v \in X^*$.

The automorphism $a \in W$ may be represented by a graph, as follows. There is one vertex for each state a_v of a , labeled π_{a_v} ; and for each $x \in X$ there is one edge from state a_v to state a_{vx} , labeled x . This graph is nothing but a quotient of the regular rooted tree X^* , where vertices v and w are identified if $a_v = a_w$. Again, this graph, with a choice of initial vertex, determines uniquely the automorphism a . It is called the *Mealy machine* associated with a .

Of particular interest are *finite-state automorphisms*: these are automorphisms whose Mealy machine has finitely many states. The product and inverse of finite-state automorphisms is again finite-state.

A subgroup $G \leq W$ is *self-similar* if $G^\phi \subset G \wr \text{Sym}(X)$. This is equivalent to asking, for every $a \in G$, that all of its states a_x also belong to G .

The following important properties have also been considered. A subgroup $G \leq W$ is *level-transitive* if its action is transitive on all the G -subsets X^n . It is *weakly branched* if it is level-transitive, and for every $v \in X^*$ there is a non-trivial $a_v \in G$ that fixes $X^* \setminus vX^*$. It is *branched* if furthermore for each $n \in \mathbb{N}$ the group generated by all such a_v for all v of length n has finite index in G .

A self-similar finitely generated group $G \leq W$ is *contracting* if there are constants $K, n \in \mathbb{N}$ and $\lambda < 1$ such that $|a_v| \leq \lambda|a| + K$ for all $a \in G$ and $v \in X^n$; here $|a|$ denotes the minimal number of generators needed to express a . It then follows that there exists a finite set $N \subset G$ such that for all $a \in G$, all but finitely many of the states of a belong to N . The minimal such N is called the *nucleus* of G . Since the states of elements of the nucleus are again in the nucleus, we see that the nucleus is naturally a Mealy machine. By considering all elements of W obtained from this Mealy machine by choosing all possible initial states, we obtain a generating set for G made of all states of a single machine; this is the *group generated* by the machine.

In this package, we are mainly interested in self-similar groups of finite-state automorphisms. The reason is historical: Aleshin [Ale83], and later Grigorchuk [Gri80] and Gupta and Sidki [GS83] constructed peculiar examples of groups using self-similar finite-state automorphisms. All these groups can be defined by drawing a small machine (at most five vertices) and considering the group that they generate.

We assumed for simplicity that the elements a were invertible. Actually, in the definition of Mealy machines it makes sense to accept arbitrary maps, and not necessarily bijections of X as a label at each vertex. One may in this way define peculiar semigroups.

2.2 An example session

This is a brief introduction describing some of the simpler features of the FR package. It assumes you have some familiarity with the theory of groups defined by automata; if not, a brief mathematical introduction may be found in Section 2.1. We show here and comment a typical use of the package.

The package is installed by unpacking the archive in the `pkg/` directory of your GAP installation. It can also be placed in a local directory, which must be added to the load-path by invoking `gap` with the `-l` option.

```

----- Example -----
gap> LoadPackage("fr");
-----
Loading FR 0.857142p5 (Functionally recursive and automata groups)
by Laurent Bartholdi (http://www.uni-math.gwdg.de/laurent)
-----
true

```

Many FR groups are predefined by FR, see Chapter 10. We consider here the *Basilica group*, considered in [GŻ02] and [BV05].

We may start by defining a group: it has two generators a and b , satisfying the specified recursions.

```

----- Example -----
gap> B := FRGroup("a=<1,b>(1,2)", "b=<1,a>:IsFRElement");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> AssignGeneratorVariables(B);
#I Assigned the global variables [ a, b ]

```

We have just created the group $B = \langle a, b \rangle$.

Note that this group is predefined as `BasilicaGroup`. We now compute the decompositions of the generators:

Example

```
gap> DecompositionOfFRElement(a); DecompositionOfFRElement(b);
[ [ <2|identity ...>, <2|b> ], (1,2) ]
[ [ <2|identity ...>, <2|a> ], () ]
```

Elements are described as words in the generators; they are printed as $\langle 2|a \rangle$, where the 2 reminds of the degree of the tree on which a acts.

The optional argument `IsFRElement` (11.2.11) tells FR to store elements in this way. This representation is always possible, but it is usually inefficient for calculations. The argument `IsMealyElement` (11.2.4) forces FR to use a more efficient representation, which in some cases may take an infinite time to set up. With no extra argument, FR does what it thinks is best.

Elements act on sequences over $\{1,2\}$. The action is computed in the standard manner:

Example

```
gap> 1^a; [1]^a; [1,1]^a;
2
[ 2 ]
[ 2, 1 ]
```

Periodic sequences are also implemented in FR; they are constructed by giving the period and preperiod. The period is printed by preceding it with a `"/`:

Example

```
gap> v := PeriodicList([1],[2]);
[ 1, / 2 ]
gap> v^a; v^(a^2);
[/ 2 ]
[/ 1, 2 ]
gap> last{[1..10]};
[ 1, 2, 1, 2, 1, 2, 1, 2, 1, 2 ]
```

Most computations are much more efficient if B 's elements are converted to *Mealy representation*,

Example

```
gap> Bm := Image(IsomorphismMealyGroup(B));
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> a := Bm.1; b := Bm.2;
<Mealy element on alphabet [ 1, 2 ] with 3 states, initial state 1>
<Mealy element on alphabet [ 1, 2 ] with 3 states, initial state 1>
```

This could have been done automatically by specifying `:IsMealyElement` as an option in the call to `FRGroup`.

The group B is torsion-free, and its elements are bounded automata. Although torsion-freeness is difficult to check for FR, it can be checked on individual elements:

Example

```
gap> IsBoundedFRSemigroup(Bm);
true
gap> Order(a); Order(b);
infinity
infinity
gap> g := PseudoRandom(B);; Length(InitialState(g));
4679
gap> Order(g); time;
infinity
2599
```

The group B is weakly branched; more precisely, the derived subgroup B' contains $B' \times B'$. To prove that, it suffices to check $[a, b] \times 1 \in B'$ and $1 \times [a, b] \in B'$. These elements are constructed using `VertexElement` (4.1.5):

Example

```
gap> c := Comm(a,b);
<Mealy element on alphabet [ 1, 2 ] with 9 states, initial state 1>
gap> K := NormalClosure(Bm, Group(c));
<self-similar group over [ 1 .. 2 ] with 3 generators>
gap> VertexElement(1,c) in K; VertexElement(1,c) in K;
true
true
gap> DecompositionOfFRElement(VertexElement(1,c)=[c, One(Bm)], ());
true
gap> VertexElement(2,c)=Comm(b, a^2);
true
```

Note that we had to guess the form of the element `VertexElement(2,c)` above. This could have been found out by GAP using `ShortGroupWordInSet` (12.1.13).

We may also check the relations $[b^p, (b^p)^{a^p}] = 1$ and $[a^{2p}, (a^{2p})^{b^p}]$ for p any power of 2:

Example

```
gap> ForAll([0..10], i->IsOne(Comm(b^(2^i), (b^(2^i))^(a^(2^i))))); time;
true
1361
```

Since the group B is bounded, it is contracting. We compute its nucleus:

Example

```
gap> NucleusOfFRSemigroup(B);
[ <2|identity ...>, <2|b>, <2|b^-1>, <2|a>, <2|a^-1>, <2|b^-1*a>, <2|a^-1*b> ]
```

We then compute the Mealy machine with stateset this nucleus, and draw it graphically (this requires the external programs `graphviz` and `imagemagick`):

Example

```
gap> N := NucleusMachine(B);
<Mealy machine on alphabet [ 1, 2 ] with 7 states>
gap> Draw(N);
```

We may also draw powers of the dual automaton: these are approximations to the Schreier graph of B . However, we also construct a smaller Mealy machine with states only a and b , which give better images:

Example

```
gap> Draw(DualMachine(N)^3);
gap> M := AsMealyMachine(FRMachine(a))[1];
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> Draw(DualMachine(M)^4);
```

These Schreier graphs are orbits of the group; they can be displayed as follows:

Example

```
gap> WordGrowth(B:point:=[1,1,1,1], draw);
```

More properties of B can be checked, or experimented with, on its finite quotients obtained by truncating the tree on which B acts at a given length. `PermGroup(B,n)` constructs a permutation group which is the natural quotient of B acting on 2^n points:

Example

```
gap> G := PermGroup(B,7);
<permutation group with 2 generators>
gap> Size(G); LogInt(last,2);
309485009821345068724781056
88
```

We may "guess" the structure of the Lie algebra of B by examining the ranks of the successive quotients along its Jennings series:

Example

```
gap> J := JenningsLieAlgebra(G); time;
<Lie algebra of dimension 88 over GF(2)>
18035
gap> List([1..15], i->Dimension(Grading(J).hom_components(i)));
[ 2, 3, 1, 4, 1, 2, 1, 4, 1, 2, 1, 3, 1, 2, 1 ]
```

The "4" in position 8 of that list should really be a "5"; computations on finite quotients of B usually give lower bounds for invariants of B . In that case, we guess that the ranks behave like a "ruler" function, i.e. that the rank of the homogeneous component of degree i is $2 + v_2(i)$ if i is a power of 2 and is $1 + v_2(i)$ otherwise; here $v_2(i)$ is the number of times 2 divides i .

Chapter 3

Functionally recursive machines

At the core of this package are *functionally recursive machines*. The internals of machine will be described later, but each machine M has an associated *alphabet* X , a *set of states* Q , and a *transition function* $\phi : Q \times X \rightarrow X \times Q$. An *element*, as we will see in Section 4, is given by a machine and an initial state $q \in Q$.

The element (M, q) defines a transformation on the set X^* of strings (finite or infinite) over the alphabet X , as follows: the empty string is always fixed. Given a string $x_1x_2 \dots x_n$ with $n \geq 0$, compute $\phi(q, x_1) = (y_1, r)$; then compute the action of (M, r) on the string $x_2 \dots x_n$, and call the result $y_2 \dots y_n$. Then the action of (M, q) on $x_1x_2 \dots x_n$ yields $y_1y_2 \dots y_n$.

This can be understood more formally as follows. The transition function ϕ induces a map $\phi^n : Q \times X^n \rightarrow X^n \times Q$, defined by successively applying ϕ to move the Q from the left to the right. Similarly, ϕ can be extended to a map $Q^m \times X^n \rightarrow X^n \times Q^m$.

We see that the action on finite strings preserves their length, and also preserves prefixes: if (M, q) maps $x_1 \dots x_n$ to $y_1 \dots y_m$, then necessarily $m = n$; and if $k < n$ then T maps $x_1 \dots x_k$ to $y_1 \dots y_k$.

The strings over the alphabet X can be naturally organised into a rooted tree. The root represents the empty string, and the strings $x_1 \dots x_n$ and $x_1 \dots x_{n+1}$ are connected by an edge, for all $x_i \in X$.

3.1 Types of machines

Machines must be accessible to computation; therefore it is reasonable to assume that their alphabet X is finite.

If the stateset Q is also finite, the machine is called a *Mealy machine*, and its transition function ϕ can be stored as a table.

More general machines are obtained if one allows the stateset Q to be a free group/semigroup/monoid generated by a finite set S , and the transition function ϕ to be specified on $S \times X$. Its values are then extended naturally by composition.

Machines store their transitions (second coordinate of ϕ), and their output, (first coordinate of ϕ) in a matrix indexed by state and letter. In particular, `PermList(output[state])` gives the action on the first level.

Because of the way GAP handles permutations and transformations, a permutation is never equal to a transformation, even though both can answer `true` to `IsOne`. Therefore, FR introduces a new type of transformation, which can be equal to a permutation, and which is actually represented as a permutation is it is invertible. Like permutations, the new transformations do not have a fixed degree. They are created by `Trans(list)`.

3.2 Products of machines

Machines can be combined in different manners. If two machines act on the same alphabet, then their *sum* and *product* are defined as machines acting again on the same alphabet; the statesets are the free products (which is also their sum, in the category of semigroups) of the respective statesets. The sum or product of machines has a stateset of highest possible category, i.e. is a group unless some argument is a monoid, and a monoid unless some argument is a semigroup. The transition and output functions are the union of the respective functions of their arguments.

If a non-empty collection of machines have same stateset, then their *tensor sum* and *tensor product* are machines again with same stateset; the alphabets on which the machines act are the disjoint union, respectively cartesian product, of the arguments' alphabets. The transition and output functions are again the union or composition of the respective functions of their arguments.

The *direct sum* and *direct product* of a collection of machines are always defined. Its stateset is generated by the union of the arguments' statesets, as for a sum or a product; its alphabet is the disjoint union, respectively cartesian product of its arguments' alphabets, as for a tensor sum or product. The transition and output functions are again the union of the respective functions of their arguments.

3.3 Creators for FRMachines

3.3.1 FRMachineNC (family,free,listlist,list)

◇ `FRMachineNC(fam, free, transitions, outputs)` (operation)

Returns: A new FR machine.

This function constructs a new FR machine, belonging to family *fam*. It has stateset the free group/semigroup/monoid *free*, and transitions described by *states* and *outputs*.

transitions is a list of lists; *transitions*[*s*][*x*] is a word in *free*, which is the state reached by the machine when started in state *s* and fed input *x*.

outputs is also a list of lists; *outputs*[*s*][*x*] is the output produced by the machine is in state *s* and inputs *x*.

Example

```
gap> f := FreeGroup(2);
<free group on the generators [ f1, f2 ]>
gap> m := FRMachineNC(FRMFamily([1,2]),f,[[One(f),f.1],[One(f),f.2^-1]],
[[2,1],[1,2]]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1, f2 ] )>
```

3.3.2 FRMachine ([list,]list,list)

◇ `FRMachine([names,]transitions, outputs)` (operation)

◇ `FRMachine(free, transitions, outputs)` (operation)

Returns: A new FR machine.

This function constructs a new FR machine. It has stateset a free group/semigroup/monoid, and structure described by *transitions* and *outputs*.

If there is an argument *free*, it is the free group/monoid/semigroup to be used as stateset. Otherwise, the stateset will be guessed from the *transitions* and *outputs*; it will be a free group if all states are invertible, and a monoid otherwise. *names* is then an optional list, with at position *s* a string naming generator *s* of the stateset. If *names* contains too few entries, they are completed by the names `--1, --2, . . .`.

transitions is a list of lists; *transitions*[*s*][*x*] is either an associative word, or a list of integers describing the state reached by the machine when started in state *s* and fed input *x*. Positive integers indicate a generator index, negative integers its inverse, the empty list in the identity state, and lists of length greater than one indicate a product of states. If an entry is an FR element, then its machine is incorporated into the newly constructed one.

outputs is a list; at position *s* it contains a permutation, a transformation, or a list of integers (the images of a transformation), describing the activity of state *s*. If all states are invertible, the outputs are all converted to permutations, while if there is a non-invertible state then the outputs are all converted to transformations.

Example

```
gap> n := FRMachine(["tau", "mu"], [[[]], [1]], [[], [-2]], [(1,2), (1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ tau, mu ] )>
gap> m=n;
true
gap> Display(n);
      |      1      2
-----+-----+-----+
tau | <id>,2      tau,1
mu | <id>,2      mu^-1,1
-----+-----+-----+
gap> m := FRMachine([[], [FRElement(n,1)]]], [()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1, f2, f3 ] )>
gap> Display(m);
      |      1      2
-----+-----+-----+
f1 | <id>,1      f2,2
f2 | <id>,2      f2,1
f3 | <id>,2      f1^-1,1
-----+-----+-----+
gap> f := FreeGroup(2);
<free group on the generators [ f1, f2 ]>
gap> p := FRMachine(f, [[One(f), f.1], [One(f), f.2^-1], [(1,2), (1,2)]]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1, f2 ] )>
gap> n=p;
true
```

3.3.3 UnderlyingFRMachine

◇ UnderlyingFRMachine(*obj*)

(attribute)

Returns: An FR machine underlying *obj*.

FR elements, FR groups etc. often have an underlying FR machine, which is returned by this command.

Example

```
gap> m := FRMachine(["a", "b"], [[[]], [2]], [[], [1]], [(1,2), ()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ a, b ] )>
gap> a := FRElement(m,1); b := FRElement(m,2);
<2|a>
<2|b>
gap> UnderlyingFRMachine(a)=m;
true
```

3.3.4 AsGroupFRMachine

◇ AsGroupFRMachine(*m*) (attribute)

◇ AsMonoidFRMachine(*m*) (attribute)

◇ AsSemigroupFRMachine(*m*) (attribute)

Returns: An FR machine isomorphic to *m*, on a free group.

This function constructs, from the FR machine *m*, an isomorphic FR machine *n* with a free group/monoid/semigroup as stateset. The attribute Correspondence(*n*) is a mapping (homomorphism or list) from the stateset of *m* to the stateset of *n*.

Example

```
gap> s := FreeSemigroup(1);;
gap> sm := FRMachine(s, [[GeneratorsOfSemigroup(s)[1],
                           GeneratorsOfSemigroup(s)[1]^2]], [(1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Semigroup( [ s1 ] )>
gap> m := FreeMonoid(1);;
gap> mm := FRMachine(m, [[One(m), GeneratorsOfMonoid(m)[1]^2]], [(1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Monoid( [ m1 ], ... )>
gap> g := FreeGroup(1);;
gap> gm := FRMachine(g, [[One(g), GeneratorsOfGroup(g)[1]^2]], [(1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1 ] )>
gap> AsGroupFRMachine(sm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1 ] )>
      |      1      2
-----+-----+-----+
      f1 | f1,2    f1^2,1
-----+-----+-----+
gap> Correspondence(last);
MappingByFunction( <free semigroup on the generators
[ s1 ]>, <free group on the generators [ f1 ]>, function( w ) ... end )
gap> AsGroupFRMachine(mm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1 ] )>
      |      1      2
-----+-----+-----+
      f1 | <id>,2    f1^2,1
-----+-----+-----+
gap> AsGroupFRMachine(gm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1 ] )>
      |      1      2
-----+-----+-----+
      f1 | <id>,2    f1^-2,1
-----+-----+-----+
gap> AsMonoidFRMachine(sm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Monoid( [ m1 ], ... )>
      |      1      2
-----+-----+-----+
      m1 | m1,2    m1^2,1
-----+-----+-----+
gap> AsMonoidFRMachine(mm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Monoid( [ m1 ], ... )>
      |      1      2
-----+-----+-----+
      m1 | <id>,2    m1^2,1
-----+-----+-----+
```

```

gap> AsMonoidFRMachine(gm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Monoid( [ m1, m2 ], ... )>
  |      1      2
  ----+-----+-----+
m1 | <id>,2    m2^2,1
m2 | m1^2,2    <id>,1
  ----+-----+-----+
gap> AsSemigroupFRMachine(sm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Semigroup( [ s1 ] )>
  |      1      2
  ----+-----+-----+
s1 | s1,2     s1^2,1
  ----+-----+-----+
gap> AsSemigroupFRMachine(mm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Semigroup( [ s1, s2 ] )>
  |      1      2
  ----+-----+-----+
s1 | s2,2     s1^2,1
s2 | s2,1     s2,2
  ----+-----+-----+
gap> AsSemigroupFRMachine(gm); Display(last);
<FR machine with alphabet [ 1 .. 2 ] on Semigroup( [ s1, s2, s3 ] )>
  |      1      2
  ----+-----+-----+
s1 | s3,2     s2^2,1
s2 | s1^2,2    s3,1
s3 | s3,1     s3,2
  ----+-----+-----+
gap>
gap> Display(GuptaSidkiMachines(3));
  |      1      2      3
  ----+-----+-----+
a | a,1     a,2     a,3
b | a,2     a,3     a,1
c | a,3     a,1     a,2
d | b,1     c,2     d,3
  ----+-----+-----+
gap> AsGroupFRMachine(GuptaSidkiMachines(3));
<FR machine with alphabet [ 1 .. 3 ] on Group( [ f1, f2 ] )>
gap> Display(last);
  |      1      2      3
  ----+-----+-----+
f1 | <id>,2    <id>,3    <id>,1
f2 | f1,1     f1^-1,2    f2,3
  ----+-----+-----+
gap> Correspondence(last);
[ <identity ...>, f1, f1^-1, f2 ]

```

3.3.5 ChangeFRMachineBasis

◇ ChangeFRMachineBasis($m[, l]$)

(attribute)

Returns: An equivalent FR machine, in a new basis.

This function constructs a new group FR machine, given a group FR machine m and a list of states l (as elements of the free object `StateSet(m)`).

The new machine has the following transitions: if alphabet letter a is mapped to b by state s in m , leading to state t , then in the new machine the new state is $l[a]^{-1} * t * l[b]$.

The group generated by the new machine is isomorphic to the group generated by m . This command amounts to a change of basis of the associated bimodule (see [Nek05, Section 2.2]). It amounts to conjugation by the automorphism $c = \text{FRElement}("c", [l[1]*c, \dots, l[n]*c], [()], 1)$.

If the second argument is absent, this command attempts to choose one that makes many entries of the recursion trivial.

Example

```
gap> n := FRMachine(["tau", "mu"], [[[]], [1]], [[[]], [-2]], [(1,2), (1,2)]);
gap> Display(n);
  G   |      1      2
-----+-----+-----+
tau | <id>,2      tau,1
mu  | <id>,2      mu^-1,1
-----+-----+-----+
gap> nt := ChangeFRMachineBasis(n, GeneratorsOfFRMachine(n) {[1,1]});
gap> Display(nt);
  G   |      1      2
-----+-----+-----+
tau | <id>,2      tau,1
mu  | <id>,2      tau^-1*mu^-1*tau,1
-----+-----+-----+
```

3.4 Attributes for FRMachines

3.4.1 StateSet (FR machine)

◇ `StateSet(m)`

(attribute)

Returns: The set of states associated with m .

This function returns the stateset of m . It can be either a list (if the machine is of Mealy type), or a free group/semigroup/monoid (in all other cases).

Example

```
gap> n := FRMachine(["tau", "mu"], [[[]], [1]], [[[]], [-2]], [(1,2), (1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ tau, mu ] )>
gap> StateSet(n);
<free group on the generators [ tau, mu ]>
gap> StateSet(AsMealyMachine(n));
[ 1 .. 4 ]
```

3.4.2 GeneratorsOfFRMachine

◇ `GeneratorsOfFRMachine(m)`

(attribute)

Returns: The generating set of the stateset of m .

This function returns the generating set of the stateset of $machine$. If m is a Mealy machine, it returns the stateset.

Example

```
gap> n := FRMachine(["tau", "mu"], [[[]], [1]], [[[]], [-2]], [(1,2), (1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ tau, mu ] )>
```

```
gap> GeneratorsOfFRMachine(n);
[ tau, mu ]
```

3.4.3 Output (FR machine,state)

◇ **Output**(*m*, *s*)

(operation)

◇ **Output**(*m*, *s*, *x*)

(operation)

Returns: A transformation of *m*'s alphabet.

This function returns the transformation of *m*'s alphabet associated with state *s*. This transformation is returned as a list of images.

s is also allowed to be a list, in which case it is interpreted as the corresponding product of states.

In the second form, the result is actually the image of *x* under **Output**(*m*, *s*).

Example

```
gap> n := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]], [(1,2), ()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ a, b ] )>
gap> Output(n, [1,2]);
[2,1]
gap> Output(n, Product(GeneratorsOfFRMachine(n)));
[2,1]
```

3.4.4 Transition (FR machine,state,input)

◇ **Transition**(*m*, *s*, *i*)

(operation)

Returns: An element of *m*'s stateset.

This function returns the state reached by *m* when started in state *s* and fed input *i*. This input may be an alphabet letter or a sequence of alphabet letters.

Example

```
gap> n := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]], [(1,2), ()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ a, b ] )>
gap> Transition(n, [2,1], 2);
a*b
gap> Transition(n, Product(GeneratorsOfFRMachine(n))^2, 1);
a*b
```

3.4.5 WreathRecursion

◇ **WreathRecursion**(*machine*)

(attribute)

Returns: A function on the stateset of *machine*.

This function returns a function on *machine*'s stateset. This function, on receiving state *q* as input, returns a list. Its first entry is a list indexed by *machine*'s alphabet, with in position *x* the state *machine* would be in if it received input *x* when in state *q*. The second entry is the list of the permutation of *machine*'s alphabet induced by *q*.

WreathRecursion(*machine*)(*q*)[1][*a*] is equal to *Transition*(*machine*, *q*, *a*) and *WreathRecursion*(*machine*)(*q*)[2] is equal to *Output*(*machine*, *q*).

Example

```
gap> n := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]], [(1,2), ()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ a, b ] )>
gap> WreathRecursion(n)(GeneratorsOfFRMachine(n)[1]);
[ [ <identity ...>, b ], [2,1] ]
```

```
gap> WreathRecursion(n) (GeneratorsOfFRMachine(n) [2]);
[ [ <identity ...>, a ], [1,2] ]
```

3.5 Operations for FRMachines

3.5.1 StructuralGroup

◇ `StructuralGroup(machine)` (operation)

◇ `StructuralMonoid(machine)` (operation)

◇ `StructuralSemigroup(machine)` (operation)

Returns: A finitely presented group/monoid/semigroup capturing the structure of *machine*.

This function returns a finitely presented group/monoid/semigroup, with generators the union of the `AlphabetOfFRObject` (11.1.3) and `GeneratorsOfFRMachine` (3.4.2) of *machine*, and relations all $qa' = aq'$ whenever $\phi(q, a) = (a', q')$.

Example

```
gap> n := FRMachine(["a", "b", "c"], [[2], [3]], [[3], [2]], [[1], [1]], [(1,2), (1,2), ()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ a, b, c ] )>
gap> StructuralGroup(n);
<fp group on the generators [ a, b, c, 1, 2 ]>
gap> RelatorsOfFpGroup(last);
[ a*2*b^-1*1^-1, a*1*c^-1*2^-1, b*2*c^-1*1^-1,
  b*1*b^-1*2^-1, c*1*a^-1*1^-1, c*2*a^-1*2^-1 ]
gap> SimplifiedFpGroup(last2);
<fp group on the generators [ a, 1 ]>
gap> RelatorsOfFpGroup(last);
[ 1^-1*a^2*1^4*a^-2*1^-1*a*1^-2*a^-1, 1*a*1^-1*a*1^2*a^-1*1*a^-2*1^-3*a,
  1^-1*a^2*1^2*a^-1*1^-1*a*1^2*a^-2*1^-2 ]
```

3.5.2 \+

◇ `\+(machine1, machine2)` (method)

Returns: A new FR machine, in the same family as its arguments.

This function returns a new FR machine, with stateset generated by the union of the statesets of its arguments. The arguments *machine1* and *machine2* must operate on the same alphabet. If the stateset of *machine1* is free on n_1 letters and the stateset of *machine2* is free on n_2 letters, then the stateset of their sum is free on $n_1 + n_2$ letters, with the first n_1 identified with *machine1*'s states and the next n_2 with *machine2*'s.

The transition and output functions are naturally extended to the sum.

The arguments may be free groups, semigroups or monoid machines. The sum is in the weakest containing category: it is a group machine if both arguments are group machines; a monoid if both are either group or monoid machines; and a semigroup machine otherwise.

The maps from the stateset of *machine1* or *machine2* to the stateset of the result *r* can be recovered as `Correspondence(r) [1]` and `Correspondence(r) [2]`; see `Correspondence` (3.5.11).

Example

```
gap> tau := FRMachine([[], [1]], [(1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1 ] )>
gap> mu := FRMachine([[], [-1]], [(1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1 ] )>
```

```

gap> sum := tau+mu;; Display(sum);
      |      1      2
-----+-----+-----+
f11 | <id>,2      f11,1
f12 | <id>,2      f12^-1,1
-----+-----+-----+
gap> Correspondence(sum)[1];
[ f1 ] -> [ f11 ]
gap> GeneratorsOfFRMachine(tau)[1]^last;
f11

```

3.5.3 $\backslash*$

◇ $\backslash*(machine1, machine2)$

(method)

Returns: A new FR machine, in the same family as its arguments.

The product of two FR machines coincides with their sum, since the natural free object mapping to the product of the statesets is generated by the union of the statesets. See therefore $\backslash+$ (3.5.2).

3.5.4 TensorSumOp (FR Machines)

◇ $TensorSumOp(FR_machines, machine)$

(method)

Returns: A new FR machine on the disjoint union of the arguments' alphabets.

The tensor sum of FR machines with same stateset is defined as the FR machine acting on the disjoint union of the alphabets; if these alphabets are $[1..n1]$ up to $[1..nk]$, then the alphabet of their sum is $[1..n1+...+nk]$ and the transition functions are similarly concatenated.

The first argument is a list; the second argument is any element of that list, and is used only to improve the method selection algorithm.

Example

```

gap> m := TensorSum(AddingMachine(2), AddingMachine(3), AddingMachine(4));
AddingMachine(2) (+) AddingMachine(3) (+) AddingMachine(4)
gap> Display(m);
      |  1    2    3    4    5    6    7    8    9
-----+-----+-----+-----+-----+-----+-----+-----+
a | a,1  a,2  a,3  a,4  a,5  a,6  a,7  a,8  a,9
b | a,2  b,1  a,4  a,5  b,3  a,7  a,8  a,9  b,6
-----+-----+-----+-----+-----+-----+-----+-----+

```

3.5.5 TensorProductOp (FR Machines)

◇ $TensorProductOp(FR, machines, machine)$

(method)

Returns: A new FR machine on the cartesian product of the arguments' alphabets.

The tensor product of FR machines with same stateset is defined as the FR machine acting on the cartesian product of the alphabets. The transition function and output function behave as if a single letter, in the tensor product's alphabet, were a word (read from left to right) in the machines' alphabets.

The first argument is a list; the second argument is any element of that list, and is used only to improve the method selection algorithm.

Due to an overloading problem in the GAP library, the user-level command is temporarily renamed `TensorProductX`.

Example

```
gap> m := TensorProductX(AddingMachine(2), AddingMachine(3));
AddingMachine(2) (*) AddingMachine(3)
gap> Display(last);
```

	1	2	3	4	5	6
a	a, 1	a, 2	a, 3	a, 4	a, 5	a, 6
b	a, 4	a, 5	a, 6	a, 2	a, 3	b, 1

3.5.6 DirectSumOp (FR Machines)

◇ `DirectSumOp(FR, machines, machine)`

(method)

Returns: A new FR machine on the disjoint union of the arguments' alphabets.

The direct sum of FR machines is defined as the FR machine with stateset generated by the disjoint union of the statesets, acting on the disjoint union of the alphabets; if these alphabets are $[1..n_1]$ up to $[1..n_k]$, then the alphabet of their sum is $[1..n_1+\dots+n_k]$ and the output and transition functions are similarly concatenated.

The first argument is a list; the second argument is any element of that list, and is used only to improve the method selection algorithm.

Example

```
gap> m := DirectSum(AddingMachine(2), AddingMachine(3), AddingMachine(4));
AddingMachine(2) # AddingMachine(3) # AddingMachine(4)
gap> Display(m);
```

	1	2	3	4	5	6	7	8	9
a	a, 1	a, 2	a, 3	a, 4	a, 5	a, 6	a, 7	a, 8	a, 9
b	a, 2	b, 1	b, 3	b, 4	b, 5	b, 6	b, 7	b, 8	b, 9
c	c, 1	c, 2	a, 3	a, 4	a, 5	c, 6	c, 7	c, 8	c, 9
d	d, 1	d, 2	a, 4	a, 5	b, 3	d, 6	d, 7	d, 8	d, 9
e	e, 1	e, 2	e, 3	e, 4	e, 5	a, 6	a, 7	a, 8	a, 9
f	f, 1	f, 2	f, 3	f, 4	f, 5	a, 7	a, 8	a, 9	b, 6

3.5.7 DirectProductOp (FR Machines)

◇ `DirectProductOp(FR, machines, machine)`

(method)

Returns: A new FR machine on the cartesian product of the arguments' alphabets.

The direct product of FR machines is defined as the FR machine with stateset generated by the product of the statesets, acting on the product of the alphabets; if these alphabets are $[1..n_1]$ up to $[1..n_k]$, then the alphabet of their product is $[1..n_1*\dots*n_k]$ and the output and transition functions act component-wise.

The first argument is a list; the second argument is any element of that list, and is used only to improve the method selection algorithm.

Example

```
gap> m := DirectProduct(AddingMachine(2), AddingMachine(3));
AddingMachine(2) x AddingMachine(3)
gap> Display(last);
```

	1	2	3	4	5	6
a	a, 1	a, 2	a, 3	a, 4	a, 5	a, 6

a		a, 1	a, 2	a, 3	a, 4	a, 5	a, 6
b		a, 2	a, 3	b, 1	a, 5	a, 6	b, 4
c		a, 4	a, 5	a, 6	c, 1	c, 2	c, 3
d		a, 5	a, 6	b, 4	c, 2	c, 3	d, 1
---+-----+-----+-----+-----+-----+-----+							

3.5.8 TreeWreathProduct (FR machine)

◇ `TreeWreathProduct(m, n, x0, y0)`

(method)

Returns: A new FR machine on the cartesian product of the arguments' alphabets.

The *tree-wreath product* of two FR machines is a machine acting on the product of its arguments' alphabets X, Y , in such a way that many images of the first machine's states under conjugation by the second commute.

It is introduced (in lesser generality, and with small variations) in [Sid05], and may be described as follows: one takes two copies of the stateset of m , one copy of the stateset of n , and, if necessary, an extra identity state.

The first copy of m fixes the alphabet $X \times Y$; its state \tilde{s} has transitions to the identity except \tilde{s} at $(x0, y0)$ and s at $(*, y0)$ for any other $*$. The second copy of m is also trivial except that, on input $(x, y0)$, its state s goes to state s' with output $(x', y0)$ whenever s originally went, on input x , to state s' with output x' . This copy of m therefore acts only in the X direction, on the subtree $(X \times \{y0\})^\infty$, on subtrees below vertices of the form $(x0, y0)^t(x, y0)$.

A state t in the copy of n maps the input (x, y) to (x, y') and proceeds to state t' if $y = y0$, and to the identity state otherwise, when on input y the original machine mapped state t to output t' and output y' .

Example

gap> m := TreeWreathProduct(AddingMachine(2), AddingMachine(3), 1, 1);
AddingMachine(2)~AddingMachine(3)
gap> Display(last);
1 2 3 4 5 6
---+-----+-----+-----+-----+-----+-----+
a c, 2 c, 3 a, 1 c, 5 c, 6 c, 4
b c, 4 c, 2 c, 3 b, 1 c, 5 c, 6
c c, 1 c, 2 c, 3 c, 4 c, 5 c, 6
d d, 1 c, 2 c, 3 b, 4 c, 5 c, 6
---+-----+-----+-----+-----+-----+-----+

3.5.9 SubFRMachine

◇ `SubFRMachine(machine1, machine2)`

(operation)

Returns: Either fail or an embedding of the states of *machine2* in the states of *machine1*.

This function attempts to locate a copy of *machine2* in *machine1*. If it succeeds, it returns a homomorphism from the stateset of *machine2* into the stateset of *machine1*; otherwise it returns fail.

Example

gap> n := FRMachine(["tau", "mu"], [[[]], [1]], [[[]], [-2]], [(1, 2), (1, 2)]);
<FR machine with alphabet [1 .. 2] on Group([tau, mu])>
gap> tauinv := FRMachine([[1], []], [(1, 2)]);
<FR machine with alphabet [1 .. 2] on Group([f1])>

```
gap> SubFRMachine(n,tauinv);
[ f1 ] -> [ tau^-1 ]
```

3.5.10 Minimized (FR machine)

◇ **Minimized(*m*)**

(operation)

Returns: A minimized machine equivalent to *m*.

This function attempts to construct a machine equivalent to *m*, but with a stateset of smaller rank. Identical generators are collapsed to a single generator of the stateset; if *m* is a group or monoid machine then trivial generators are removed; if *m* is a group machine then mutually inverse generators are grouped. This function sets as `Correspondence(result)` a mapping between the stateset of *m* and the stateset of the result; see `Correspondence` (3.5.11).

Example

```
gap> n := FRMachine(["tau","mu"],[[[]],[1]],[[],[-2]],[(1,2),(1,2)]);
gap> m := FRMachine(["tauinv"],[[[1]],[[]]],[(1,2)]);
gap> sum := n+m+n;
<FR machine with alphabet [ 1 .. 2 ] on Group( [ tau1, mul, tauinv1, tau2, mu2 ] )>
gap> min := Minimized(sum);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ tau1, mul ] )>
gap> Correspondence(min);
[ tau1, mul, tauinv1, tau2, mu2 ] -> [ tau1, mul, tau1^-1, tau1, mul ]
```

3.5.11 Correspondence (FR machine)

◇ **Correspondence(*m*)**

(attribute)

Returns: A mapping between statesets of FR machines.

If a machine *m* was created as a minimized group/monoid/semigroup machine, then `Correspondence(m)` is a mapping between the stateset of the original machine and the stateset of *m*. See `Minimized` (3.5.10) for an example.

If *m* was created as a minimized Mealy machine, then `Correspondence(m)` is a list identifying, for each state of the original machine, a state of the new machine. If the original state is inaccessible, the corresponding list entry is unbound. See `Minimized` (5.2.2) for an example.

If *m* was created using `AsGroupFRMachine` (3.3.4), `AsMonoidFRMachine` (3.3.4), `AsSemigroupFRMachine` (3.3.4), or `AsMealyMachine` (5.2.18), then `Correspondence(m)` is a list or a homomorphism identifying for each generator of the original machine a generator, or word in the generators, of the new machine. It is a list if either the original or the final machine is a Mealy machine, and a homomorphism in other cases.

If *m* was created as a sum of two machines, then *m* has a mapping `Correspondence(m)[i]` between the stateset of machine *i*=1,2 and its own stateset. See `\+` (3.5.2) for an example.

Chapter 4

Functionally recursive elements

A *functionally recursive element* is given by a functionally recursive machine and an initial state q . Many functions for FR machines, which accept a state as an argument, apply to FR elements. In that case, no state is passed to the function.

The main function of FR elements is to serve as group/monoid/semigroup elements: they can be multiplied and divided, and they act naturally on sequences. They can also be tested for equality, and can be sorted.

FR elements are stored as free group/monoid/semigroup words. They are printed as $\langle n|w \rangle$, where n is the degree of their alphabet.

Equality of FR elements is tested as follows. Given FR elements (m, q) and (m, r) , we set up a "rewriting system" for m , which records a purported set of relations among states of m . We start by an empty rewriting system, and we always ensure that the rewriting system is reduced and shortlex-reducing. Then, to compare q and r , we first compare their activities. If they differ, the elements are distinct. Otherwise, we reduce q and r using the rewriting system. If the resulting words are graphically equal, then they are equal. Otherwise, we add the rule $q \rightarrow r$ or $r \rightarrow q$ to the rewriting system, and proceed recursively to compare coordinatewise the states of these reduced words. As a bonus, we keep the rewriting system to speed up future comparisons.

Efficient comparison requires lookup in sorted lists, aka "Sets". Given two FR elements x and y , we declare that $x < y$ if, for the shortlex-first sequence l such that $\text{Output}(\text{Transition}(x, l))$ and $\text{Output}(\text{Transition}(y, l))$ differ, the former is less than the latter (compared as lists). In fact, a single internal function compares x and y and returns $-1, 0, 1$ depending on whether $x < y$ or $x = y$ or $x > y$. It traverses, in breadth first fashion, the alphabet sequences, and stops either when provably $x = y$ or if different outputs appear.

4.1 Creators for FRElements

4.1.1 FRElementNC (family,free,listlist,list,assocword)

◇ `FRElementNC(fam, free, transitions, outputs, init)` (operation)

Returns: A new FR element.

This function constructs a new FR element, belonging to family *fam*. It has stateset the free group/semigroup/monoid *free*, and transitions described by *states* and *outputs*, and initial states *init*.

transitions is a list of lists; *transitions*[*s*][*x*] is a word in *free*, which is the state reached by the machine when started in state *s* and fed input *x*.

outputs is a list of lists; *outputs*[*s*][*x*] is a output letter of the machine when it receives input *x* in state *s*.

init is a word in *free*.

Example

```
gap> f := FreeGroup(2);
<free group on the generators [ f1, f2 ]>
gap> e := FRElementNC(FREFamily([1,2]), f, [[One(f), f.1], [One(f), f.2^-1]],
      [[2,1], [2,1]], f.1);
<2|f1>
```

4.1.2 FRElement ([list],list,list,list)

◇ *FRElement*([*names*,]*transitions*, *outputs*, *init*) (operation)

◇ *FRElement*(*free*, *transitions*, *outputs*, *init*) (operation)

Returns: A new FR element.

This function constructs a new FR element. It has *stateset* a free group/semigroup/monoid, structure described by *transitions* and *outputs*, and initial state *init*. If the *stateset* is not passed as argument *free*, then it is determined by *transitions* and *outputs*; it is a free group if all states are invertible, and a free monoid otherwise. In that case, *names* is an optional list; at position *s* it contains a string naming generator *s*.

transitions is a list of lists; *transitions*[*s*][*x*] is either an associative word, or a list of integers or FR elements describing the state reached by the machine when started in state *s* and fed input *x*. Positive integers indicate a generator, negative integers its inverse, the empty list in the identity state, and lists of length greater than one indicate a product of states. If an entry is an FR element, then its machine is incorporated into the newly constructed element.

outputs is a list; at position *s* it contains a permutation, a transformation, or a list of images, describing the activity of state *s*.

init is either an associative word, an integer, or a list of integers describing the initial state of the machine.

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]], [(1,2)], [1]);
<2|tau>
gap> tau1 := FRElement(["tau1"], [[[]], [2]], [[], [2]], [(1,2)], [1]);
<2|tau1>
gap> (tau/tau1)^2;
<2|tau1*tau2^-1*tau1*tau2^-1>
gap> IsOne(last);
true
```

Example

```
gap> f := FreeGroup("tau", "tau1");
<free group on the generators [ tau, tau1 ]>
gap> tau := FRElement(f, [[One(f), f.1], [One(f), f.1]], [(1,2), ()], f.1);
<2|tau>
gap> tau1 := FRElement(f, [[One(f), f.1], [One(f), f.1]], [(1,2), ()], f.2);
<2|tau1>
gap> (tau/tau1)^2;
<2|tau1*tau2^-1*tau1*tau2^-1>
```

```
gap> IsOne(last);
true
gap> tauX := FRElement(f, [[One(f), f.1], [One(f), f.1]], [(1,2), ()], 1);
gap> tauY := FRElement(f, [[One(f), f.1], [One(f), f.1]], [(1,2), ()], f.1);
gap> Size(Set([tau, tauX, tauY]));
1
```

4.1.3 FRElement (machine/element,list)

◇ FRElement(*m*, *q*) (operation)

Returns: A new FR element.

This function constructs a new FR element. If *m* is an FR machine, it creates the element (*m*, *q*) whose FRMachine is *m* and whose initial state is *q*.

If *m* is an FR element, this command creates an FR element with the same FR machine as *m*, and with initial state *q*.

Example

```
gap> m := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]], [(1,2), ()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ a, b ] )>
gap> a := FRElement(m, 1); b := FRElement(m, 2);
<2|a>
<2|b>
gap> Comm(b, b^a);
<2|b^-1*a^-1*b^-1*a*b*a^-1*b*a>
gap> IsOne(last);
true
gap> last2 := FRElement(m, [-2, -1, -2, 1, 2, -1, 2, 1]);
true
```

4.1.4 ComposeElement (elementcoll, perm)

◇ ComposeElement(*l*, *p*) (operation)

Returns: A new FR element.

This function constructs a new FR element. *l* is a list of FR elements, and *p* is a permutation, transformation or list. In that last case, the resulting element *g* satisfies $\text{DecompositionOfFRElement}(g) = [l, p]$.

If all arguments are Mealy element, the result is a Mealy element. Otherwise, it is a Monoid-FRElement.

Example

```
gap> m := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]], [(1,2), ()]);
gap> a := FRElement(m, 1); b := FRElement(m, 2);
<2|a>
<2|b>
gap> ComposeElement([b^0, b], (1,2));
<2|f1>
gap> last := a;
true
gap> DecompositionOfFRElement(last2);
[ [ <2|identity ...>, <2|f5> ], [ 2, 1 ] ]
```

4.1.5 VertexElement

◇ `VertexElement(v, e)`

(operation)

Returns: A new FR element.

This function constructs a new FR element. v is either an integer or a list of integers, and represents a vertex. e is an FR element. The resulting element acts on the subtree below vertex v as e acts on the whole tree, and fixes all other subtrees.

Example

```
gap> e := FRElement([[[]], [[]]], [(1,2)], [1]);
<2|f1>
gap> f := VertexElement(1,e);
gap> g := VertexElement(2,f);
gap> g = VertexElement([2,1],e);
true
gap> 1^e;
2
gap> [1,1]^f;
[ 1, 2 ]
gap> [2,1,1]^g;
[ 2, 1, 2 ]
```

4.1.6 DiagonalElement

◇ `DiagonalElement(n, e)`

(operation)

Returns: A new FR element.

This function constructs a new FR element. n is either an integer or a list of integers, representing a sequence of operations to be performed on e starting from the last.

`DiagonalElement(n, e)` is an element with trivial output, and with $e^{(-1)^i \text{binomial}(n,i)}$ in coordinate $i+1$ of the alphabet, assumed to be of the form $[1\dots d]$.

In particular, `DiagonalElement(0, e)` is the same as `VertexElement(1, e)`; `DiagonalElement(1, e)` is the commutator of `VertexElement(1, e)` with any cycle mapping 1 to 2; and `DiagonalElement(-1, e)` has a transition to e at all inputs.

Example

```
gap> e := FRElement([[[]], [], [1]], [(1,2,3)], [1]);
<3|f1>
gap> Display(e);
      |      1      2      3
----+-----+-----+-----+
f1 | <id>,2  <id>,3  f1,1
----+-----+-----+-----+
Initial state: f1
gap> Display(DiagonalElement(0,e));
      |      1      2      3
----+-----+-----+-----+
f1 |  f2,1  <id>,2  <id>,3
f2 | <id>,2  <id>,3  f2,1
----+-----+-----+-----+
Initial state: f1
gap> Display(DiagonalElement(1,e));
      |      1      2      3
----+-----+-----+-----+
```

```

f1 | f2,1 f2^-1,2 <id>,3
f2 | <id>,2 <id>,3 f2,1
-----+-----+-----+-----+
Initial state: f1
gap> Display(DiagonalElement(2,e));
| 1 2 3
-----+-----+-----+-----+
f1 | f2,1 f2^-2,2 f2,3
f2 | <id>,2 <id>,3 f2,1
-----+-----+-----+-----+
Initial state: f1
gap> Display(DiagonalElement(-1,e));
| 1 2 3
-----+-----+-----+-----+
f1 | f2,1 f2,2 f2,3
f2 | <id>,2 <id>,3 f2,1
-----+-----+-----+-----+
Initial state: f1
gap> DiagonalElement(-1,e)=DiagonalElement(2,e);
true
gap> Display(DiagonalElement([0,-1],e));
G | 1 2 3
-----+-----+-----+-----+
f1 | f2,1 <id>,2 <id>,3
f2 | f3,1 f3,2 f3,3
f3 | <id>,2 <id>,3 f3,1
-----+-----+-----+-----+
Initial state: f1
gap> Display(DiagonalElement([-1,0],e));
G | 1 2 3
-----+-----+-----+-----+
f1 | f2,1 f2,2 f2,3
f2 | f3,1 <id>,2 <id>,3
f3 | <id>,2 <id>,3 f3,1
-----+-----+-----+-----+
Initial state: f1

```

4.1.7 AsGroupFRElement

- ◇ AsGroupFRElement(e) (operation)
- ◇ AsMonoidFRElement(e) (operation)
- ◇ AsSemigroupFRElement(e) (operation)

Returns: An FR element isomorphic to m , with a free group/monoid/semigroup as stateset.

This function constructs, from the FR element e , an isomorphic FR element f with a free group/monoid/semigroup as stateset. e may be a Mealy, group, monoid or semigroup FR element.

Example

```

gap> e := AsGroupFRElement(FRElement(GuptaSidkiMachines(3),4));
<3|f1>
gap> Display(e);
G | 1 2 3
-----+-----+-----+-----+
f1 | f2,1 f2^-1,2 f1,3

```

```

f2 | <id>,2    <id>,3    <id>,1
-----+-----+-----+-----+
Initial state: f1
gap> e=FRElement(GuptaSidkiMachines(3),4);
#I \=: converting second argument to FR element
true

```

Example

```

gap> e := AsMonoidFRElement(FRElement(GuptaSidkiMachines(3),4));
<3|m1>
gap> Display(e);
M |      1      2      3
-----+-----+-----+
m1 |  m2,1    m3,2    m1,3
m2 |  <id>,2  <id>,3  <id>,1
m3 |  <id>,3  <id>,1  <id>,2
-----+-----+-----+
Initial state: m1
gap> e=FRElement(GuptaSidkiMachines(3),4);
#I \=: converting second argument to FR element
true

```

Example

```

gap> e := AsSemigroupFRElement(FRElement(GuptaSidkiMachines(3),4));
<3|s1>
gap> Display(e);
S |      1      2      3
-----+-----+-----+
s1 | s2,1    s3,2    s1,3
s2 | s4,2    s4,3    s4,1
s3 | s4,3    s4,1    s4,2
s4 | s4,1    s4,2    s4,3
-----+-----+-----+
Initial state: s1
gap> e=FRElement(GuptaSidkiMachines(3),4);
#I \=: converting second argument to FR element
true

```

4.2 Operations and Attributes for FRElements

4.2.1 Output (FR element)

◇ Output (e)

(operation)

Returns: A transformation of e 's alphabet.

This function returns the transformation of e 's alphabet, i.e. the action on strings of length 1 over the alphabet. This transformation is a permutation if *machine* is a group machine, and a transformation otherwise.

Example

```

gap> tau := FRElement(["tau"],[[[]],[1]],[(1,2)],[1]);
gap> Output(tau);
(1,2)
zap := FRElement(["zap"],[[[]],[1]],[[1,1]],[1]);

```

```
gap> Output (zap);
<1,1>
```

4.2.2 Activity

◇ `Activity(e[, l])` (operation)
 ◇ `ActivityInt(e[, l])` (operation)
 ◇ `ActivityTransformation(e[, l])` (operation)
 ◇ `ActivityPerm(e[, l])` (operation)

Returns: The transformation induced by e on the l th level of the tree.

This function returns the transformation induced by e on the l th level of the tree, i.e. on the strings of length l over e 's alphabet.

This set of strings is identified with the set $L = \{1, \dots, d^l\}$ of integers, where the alphabet of e has d letters. Changes of the first letter of a string induce changes of a multiple of d^{l-1} on the position in L , while changes of the last letter of a string induce changes of 1 on the position in L .

This command returns a permutation if e is invertible; and a transformations otherwise. In the second form, it returns the unique integer i such that the transformation e acts on $[1..Length(AlphabetOfFRObj(e))^n]$ as adding i in base $Length(alphabet(e))$, or fail if no such i exists.

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]], [(1,2)], [1]);;
gap> Output (tau); PermList (last)=Activity (tau);
[ 2, 1 ]
true
gap> Activity (tau,2); ActivityInt (tau,2);
(1,3,2,4)
1
gap> Activity (tau,3); ActivityInt (tau,3);
(1,5,3,7,2,6,4,8)
1
zap := FRElement(["zap"], [[1], []], [[1,1]], [1]);
<2|zap>
gap> Output (zap);
[ 1, 1 ]
gap> Activity (zap,3);
<1,1,1,2,1,2,3,4>
```

4.2.3 Transition (FR element,input)

◇ `Transition(e, i)` (operation)

Returns: An element of *machine*'s stateset.

This function returns the state reached by e when fed input i . This input may be an alphabet letter or a sequence of alphabet letters.

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]], [(1,2)], [1]);;
gap> Transition (tau,2);
tau
gap> Transition (tau, [2,2]);
tau
```

```
gap> Transition(tau^2, [2,2]);
tau
```

4.2.4 Portrait

◇ `Portrait(e, l)`

(operation)

◇ `PortraitInt(e, l)`

(operation)

Returns: A nested list describing the action of e .

This function returns a sequence of $l + 1$ lists; the i th list in the sequence is an $i - 1$ -fold nested list. The entry at position (x_1, \dots, x_i) is the transformation of the alphabet induced by e under vertex $x_1 \dots x_i$.

The difference between `Portrait` and `PortraitInt` is that the latter describes transformations are described as powers of the cycle $x \mapsto x + 1$, as for the function `ActivityInt` (4.2.2).

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]]], [(1,2)], [1]);;
gap> Portrait(tau, 0);
[ (1,2) ]
gap> Portrait(tau, 3);
[ (1,2), [ (), (1,2) ], [ [ (), () ], [ (), (1,2) ] ],
  [ [ [ (), () ], [ (), () ] ], [ [ (), () ], [ (), (1,2) ] ] ] ]
gap> PortraitInt(tau, 0);
[ ZmodpZObj(1,2) ]
gap> PortraitInt(tau, 3);
[ ZmodpZObj(1,2), [ZmodpZObj(0,2), ZmodpZObj(1,2)],
  [ [ZmodpZObj(0,2), ZmodpZObj(0,2)], [ZmodpZObj(0,2), ZmodpZObj(1,2)] ],
  [ [ [ZmodpZObj(0,2), ZmodpZObj(0,2)], [ZmodpZObj(0,2), ZmodpZObj(0,2)] ],
    [ [ZmodpZObj(0,2), ZmodpZObj(0,2)], [ZmodpZObj(0,2), ZmodpZObj(1,2)] ] ] ] ]
```

4.2.5 DecompositionOffRElement

◇ `DecompositionOffRElement(e[, n])`

(operation)

Returns: A list describing the action and transitions of e .

This function returns a list. The second coordinate is the action of e on its alphabet, see Output (4.2.1). The first coordinate is a list, containing in position i the FR element inducing the action of e on strings starting with i .

If a second argument n is supplied, the decomposition is iterated n times.

This FR element has same underlying machine as e , and initial state given by `Transition` (4.2.3).

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]]], [(1,2)], [1]);;
gap> DecompositionOffRElement(tau);
[ [ <2|identity ...>, <2|tau> ], [ 2, 1 ] ]
```

4.2.6 StateSet (FR element)

◇ `StateSet(e)`

(operation)

Returns: The set of states associated with e .

This function returns the stateset of e . If e is of Mealy type, this is the list of all states reached by e .

If e is of group/semigroup/monoid type, then this is the stateset of the underlying FR machine, and not the minimal set of states of e , which is computed with `States` (4.2.8).

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]]], [(1,2)], [1]);;
gap> StateSet(tau);
<free group on the generators [ tau ]>
```

4.2.7 State

◇ `State(e , v)`

(operation)

Returns: An FR element describing the action of e at vertex v .

This function returns the FR element with same underlying machine as e , acting on the binary tree as e acts on the subtree below v .

v is either an integer or a list. This function returns an FR element, but otherwise is essentially a call to `Transition` (4.2.3).

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]]], [(1,2)], [1]);;
gap> State(tau, 2);
<2|tau>
gap> State(tau, [2,2]);
<2|tau>
gap> State(tau^2, [2,2]);
<2|tau>
```

4.2.8 States

◇ `States(e)`

(operation)

Returns: A list of FR elements describing the action of e on all subtrees.

This function calls repeatedly `State` (4.2.7) to compute all the states of e ; it returns the smallest list of `FRElements` that is closed under the function `State` (4.2.7).

e may be either an FR element, or a list of FR elements. In the latter case, it amounts to computing the list of all states of all elements of the list e .

The ordering of the list is as follows. First come e , or all elements of e . Then come the states reached by e in one transition, ordered by the alphabet letter leading to them; then come those reached in two transitions, ordered lexicographically by the transition; etc.

Note that this function is not guaranteed to terminate. There is currently no mechanism that detects whether an FR element is finite state, so in fact this function terminates if and only if e is finite-state.

Example

```
gap> m := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]]], [(1,2), ()]);;
gap> a := FRElement(m, 1);; b := FRElement(m, 2);;
gap> States(a);
[ <2|a>, <2|identity ...>, <2|b> ]
gap> States(b);
[ <2|b>, <2|identity ...>, <2|a> ]
gap> States(a^2);
[ <2|a^2>, <2|b>, <2|identity ...>, <2|a> ]
```

4.2.9 FixedStates

◇ FixedStates(*e*)

(operation)

Returns: A list of FR elements describing the action of *e* at fixed vertices.

This function calls repeatedly State (4.2.7) to compute all the states of *e* at non-trivial fixed vertices.

e may be either an FR element, or a list of FR elements. In the latter case, it amounts to computing the list of all states of all elements of the list *e*.

The ordering of the list is as follows. First come *e*, or all elements of *e*. Then come the states reached by *e* in one transition, ordered by the alphabet letter leading to them; then come those reached in two transitions, ordered lexicographically by the transition; etc.

Note that this function is not guaranteed to terminate, if *e* is not finite-state.

Example

```
gap> m := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]], [(1, 2), ()]);;
gap> a := FRElement(m, 1);; b := FRElement(m, 2);;
gap> FixedStates(a);
[ ]
gap> FixedStates(b);
[ <2|identity ...>, <2|a> ]
gap> FixedStates(a^2);
[ <2|b>, <2|identity ...>, <2|a> ]
```

4.2.10 LimitStates

◇ LimitStates(*e*)

(operation)

Returns: A set of FR element describing the recurring actions of *e* on all subtrees.

This function computes the States (4.2.8) *S* of *e*, and then repeatedly removes elements that are not *recurrent*, i.e. that do not appear as states of elements of *S* on subtrees distinct from the entire tree; and then converts the result to a set.

As for States (4.2.8), *e* may be either an FR element, or a list of FR elements.

Note that this function is not guaranteed to terminate. It currently terminates if and only if States (4.2.8) terminates.

Example

```
gap> m := FRMachine(["a", "b"], [[[]], [2]], [[[]], [1]], [(1, 2), ()]);;
gap> a := FRElement(m, 1);; b := FRElement(m, 2);;
gap> LimitStates(a);
[ <2|a>, <2|identity ...>, <2|b> ]
gap> LimitStates(a^2);
[ <2|b>, <2|identity ...>, <2|a> ]
```

4.2.11 IsFiniteStateFRElement

◇ IsFiniteStateFRElement(*e*)

(property)

◇ IsFiniteStateFRMachine(*e*)

(property)

Returns: true if *e* is a finite-state element.

This function tests whether *e* is a finite-state element.

When applied to a Mealy element, it returns true.

Example

```
gap> m := GuptaSidkiMachines(3);; Display(m);
  | 1      2      3
---+-----+-----+-----+
a | a,1    a,2    a,3
b | a,2    a,3    a,1
c | a,3    a,1    a,2
d | b,1    c,2    d,3
---+-----+-----+-----+
gap> Filtered(StateSet(m), i->IsFiniteStateFRElement(FRElement(m,i)));
[ 1, 2, 3, 4 ]
gap> IsFiniteStateFRMachine(m);
true
```

4.2.12 InitialState

◇ InitialState(e)

(operation)

Returns: The initial state of an FR element.

This function returns the initial state of an FR element. It is an element of the stateset of the underlying FR machine of e .

Example

```
gap> n := FRElement(["tau", "mu"], [[[]], [1]], [[[]], [-2]], [(1,2), (1,2)], [1,2]);
<2|tau*mu>
gap> InitialState(n);
tau*mu
gap> last in StateSet(n);
true
```

4.2.13 \backslash^e (POW)

◇ $\backslash^e(e, v)$

(method)

Returns: The image of a vertex v under e .

This function accepts an FR element and a vertex v , which is either an integer or a list. It returns the image of v under the transformation e , in the same format (integer/list) as v .

The list v can be a periodic list (see [PeriodicList \(12.1.6\)](#)). In that case, the result is again a periodic list. The computation will succeed only if the states along the period are again periodic.

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]], [(1,2)], [1]);;
gap> 1^tau;
2
gap> [1,1]^tau;
[ 2, 1 ]
gap> [2,2,2]^tau;
[ 1, 1, 1 ]
gap> List([0..5], i->PeriodicList([], [2])^(tau^i));
[ [/ 2 ], [/ 1 ], [ 2, / 1 ], [ 1, 2, / 1 ], [ 2, 2, / 1 ],
  [ 1, 1, 2, / 1 ] ]
```

4.2.14 $\backslash*$ (PROD)

$\diamond \backslash*(m, n)$

(method)

Returns: The product of the two FR elements m and n .

This function returns a new FR element, which is the product of the FR elements m and n .

In case m and n have the same underlying machine, this is the machine of the result. In case the machine of n embeds in the machine of m (see `SubFRMachine` (3.5.9)), the machine of the product is the machine of m . In case the machine of m embeds in the machine of n , the machine of the product is the machine of n . Otherwise the machine of the product is the product of the machines of m and n (See $\backslash*$ (3.5.3)).

Example

```
gap> tau := FRElement(["tau"], [[[]], [1]]], [(1,2)], [1]);;
gap> tau*tau; tau^2;
<2|tau^2>
<2|tau^2>
gap> [2,2,2]^(tau^2);
[ 2, 1, 1 ]
```

4.2.15 $\backslash[\backslash]$ (ELMLIST)

$\diamond \backslash[\backslash](m, i)$

(method)

$\diamond \backslash\{\backslash\}(m, l)$

(method)

Returns: A [list of] FR element[s] with initial state i .

These are respectively synonyms for `FRElement(m, i)` and `List(l, s->FRElement(m, s))`. The argument m must be an FR machine, i must be a positive integer, and l must be a list.

Chapter 5

Mealy machines and elements

Mealy machines form a special class of FR machines. They have as stateset a finite set, as opposed to a free group/monoid/semigroup. All commands available for FR machines are also available for Mealy machines, but the latter have added functionality.

There are currently two types of Mealy machines; one has as stateset an interval of integers of the form $[1..m]$ and as alphabet a set of integers; the other has an arbitrary domain as stateset and alphabet. Almost no functionality is implemented for the latter type, but there is a function converting it to the former type (see `AsMealyMachine` (5.2.18)).

The internal representation of a Mealy machine of the first kind is quite different from that of FR machines. The alphabet is assumed to be an interval $[1..n]$, and the stateset is assumed to be an interval $[1..m]$. The transitions are stored as a $m \times n$ matrix, and the outputs are stored in a list of length m , consisting of permutations or transformations.

Mealy machines have additional properties, in particular they can act on periodic sequences (see `PeriodicList` (12.1.6)). For example, the periodic sequence `PeriodicList([1], [1,2])` describes the infinite ray $[1, 1, 2, 1, 2, \dots]$ in the tree. In principle, Mealy machines could act on sequences accepted by an automaton, although this is not yet implemented.

Mealy elements are Mealy machines with an initial state. For efficiency reasons, Mealy elements are always minimized, and their states are ordered in a canonical top-down, left-to-right order of traversal of the tree. In particular, their initial state is always 1. In this implementation, multiplication of Mealy elements is slower than multiplication of group FR elements, while comparison of Mealy elements is faster than comparison of group FR elements. In practise, it is better to work with Mealy elements as often as possible.

Products of Mealy machines behave in the same way as products of general FR machines, see 3.2. The only difference is that now the sum and products of statesets are distinct; the sum of statesets being their disjoint union, and their product being their cartesian product.

5.1 Creators for MealyMachines and MealyElements

5.1.1 MealyMachine ([list],listlist,list)

◇ `MealyMachine([alphabet,]transitions, output)` (operation)

◇ `MealyElement([alphabet,]transitions, output, init)` (operation)

Returns: A new Mealy machine/element.

This function constructs a new Mealy machine or element, of integer type.

transitions is a list of lists; *transitions*[*s*][*x*] is an integer, which is the state reached by the machine when started in state *s* and fed input *x*.

output is a list; at position *s* it contains a permutation, a transformation describing the activity of state *s*, or a list describing the images of the transformation.

alphabet is an optional domain given as first argument; When present, it is assumed to be a finite domain, mapped bijectively to $[1..n]$ by its enumerator. The indices "[*s*]" above are then understood with respect to this enumeration.

init is an integer describing the initial state the newly created Mealy element should be in.

Example

```
gap> b := MealyMachine([[3,2],[3,1],[3,3]],[(1,2),(),()]);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> Display(b);
  | 1      2
---+-----+-----+
a | c,2    b,1
b | c,1    a,2
c | c,1    c,2
---+-----+-----+
gap> n := MealyMachine(Domain([11,12]),[[3,2],[3,1],[3,3]],[(1,2),(),()]);
<Mealy machine on alphabet [ 11, 12 ] with states [ 1 .. 3 ]>
gap> Display(n);
  | 11     12
---+-----+-----+
a | c,12   b,11
b | c,11   a,12
c | c,11   c,12
---+-----+-----+
```

Example

```
gap> tau := MealyElement([[2,1],[2,2]],[(1,2),(),1],1);
<Mealy machine on alphabet [ 1, 2 ] with 2 states, initial state 1>
gap> Display(tau);
  | 1      2
---+-----+-----+
a | b,2    a,1
b | b,1    b,2
---+-----+-----+
Initial state:  a
gap> [1,1]^tau; [[1]]^tau; [[2]]^tau;
[ 2, 1 ]
[ 2, [ 1 ] ]
[ [ 1 ] ]
```

5.1.2 MealyMachine (domain,domain,function,function)

◇ MealyMachine(*stateset*, *alphabet*, *transitions*, *output*) (operation)

◇ MealyElement(*stateset*, *alphabet*, *transitions*, *output*, *init*) (operation)

Returns: A new Mealy machine/element.

This function constructs a new Mealy machine or element, of domain type.

stateset and *alphabet* are domains; they are not necessarily finite.

transitions is a function; it takes as arguments a state and an alphabet letter, and returns a state.

output is either a function, accepting as arguments a state and a letter, and returning a letter.

init is an element of *stateset* describing the initial state the newly created Mealy element should be in.

Example

```
gap> g := Group((1,2));; n := MealyMachine(g,g,\*,\*);
<Mealy machine on alphabet [ (), (1,2) ] with states Group( [ (1,2) ] )>
gap> [(1,2),()]^FRElement(n,());
[ (1,2), (1,2) ]
gap> a := MealyElement(g,g,\*,\*,());
<Mealy machine on alphabet [ (), (1,2) ] with states Group(
[ (1,2) ] ), initial state ()>
gap> [(1,2),()]^a;
[ (1,2), (1,2) ]
```

5.1.3 MealyMachineNC (family,listlist,list)

◇ MealyMachineNC(*fam*, *transitions*, *output*) (operation)

◇ MealyElementNC(*fam*, *transitions*, *output*, *init*) (operation)

Returns: A new Mealy machine/element.

This function constructs a new Mealy machine or element, of integer type. No tests are performed to check that the arguments contain values within bounds, or even of the right type (beyond the simple checking performed by GAP's method selection algorithms). In particular, Mealy elements are always assumed to be minimized, but these functions leave this task to the user.

fam is the family to which the newly created Mealy machine will belong.

transitions is a list of lists; *transitions*[*s*][*x*] is an integer, which is the state reached by the machine when started in state *s* and fed input *x*.

output is a list; at position *s* it contains a permutation or a transformation describing the activity of state *s*.

init is an integer describing the initial state the newly created Mealy element should be in.

Example

```
gap> taum := MealyMachine([[2,1],[2,2]],[(1,2),()]);
<Mealy machine on alphabet [ 1, 2 ] with 2 states>
gap> tauminv := MealyMachineNC(FamilyObj(taum),[[1,2],[2,2]],[(1,2),()]);
<Mealy machine on alphabet [ 1, 2 ] with 2 states>
gap> tau := MealyElement([[2,1],[2,2]],[(1,2),()],1);
<Mealy machine on alphabet [ 1, 2 ] with 2 states, initial state 1>
gap> tauinv := MealyElementNC(FamilyObj(n),[[1,2],[2,2]],[(1,2),()],1);
<Mealy machine on alphabet [ 1, 2 ] with 2 states, initial state 1>
gap> tau=FRElement(taum,1); tauinv=FRElement(tauminv,1);
true
true
gap> IsOne(tau*tauinv);
true
```

5.1.4 AllMealyMachines

◇ AllMealyMachines(*m*, *n*[, *filters*]) (function)

Returns: A list of all Mealy machines with specified properties.

This function constructs all mealy with alphabet $[1..m]$, stateset $[1..n]$ and specified properties.

These properties are specified as additional arguments. They can include `IsInvertible` (11.2.14), `IsReversible` (5.2.4), `IsBireversible` (5.2.7), and `IsMinimized` (5.2.5) to specify that the machines should have that property.

A group/monoid/semigroup p may also be passed as argument; this specifies the allowable vertex transformations of the machines. The property `IsTransitive` requires that the state-closed group/monoid/semigroup of the machine act transitively on its alphabet, and `IsSurjective` requires that its `VertexTransformationsFRMachine` (5.2.15) be precisely equal to p .

The argument `EquivalenceClasses` returns one isomorphism class of Mealy machine, under the permutations of the stateset and alphabet.

The following example constructs the two Mealy machines `AleshinMachine` (10.1.14) and `BabyAleshinMachine` (10.1.15):

Example

```
gap> l := AllMealyMachines(2,3,IsBireversible,IsSurjective,EquivalenceClasses);;
gap> Length(l);
20
gap> Filtered(l,x->VertexTransformationsFRMachine(DualMachine(x))=SymmetricGroup(3)
> and Size(StateSet(Minimized(x)))=3);
[ <Mealy machine on alphabet [ 1, 2 ] with 3 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 3 states> ]
gap> Display(last[1]);
  | 1      2
---+-----+-----+
a | a,1    b,2
b | c,2    c,1
c | b,1    a,2
---+-----+-----+
gap> Display(last[2]);
  | 1      2
---+-----+-----+
a | a,2    b,1
b | c,1    c,2
c | b,2    a,1
---+-----+-----+
```

5.2 Operations and Attributes for MealyMachines and MealyElements

5.2.1 Draw

◇ `Draw(m[, filename])`

(operation)

This function creates a graph description of the Mealy machine/element m . If a second argument `filename` is present, the graph is saved, in dot format, under that filename; otherwise it is converted to Postscript using the program `dot` from the graphviz package, and is displayed in a separate X window using the program `display`. This works on UNIX systems.

A circle is displayed for every state of m , and there is an edge for every transition in m . It has label of the form x/y , where x is the input symbol and y is the corresponding output. Edges are coloured

according to the input symbol, in the order "red", "blue", "green", "gray", "yellow", "cyan", "orange", "purple". If m has an initial state, it is indicated as a doubly circled state.

If m is a FR machine, `Draw` first attempts to convert it to a Mealy machine (see `AsMealyMachine` (5.2.18)).

It is assumed, but not checked, that `graphviz` and `display` are properly installed on the system.

5.2.2 Minimized (Mealy machine)

◇ `Minimized(m)`

(operation)

Returns: A minimized machine equivalent to m .

This function constructs the minimized Mealy machine r corresponding to m , by identifying isomorphic states; and, if m is initial, by removing inaccessible states.

If m is initial, the minimized automaton is such that its states are numbered first by distance to the initial state, and then lexicographically by input letter. (in particular, the initial state is 1). This makes comparison of minimized automata efficient.

Furthermore, `Correspondence(r)` is a list describing, for each (accessible) state of m , its corresponding state in r ; see `Correspondence` (3.5.11).

```

Example
gap> GrigorchukMachine := MealyMachine([[2,3],[4,4],[2,5],[4,4],[4,1]],
                                         [(),(1,2),(),(),()]);
<Mealy machine on alphabet [ 1, 2 ] with 5 states>
gap> g2 := GrigorchukMachine^2;
<Mealy machine on alphabet [ 1, 2 ] with 25 states>
gap> Minimized(g2);
<Mealy machine on alphabet [ 1, 2 ] with 11 states, minimized>
gap> Correspondence(last);
[ 2, 1, 4, 11, 9, 1, 2, 5, 7, 6, 4, 3, 2, 9, 11, 11, 10, 9, 2, 4, 9, 8, 11, 4, 2 ]
gap> e := FRElement(g2,11);
<Mealy element on alphabet [ 1, 2 ] with 25 states, initial state 11>
gap> Minimized(e);
<Mealy element on alphabet [ 1, 2 ] with 5 states, initial state 1, minimized>
gap> Correspondence(last);
[ 3, 2, 1, 4, 5, 2, 3,,,, 1,, 3, 5, 4, 4,, 5, 3, 1, 5,, 4, 1, 3 ]

```

5.2.3 DualMachine

◇ `DualMachine(m)`

(operation)

Returns: The dual Mealy machine of m .

This function constructs the *dual* machine of m , i.e. the machine with stateset the alphabet of m , with alphabet the stateset of m , and similarly with transitions and output switched.

```

Example
gap> b := MealyMachine([[3,2],[3,1],[3,3]],[(1,2),(),()]);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> d := DualMachine(b)^4;
<Mealy machine on alphabet [ 1, 2, 3 ] with 16 states>
gap> Draw(d); # action on 2^4 points
gap> DualMachine(d);
<Mealy machine on alphabet [ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16
] with 3 states>

```

```
gap> Output(last,1)=Activity(FRElement(b,1),4);
true
```

5.2.4 IsReversible

◇ IsReversible(m)

(property)

Returns: true if m is a reversible Mealy machine.

This function tests whether m is *reversible*, i.e. whether the DualMachine (5.2.3) of m is invertible. See [MNS00] for more details.

Example

```
gap> IsReversible(MealyMachine([[1,2],[2,2]],[(1,2),()]]);
false
gap> IsReversible(MealyMachine([[1,2],[2,1]],[(1,2),()]]);
```

5.2.5 IsMinimized

◇ IsMinimized(m)

(property)

Returns: true if m is a minimized Mealy machine.

This function tests whether m is *minimized*, i.e. whether none of its states can be removed or coalesced. All Mealy elements are automatically minimized.

Example

```
gap> AllMealyMachines(2, 2, IsBireversible,EquivalenceClasses);
[ <Mealy machine on alphabet [ 1, 2 ] with 2 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 2 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 2 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 2 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 2 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 2 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 2 states>,
  <Mealy machine on alphabet [ 1, 2 ] with 2 states> ]
gap> List(last,IsMinimized);
[ false, true, false, false, false, false, true, false ]
```

5.2.6 AlphabetInvolution

◇ AlphabetInvolution(m)

(attribute)

Returns: A list giving, for each alphabet letter, its inverse.

If m is a bireversible machine, it may happen that the stateset of the dual of m (see DualMachine (5.2.3)) is closed under taking inverses. If this happens, then this list records the mapping from an alphabet letter of m to its inverse.

Example

```
gap> m := GammaPQMachine(3,5);; AlphabetOfFRObj(m);
[ 1 .. 6 ]
gap> IsBireversible(m); AlphabetInvolution(GammaPQMachine(3,5));
true
[ 6, 5, 4, 3, 2, 1 ]
```

5.2.7 IsBireversible

◇ IsBireversible(m)

(property)

Returns: true if m is a bireversible Mealy machine.

This function tests whether m is *bireversible*, i.e. whether all eight machines obtained from m using DualMachine (5.2.3) and Inverse are well-defined. See [MNS00] for more details.

Example

```
gap> IsBireversible(MealyMachine([[1,2],[2,1]],[(1),(1,2)]));
false
gap> IsBireversible(MealyMachine([[1,1],[2,2]],[(1),(1,2)]));
true
```

5.2.8 StateGrowth

◇ StateGrowth($m[, x]$)

(operation)

Returns: The state growth of the Mealy machine or element m .

This function computes, as a rational function, the power series in x whose coefficient of degree n is the number of non-trivial states at level n of the tree.

If x is absent, it is assumed to be Indeterminate(Rationals).

If m is a Mealy machine, this function is computed with respect to all possible starting states. If m is a Mealy element, this function is computed with respect to the initial state of m .

Example

```
gap> b := MealyMachine([[3,2],[3,1],[3,3]],[(1,2),(),()]);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> StateGrowth(b,Indeterminate(Rationals));
(2)/(-x_1+1)
gap> StateGrowth(FRElement(b,1),Indeterminate(Rationals));
(1)/(-x_1+1)
```

5.2.9 Degree (FR element)

◇ Degree(m)

(operation)

◇ DegreeOfFRMachine(m)

(operation)

◇ DegreeOfFRElement(m)

(operation)

Returns: The growth degree of the Mealy machine or element m .

This function computes the order of the pole at $x = 1$ of StateGrowth(m, x), in case its denominator is a product of cyclotomics; and returns infinity otherwise.

This attribute of Mealy machines was studied inter alia in [Sid00].

Example

```
gap> m := MealyMachine([[2,1],[3,2],[3,3]],[(1),(1,2),()]);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> StateGrowth(m,Indeterminate(Rationals));
(-x_1+2)/(x_1^2-2*x_1+1)
gap> List(StateSet(m),i->Degree(FRElement(m,i)));
[ 2, 1, -1 ]
gap> a := MealyMachine(Group((1,2)),Group((1,2)),\*,\*);
<Mealy machine on alphabet [ (), (1,2) ] with states Group([ (1,2) ])>
gap> Degree(a);
infinity
```

5.2.10 IsFinitaryFRElement

◇ IsFinitaryFRElement(*e*)

(property)

◇ IsFinitaryFRMachine(*e*)

(property)

Returns: true if *e* is a finitary element.

This function tests whether *e* is a finitary element. These are by definition the elements of growth degree at most 0.

When applied to a Mealy machine, it returns true if all states of *e* are finitary.

Example

```
gap> m := GuptaSidkiMachines(3);; Display(m);
| 1      2      3
---+-----+-----+-----+
a | a,1   a,2   a,3
b | a,2   a,3   a,1
c | a,3   a,1   a,2
d | b,1   c,2   d,3
---+-----+-----+-----+
gap> Filtered(StateSet(m), i->IsFinitaryFRElement(FRElement(m,i)));
[ 1, 2, 3 ]
gap> IsFinitaryFRElement(m);
false
```

5.2.11 Depth (FR element)

◇ Depth(*m*)

(attribute)

◇ DepthOfFRMachine(*m*)

(attribute)

◇ DepthOfFRElement(*m*)

(attribute)

Returns: The depth of the finitary Mealy machine or element *m*.

This function computes the maximal level at which the *m* has a non-trivial state. In particular the identity has depth 0, and FR elements acting only at the root vertex have depth 1. The value infinity is returned if *m* is not finitary (see IsFinitaryFRElement (5.2.10)).

Example

```
gap> m := MealyMachine([[2,1],[3,3],[4,4],[4,4]],[( ),( ),(1,2),( )]);
<Mealy machine on alphabet [ 1, 2 ] with 4 states>
gap> DepthOfFRMachine(m);
infinity
gap> List(StateSet(m), i->DepthOfFRElement(FRElement(m,i)));
[ infinity, 2, 1, 0 ]
```

5.2.12 IsBoundedFRElement

◇ IsBoundedFRElement(*e*)

(property)

◇ IsBoundedFRMachine(*e*)

(property)

Returns: true if *e* is a finitary element.

This function tests whether *e* is a bounded element. These are by definition the elements of growth degree at most 1.

When applied to a Mealy machine, it returns true if all states of *e* are bounded.

Example

```
gap> m := GuptaSidkiMachines(3);; Display(m);
| 1      2      3
```

```

---+-----+-----+-----+
a | a,1   a,2   a,3
b | a,2   a,3   a,1
c | a,3   a,1   a,2
d | b,1   c,2   d,3
---+-----+-----+-----+
gap> Filtered(StateSet(m), i->IsBoundedFRElement(FRElement(m,i)));
[ 1, 2, 3, 4 ]
gap> IsBoundedFRMachine(m);
true

```

5.2.13 IsPolynomialGrowthFRElement

◇ IsPolynomialGrowthFRElement(e)

(property)

◇ IsPolynomialGrowthFRMachine(e)

(property)

Returns: true if e is an element of polynomial growth.

This function tests whether e is a polynomial element. These are by definition the elements of polynomial growth degree.

When applied to a Mealy machine, it returns true if all states of e are of polynomial growth.

Example

```

gap> m := GuptaSidkiMachines(3);; Display(m);
| 1      2      3
---+-----+-----+-----+
a | a,1   a,2   a,3
b | a,2   a,3   a,1
c | a,3   a,1   a,2
d | b,1   c,2   d,3
---+-----+-----+-----+
gap> Filtered(StateSet(m), i->IsPolynomialGrowthFRElement(FRElement(m,i)));
[ 1, 2, 3, 4 ]
gap> IsPolynomialGrowthFRMachine(m);
true

```

5.2.14 Signatures

◇ Signatures(e)

(operation)

Returns: A list describing the product of the activities on each level.

This function computes the product of the activities of e on each level, and returns a periodic list describing it (see PeriodicList (12.1.6)).

The entries π_i are permutations, and their values are meaningful only when projected in the abelianization of VertexTransformationsFRElement(e).

Example

```

gap> Signatures(GrigorchukGroup.1);
[ (1,2), / () ]
gap> Signatures(GrigorchukGroup.2);
[/ (), (1,2), (1,2) ]
gap> last[50];
(1,2)
gap> Signatures(AddingMachine(3)[2]);
[/ (1,2,3) ]

```

5.2.15 VertexTransformationsFRMachine

◇ VertexTransformationsFRMachine(*m*)

(operation)

◇ VertexTransformationsFRElement(*e*)

(operation)

Returns: The group/monoid generated by all vertex transformations of states of *m*.

The first function computes the finite permutation group / transformation monoid generated by all outputs of states of *m*.

The second command is a short-hand for VertexTransformationsFRMachine(UnderlyingFRMachine(*e*)).

Example

```
gap> m := MealyMachine([[1,3,2],[3,2,1],[2,1,3]],[(2,3),(1,3),(1,2)]);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> VertexTransformationsFRMachine(m);
Group([ (2,3), (1,3), (1,2) ])
```

5.2.16 FixedRay (FR element)

◇ FixedRay(*e*)

(operation)

Returns: The lexicographically first ray fixed by *e*.

This function computes the lexicographically first infinite sequence that is fixed by the FR element *e*, and returns it as a periodic list (see PeriodicList (12.1.6)). It returns fail if no such ray exists.

Example

```
gap> m := MealyMachine([[1,3,2],[3,2,1],[2,1,3]],[(2,3),(1,3),(1,2)]);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> FixedRay(FRElement(m,1));
[/ 1 ]
gap> last^FRElement(m,1);
[/ 1 ]
gap> FixedRay(FRElement(m,[1,2]));
fail
```

5.2.17 IsLevelTransitive (FR element)

◇ IsLevelTransitive(*e*)

(property)

Returns: true if *e* acts transitively on each level of the tree.

This function tests whether *e* acts transitively on each level of the tree. It is implemented only if VertexTransformationsFRElement(*e*) is abelian.

This function is used as a simple test to detect whether an element has infinite order: if *e* has a fixed vertex *v* such that the State(*e*, *v*) is level-transitive, then *e* has infinite order.

Example

```
gap> m := AddingMachine(3);; Display(m);
  | 1      2      3
---+---+---+---+
a | a,1   a,2   a,3
b | a,2   a,3   b,1
---+---+---+---+
Initial state:  b
gap> IsLevelTransitive(m);
true
gap> IsLevelTransitive(Product(UnderlyingFRMachine(GrigorchukOverGroup){[2..5]}));
true
```

5.2.18 AsMealyMachine (FR machine)

◇ AsMealyMachine(*m*)

(attribute)

Returns: A Mealy machine isomorphic to *m*.

This function constructs a Mealy machine *r*, which is as close as possible to the FR machine *m*. Furthermore, Correspondence(*r*) is a list identifying, for every generator of the stateset of *m*, a corresponding state in the new Mealy machine; see Correspondence (3.5.11).

m may be a group/monoid/semigroup FR machine, or a Mealy machine; in which case the result is returned unchanged.

In particular, FRElement(*m*, *s*) and FRElement(AsMealyMachine(*m*), *s*) return the same tree automorphism, for any FR machine *m* and any state *s*.

This function is not guaranteed to return; if *m* does not have finite states, then it will loop forever.

Example

```
gap> n := FRMachine(["tau", "mu"], [[[]], [1]], [[[]], [-2]], [(1,2), (1,2)]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ tau, mu ] )>
gap> Display(n);
      |      1      2
-----+-----+-----+
tau | <id>,2      tau,1
mu | <id>,2      mu^-1,1
-----+-----+-----+
gap> AsMealyMachine(n);
<Mealy machine on alphabet [ 1, 2 ] with 4 states>
gap> Display(last);
      |      1      2
---+---+---+
a | c,2      a,1
b | c,2      d,1
c | c,1      c,2
d | b,2      c,1
---+---+---+
gap> Correspondence(last);
[ 1, 2 ]
```

5.2.19 AsMealyMachine (List)

◇ AsMealyMachine(*l*)

(attribute)

Returns: A Mealy machine constructed out of the FR elements in *l*.

This function constructs a Mealy machine *r*, with states *l* (which must be a state-closed set). Its outputs are the outputs of its elements, and its transitions are the transitions of its elements; in particular, FRElement(*r*, *i*) is equal to *l*[*i*] as an FR element.

Correspondence(*r*) records the argument *l*.

This function returns fail if *l* is not state-closed.

Example

```
gap> mu := FRElement([[[]], [-1]], [(1,2)], [1]);
<2|f1>
gap>
gap> States(mu);
[ <2|f1>, <2|identity ...>, <2|f1^-1> ]
gap> AsMealyMachine(last);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
```

```
gap> Display(last);
| 1      2
---+-----+-----+
a | b,2   c,1
b | b,1   b,2
c | a,2   b,1
---+-----+-----+
```

5.2.20 AsMealyElement

◇ AsMealyElement (*m*)

(attribute)

Returns: A Mealy element isomorphic to *m*.

This function constructs a Mealy element, which induces the same tree automorphism as the FR element *m*.

m may be a group/monoid/semigroup FR element, or a Mealy element; in which case the result is returned unchanged.

This function is not guaranteed to return; if *m* does not have finite states, then it will loop forever.

Example

```
gap> mu := FRElement([[[[]], [-1]]], [(1,2)], [1]);
<2|f1>
gap> AsMealyElement(mu);
<Mealy machine on alphabet [ 1, 2 ] with 3 states, initial state 1>
gap> [[2,1]]^last;
[ [ 1, 2 ] ]
gap> [2,1,2,1]^mu;
[ 1, 2, 1, 2 ]
```

5.2.21 AsIntMealyMachine

◇ AsIntMealyMachine (*m*)

(attribute)

◇ AsIntMealyElement (*m*)

(attribute)

Returns: A Mealy machine in integer format, isomorphic to *m*.

This function constructs a Mealy machine *r*, which has similar behaviour as *m* while having state-set $[1..n]$ for some natural *n*. Most FR commands operate efficiently only on Mealy machines of this type.

This function is not guaranteed to return; if *m* does not have finite states, then it will loop forever.

Example

```
gap> g := Group((1,2));; n := MealyMachine(g,g,\*,\*);
<Mealy machine on alphabet [ (), (1,2) ] with states Group( [ (1,2) ] )>
gap> Display(n);
|      ()      (1,2)
-----+-----+-----+
() |      (), ()      (1,2), (1,2)
(1,2) | (1,2), (1,2)      (), ()
-----+-----+-----+
gap> AsIntMealyMachine(n);
<Mealy machine on alphabet [ 1, 2 ] with 2 states>
gap> Display(last);
| 1      2
---+-----+-----+
```

```

a | a,1  b,2
b | b,2  a,1
---+-----+-----+
gap> Correspondence(last);
[ 1, 2 ]

```

5.2.22 TopElement

◇ TopElement($p[, n]$)

(attribute)

Returns: A Mealy machine in integer format, acting on the first symbol of sequences.

This function constructs a Mealy machine r , which acts as p on the first letter of sequences and fixes the other letters. The argument n is the size of the alphabet of r ; if it is omitted, then it is assumed to be the degree of the transformation p , or the largest moved point of the permutation or trans p .

Example

```

gap> a := TopElement((1,2));
<Mealy element on alphabet [ 1, 2 ] with 2 states>
gap> last=GrigorchukGroup.1;
true
gap> a := TopElement((1,2),3);
<Mealy element on alphabet [ 1, 2, 3 ] with 2 states>
gap> last in GuptaSidkiGroup;
false

```

5.2.23 ConfinalityClasses

◇ ConfinalityClasses(e)

(attribute)

◇ IsWeaklyFinitaryFRElement(e)

(attribute)

Returns: A list describing the non-trivial confinality classes of e .

If e is a bounded element (see IsBoundedFRElement (5.2.12)), there are finitely many infinite sequences that have confinality class larger than one; i.e. ultimately periodic sequences that are mapped by e to a sequence with different period. This function returns a list of equivalence classes of periodic lists, see PeriodicList (12.1.6), which are related under e .

By definition, an element is *weakly finitary* if it has no non-singleton confinality classes.

Example

```

gap> g := FRGroup("t=<,,t>(2,3)", "u=<u,,>(1,2)", "v=<u,t,>");;
gap> ConfinalityClasses(g.1);
[ {PeriodicList([ ], [ 2 ])} ]
gap> List(GeneratorsOfGroup(g), x->Elements(ConfinalityClasses(x)[1]));
[ [ [/ 2 ], [/ 3 ] ],
  [ [/ 1 ], [/ 2 ] ],
  [ [/ 1 ], [/ 2 ], [/ 3 ] ] ]
gap> IsWeaklyFinitaryFRElement(BinaryAddingElement);
false
gap> IsWeaklyFinitaryFRElement(GuptaSidkiGroup.2);
true

```

5.2.24 Germs

◇ `Germ(e)`

(attribute)

◇ `NormOfBoundedFRElement(e)`

(attribute)

Returns: The germs of the bounded element e .

The *germs* of a bounded element are the finitely many ultimately periodic sequences on which the state of e does not vanish. This function returns the germs of e , as a list of pairs; the first entry is a ray described as a periodic sequence of integers (see `PeriodicList` (12.1.6)), and the second entry is the periodic sequence of states that appear along that ray.

The *norm* of a bounded element is the length of its list of germs.

Example

```
gap> Germ(BinaryAddingElement);
[ [ [ / 2 ], [ / 1 ] ] ]
gap> Germ(GrigorchukGroup.1);
[ ]
gap> Germ(GrigorchukGroup.2);
[ [ [ / 2 ], [ / 1, 3, 5 ] ] ]
gap> Display(GrigorchukGroup.2);
  | 1      2
---+-----+-----+
a | b,1    c,2
b | d,2    d,1
c | b,1    e,2
d | d,1    d,2
e | d,1    a,2
---+-----+-----+
Initial state: a
```

5.2.25 HasOpenSetConditionFRElement

◇ `HasOpenSetConditionFRElement(e)`

(property)

Returns: `true` if e has the open set condition.

An FR element e has the *open set condition* if for every infinite ray in the tree which is fixed by e , there is an open set around that ray which is also fixed by e . This function tests for e to have the open set condition. It currently is implemented only for bounded elements.

Example

```
gap> HasOpenSetConditionFRElement(GrigorchukGroup.1);
true
gap> HasOpenSetConditionFRElement(GrigorchukGroup.2);
false
```

5.2.26 LimitMachine

◇ `LimitMachine(m)`

(attribute)

Returns: The submachine of m on all recurrent states.

This command creates a new Mealy machine, with stateset the limit states of m .

Example

```
gap> m := MealyMachine([[2,2,3],[2,3,3],[3,3,3]],[(),(),(1,2,3)]);
<Mealy machine on alphabet [ 1 .. 3 ] with 3 states>
gap> Display(m);
```

```

      | 1      2      3
----+-----+-----+-----+
a | b,1    b,2    c,3
b | b,1    c,2    c,3
c | c,2    c,3    c,1
----+-----+-----+-----+
gap> LimitStates(m);
[ <Mealy element on alphabet [ 1 .. 3 ] with 2 states>,
  <Mealy element on alphabet [ 1 .. 3 ] with 1 state> ]
gap> LimitMachine(m);
<Mealy machine on alphabet [ 1 .. 3 ] with 2 states>
gap> Display(last);
      | 1      2      3
----+-----+-----+-----+
a | a,1    b,2    b,3
b | b,2    b,3    b,1
----+-----+-----+-----+

```

5.2.27 NucleusMachine (FR machine)

◇ **NucleusMachine** (*m*)

(attribute)

Returns: The nucleus of *m*.

This command creates a new Mealy machine *n*, which is such that `LimitMachine(m*n)` is isomorphic to *n*, after minimisation. It is also isomorphic to the `NucleusMachine` (7.2.18) of the state closure of the `SCSemigroup` (7.1.2) of *m*. (Note that the ordering of the states in the resulting machine is not necessarily the same as in *m*; however, if *m* and *n* are isomorphic, then this command returns *m*).

Example

```

gap> m := MealyMachine([[2,1,1],[2,2,2]],[(1,2,3),()]);
<Mealy machine on alphabet [ 1, 2, 3 ] with 2 states>
gap> Display(m);
      | 1      2      3
----+-----+-----+-----+
a | b,2    a,3    a,1
b | b,1    b,2    b,3
----+-----+-----+-----+
gap> NucleusMachine(m);
<Mealy machine on alphabet [ 1, 2, 3 ] with 3 states>
gap> Display(last);
      | 1      2      3
----+-----+-----+-----+
a | a,1    a,2    a,3
b | c,3    b,1    c,2
c | a,2    c,3    c,1
----+-----+-----+-----+

```

5.2.28 GuessMealyElement

◇ **GuessMealyElement** (*p*, *d*, *n*)

(operation)

Returns: A Mealy element that probably has the same activity as *p*.

This function receives a permutation or transformation *p*, a degree *d* and a level *n*, and attempts to find a Mealy element on the alphabet `[1..d]` whose activity on level *n* is *p*.

This function returns `fail` if it thinks that the given level is not large enough to make a reasonable guess. In all cases, the function is not guaranteed to return the correct Mealy machine.

Example

```
gap> GuessMealyElement(Activity(GrigorchukGroup.2,6),2,6);
<Mealy element on alphabet [ 1, 2 ] with 5 states>
gap> last=GrigorchukGroup.2;
true
gap> GuessMealyElement(Activity(GrigorchukGroup.2,5),2,5);
fail
gap> ComposeElement([GrigorchukGroup.2,One(GrigorchukGroup)],());
<Mealy element on alphabet [ 1, 2 ] with 6 states>
gap> last=GuessMealyElement(Activity(GrigorchukGroup.2,6),2,7);
true
```

Chapter 6

Linear machines and elements

Linear machines are a special class of FR machines, in which the stateset Q and the alphabet X are vector spaces over a field \mathbb{k} , and the transition map $\phi : Q \otimes X \rightarrow X \otimes Q$ is a linear map; furthermore, there is a functional $\pi : Q \rightarrow \mathbb{k}$ called the *output*.

As before, a choice of initial state $q \in Q$ induces a linear map $q : T(X) \rightarrow T(X)$, where $T(X) = \bigoplus X^{\otimes n}$ is the tensor algebra generated by X . This map is defined as follows: given $x = x_1 \otimes \dots \otimes x_n \in T(X)$, rewrite $q \otimes x$ as a sum of expressions of the form $y \otimes r$ with $y \in T(X)$ and $r \in Q$; then q , by definition, maps x to the sum of the $\pi(r)y$.

There are two sorts of linear machines: *vector machines*, for which the state space is a finite-dimensional vector space over a field; and *algebra machines*, for which the state space is a free algebra in a finite set of variables.

In a vector machine, the transition and output maps are stored as a matrix and a vector respectively. Minimization algorithms are implemented, as for Mealy machines.

In an algebra machine, the transition and output maps are stored as words in the algebra. These machines are natural extensions of group/monoid/semigroup machines.

Linear elements are given by a linear machine and an initial state. They can be added and multiplied, and act on the tensor algebra of the alphabet, admitting natural representations as matrices.

6.1 Methods and operations for LinearFRMachines and LinearFRElements

6.1.1 VectorMachine

<code>◇ VectorMachine(domain, transitions, output)</code>	(operation)
<code>◇ VectorElement(domain, transitions, output, init)</code>	(operation)
<code>◇ VectorMachineNC(fam, transitions, output)</code>	(operation)
<code>◇ VectorElementNC(fam, transitions, output, init)</code>	(operation)

Returns: A new vector machine/element.

This function constructs a new linear machine or element, of vector type.

transitions is a matrix of matrices; for a, b indices of basis vectors of the alphabet, $\text{transitions}[a][b]$ is a square matrix indexed by the stateset, which is the transition to be effected on the stateset upon the output $a \rightarrow b$.

output and *init* are vectors in the stateset.

In the "NC" version, no tests are performed to check that the arguments contain values within bounds, or even of the right type (beyond the simple checking performed by GAP's method selection algorithms). The first argument should be the family of the resulting object. These "NC" methods are mainly used internally by the package.

Example

```
gap> M := VectorMachine(Rationals, [[[1]], [[2]]], [[[3]], [[4]]], [1]);
<Linear machine on alphabet Rationals^2 with 1-dimensional stateset>
gap> Display(M);
  Rationals | 1 | 2 |
-----+---+---+
          1 | 1 | 2 |
-----+---+---+
          2 | 3 | 4 |
-----+---+---+
Output: 1
gap> A := VectorElement(Rationals, [[[1]], [[2]]], [[[3]], [[4]]], [1], [1]);
<Linear element on alphabet Rationals^2 with 1-dimensional stateset>
gap> Display(Activity(A, 2));
[ [ 1, 2, 2, 4 ],
  [ 3, 4, 6, 8 ],
  [ 3, 6, 4, 8 ],
  [ 9, 12, 12, 16 ] ]
gap> DecompositionOfFRElement(A);
[ [ <Linear element on alphabet Rationals^2 with 1-dimensional stateset>,
    <Linear element on alphabet Rationals^2 with 1-dimensional stateset> ],
  [ <Linear element on alphabet Rationals^2 with 1-dimensional stateset>,
    <Linear element on alphabet Rationals^2 with 1-dimensional stateset> ] ]
gap> last=[A, 2*A], [3*A, 4*A];
true
```

6.1.2 AlgebraMachine

- ◇ AlgebraMachine([domain, ring, transitions, output]) (operation)
- ◇ AlgebraElement([domain, ring, transitions, output, init]) (operation)
- ◇ AlgebraMachineNC(fam, ring, transitions, output) (operation)
- ◇ AlgebraElementNC(fam, ring, transitions, output, init) (operation)

Returns: A new algebra machine/element.

This function constructs a new linear machine or element, of algebra type.

ring is a free associative algebra, optionally with one. *domain* is the vector space on which the alphabet is defined. If absent, this argument defaults to the LeftActingDomain (**Reference: LeftActingDomain**) of *ring*.

transitions is a list of matrices; for each generator number *i* of *ring*, the matrix *transitions*[*i*], with entries in *ring*, describes the decomposition of generator *i* as a matrix.

output is a vector over *domain*, and *init* is a vector over *ring*.

In the "NC" version, no tests are performed to check that the arguments contain values within bounds, or even of the right type (beyond the simple checking performed by GAP's method selection algorithms). The first argument should be the family of the resulting object. These "NC" methods are mainly used internally by the package.

Example

```
gap> F := FreeAssociativeAlgebraWithOne(Rationals, 1);;
```

```

gap> A := AlgebraMachine(F, [[F.1, F.1^2+F.1], [One(F), Zero(F) ]], [1]);
<Linear machine on alphabet Rationals^2 with generators [ (1)*x.1 ]>
gap> Display(A);
  Rationals |      1      |      2      |
  -----+-----+-----+
           1 |      x.1 | x.1+x.1^2 |
  -----+-----+-----+
           2 |      1   |      0   |
  -----+-----+-----+
Output: 1
gap> M := AlgebraElement(F, [[F.1, F.1^2+F.1], [One(F), Zero(F) ]], [1], F.1);
<Rationals^2|(1)*x.1>
gap> Display(Activity(M, 2));
[ [ 1, 2, 4, 4 ],
  [ 1, 0, 2, 2 ],
  [ 1, 0, 0, 0 ],
  [ 0, 1, 0, 0 ] ]

```

6.1.3 Transition (Linear machine)

◇ **Transition**(*m*, *s*, *a*, *b*)

(operation)

Returns: An element of *m*'s stateset.

This function returns the state reached by *m* when started in state *s* and performing output $a \rightarrow b$.

Example

```

gap> M := AsVectorMachine(Rationals, FRMachine(GuptaSidkiGroup.2));
<Linear machine on alphabet Rationals^3 with 4-dimensional stateset>
gap> Transition(M, [1,0,0,0], [1,0,0], [1,0,0]);
[ 0, 1, 0, 0 ]
gap> Transition(M, [1,0,0,0], [0,1,0], [0,1,0]);
[ 0, 0, 1, 0 ]
gap> Transition(M, [1,0,0,0], [0,0,1], [0,0,1]);
[ 1, 0, 0, 0 ]
gap> A := AsVectorElement(Rationals, GuptaSidkiGroup.2);
<Linear element on alphabet Rationals^3 with 4-dimensional stateset>
gap> Transition(A, [1,0,0], [1,0,0]);
[ 0, 1, 0, 0 ]

```

6.1.4 Transitions

◇ **Transitions**(*m*, *s*, *a*)

(operation)

Returns: An vector of elements of *m*'s stateset.

This function returns the state reached by *m* when started in state *s* and receiving input *a*. The output is a vector, indexed by the alphabet's basis, of output states.

Example

```

gap> M := AsVectorMachine(Rationals, FRMachine(GuptaSidkiGroup.2));
<Linear machine on alphabet Rationals^3 with 4-dimensional stateset>
gap> Transitions(M, [1,0,0,0], [1,0,0]);
[ [ 0, 1, 0, 0 ], [ 0, 0, 0, 0 ], [ 0, 0, 0, 0 ] ]
gap> A := AsVectorElement(Rationals, GuptaSidkiGroup.2);
<Linear element on alphabet Rationals^3 with 4-dimensional stateset>

```

```
gap> Transitions(A, [1,0,0]);
[ [ 0, 1, 0, 0 ], [ 0, 0, 0, 0 ], [ 0, 0, 0, 0 ] ]
```

6.1.5 NestedMatrixState

◇ `NestedMatrixState(e, i, j)`

(operation)

◇ `NestedMatrixCoefficient(e, i, j)`

(operation)

Returns: A coefficient of an iterated decomposition of e .

The first form returns the entry at position (i, j) of e 's decomposition. Both of i, j are lists. The second form returns the output of the state.

In particular, `NestedMatrixState(e, [], []) = e`, and `Activity(e, 1) [i] [j] = NestedMatrixCoefficient(e, [i], [j])`, and `DecompositionOfFRElement(e, 1) [i] [j] = NestedMatrixState(e, [i], [j])`.

Example

```
gap> A := AsVectorElement(Rationals, GuptaSidkiGroup.2);
gap> A = NestedMatrixState(A, [3,3], [3,3]);
true
gap> IsOne(NestedMatrixState(A, [3,3,3,3,1,1], [3,3,3,3,1,2]));
true
gap> List([1..3], i -> List([1..3], j -> NestedMatrixCoefficient(A, [i], [j]))) = Activity(A, 1);
true
```

6.1.6 ActivitySparse

◇ `ActivitySparse(m, i)`

(operation)

Returns: A sparse matrix.

`Activity(m, i)` returns an $n^i \times n^i$ matrix describing the action on the i -fold tensor power of the alphabet. This matrix can also be returned as a sparse matrix, and this is performed by this command. A sparse matrix is described as a list of expressions of the form `[[i, j], c]`, representing the elementary matrix with entry c at position (i, j) . The activity matrix is then the sum of these elementary matrices.

Example

```
gap> A := AsVectorElement(Rationals, GuptaSidkiGroup.2);
gap> Display(Activity(A, 2));
[ [ 0, 1, 0, 0, 0, 0, 0, 0, 0 ],
  [ 0, 0, 1, 0, 0, 0, 0, 0, 0 ],
  [ 1, 0, 0, 0, 0, 0, 0, 0, 0 ],
  [ 0, 0, 0, 0, 0, 1, 0, 0, 0 ],
  [ 0, 0, 0, 1, 0, 0, 0, 0, 0 ],
  [ 0, 0, 0, 0, 1, 0, 0, 0, 0 ],
  [ 0, 0, 0, 0, 0, 0, 1, 0, 0 ],
  [ 0, 0, 0, 0, 0, 0, 0, 1, 0 ],
  [ 0, 0, 0, 0, 0, 0, 0, 0, 1 ] ]
gap> ActivitySparse(A, 2);
[ [ [ 1, 2 ], 1 ], [ [ 2, 3 ], 1 ], [ [ 3, 1 ], 1 ], [ [ 4, 6 ], 1 ],
  [ [ 5, 4 ], 1 ], [ [ 6, 5 ], 1 ], [ [ 7, 7 ], 1 ], [ [ 8, 8 ], 1 ],
  [ [ 9, 9 ], 1 ] ]
```

6.1.7 Activities

◇ `Activities(m, i)`

(operation)

Returns: Activities of m on the first i levels.

`Activity(m, i)` returns an $n^i \times n^i$ matrix describing the action on the i -fold tensor power of the alphabet. This command returns `List([0..i-1], j->Activity(m, j))`.

Example

```
gap> A := AsVectorElement(Rationals, GrigorchukGroup.2);
gap> Activities(A, 3);
[ [ [ 1 ] ],
  [ [ 1, 0 ], [ 0, 1 ] ],
  [ [ 0, 1, 0, 0 ], [ 1, 0, 0, 0 ], [ 0, 0, 1, 0 ], [ 0, 0, 0, 1 ] ] ]
```

6.1.8 IsConvergent

◇ `IsConvergent(e)`

(property)

Returns: Whether the linear element e is convergent.

A linear element is *convergent* if its state at position $(1, 1)$ is equal to itself.

Example

```
gap> n := 3;;
gap> shift := VectorElement(CyclotomicField(n), [[ [1, 0], [0, 0] ],
  [[0, 0], [0, 1]], [[0, 1], [0, 0]], [[1, 0], [0, 0]]], [1, E(n)], [1, 0]);
<Linear element on alphabet CF(3)^2 with 2-dimensional stateset>
gap> IsConvergent(shift);
true
gap> Display(Activity(shift, 2));
[ [ 1, 0, 0, 0 ],
  [ E(3), 1, 0, 0 ],
  [ 0, E(3), 1, 0 ],
  [ 0, 0, E(3), 1 ] ]
gap> Display(Activity(shift, 3));
[ [ 1, 0, 0, 0, 0, 0, 0, 0 ],
  [ E(3), 1, 0, 0, 0, 0, 0, 0 ],
  [ 0, E(3), 1, 0, 0, 0, 0, 0 ],
  [ 0, 0, E(3), 1, 0, 0, 0, 0 ],
  [ 0, 0, 0, E(3), 1, 0, 0, 0 ],
  [ 0, 0, 0, 0, E(3), 1, 0, 0 ],
  [ 0, 0, 0, 0, 0, E(3), 1, 0 ],
  [ 0, 0, 0, 0, 0, 0, E(3), 1 ] ]
```

6.1.9 TransposedFRElement

◇ `TransposedFRElement(e)`

(operation)

◇ `IsSymmetricFRElement(e)`

(property)

◇ `IsAntisymmetricFRElement(e)`

(property)

◇ `IsLowerTriangularFRElement(e)`

(property)

◇ `IsUpperTriangularFRElement(e)`

(property)

◇ `IsDiagonalFRElement(e)`

(property)

Returns: The elementary matrix operation/property.

Since linear FR elements may be interpreted as infinite matrices, it makes sense to transpose them, test whether they're symmetric, antisymmetric, diagonal, or triangular.

Example

```
gap> n := 3;;
gap> shift := VectorElement(CyclotomicField(n), [[[[1,0],[0,0]],
  [[0,0],[0,1]], [[0,1],[0,0]], [[1,0],[0,0]]], [1,E(n)], [1,0]);
<Linear element on alphabet CF(3)^2 with 2-dimensional stateset>
gap> Display(Activity(shift,2));
[ [ 1, 0, 0, 0 ],
  [ E(3), 1, 0, 0 ],
  [ 0, E(3), 1, 0 ],
  [ 0, 0, E(3), 1 ] ]
gap> Display(Activity(TransposedFRElement(shift),2));
[ [ 1, E(3), 0, 0 ],
  [ 0, 1, E(3), 0 ],
  [ 0, 0, 1, E(3) ],
  [ 0, 0, 0, 1 ] ]
gap> IsSymmetricFRElement(shift);
false
gap> IsSymmetricFRElement(shift+TransposedFRElement(shift));
true
gap> IsLowerTriangularFRElement(shift);
true
gap> IsUpperTriangularFRElement(shift);
false
```

6.1.10 LDUDecompositionFRElement

◇ LDUDecompositionFRElement(e)

(operation)

Returns: A factorization $e = LDU$.

Given a linear element e , this command attempts to find a decomposition of the form $e = LDU$, where L is lower triangular, D is diagonal, and U is upper triangular (see IsLowerTriangularFRElement (6.1.9) etc.).

The result is returned as a list with entries L, D, U . Note that it is not guaranteed to succeed. For more examples, see Section 10.4.

Example

```
gap> List([0..7], s->List([0..7], t->E(4)^ValuationInt(Binomial(s+t,s),2)));;
gap> A := GuessVectorElement(last);
<Linear element on alphabet GaussianRationals^2 with 2-dimensional stateset>
gap> LDU := LDUDecompositionFRElement(A);
[ <Linear element on alphabet GaussianRationals^2 with 4-dimensional stateset>,
  <Linear element on alphabet GaussianRationals^2 with 3-dimensional stateset>,
  <Linear element on alphabet GaussianRationals^2 with 4-dimensional stateset> ]
gap> IsLowerTriangularFRElement(LDU[1]); IsDiagonalFRElement(LDU[2]);
true
true
gap> TransposedFRElement(LDU[1])=LDU[3];
true
gap> Product(LDU)=A;
true
```

6.1.11 GuessVectorElement

◇ `GuessVectorElement(m)`

(function)

Returns: A vector element that acts like m .

The arguments to this function include a matrix or list of matrices, and an optional ring. The return value is a vector element, over the ring if it was specified, that acts like the sequence of matrices.

If a single matrix is specified, then it is assumed to represent a convergent element (see `IsConvergent` (6.1.8)).

This function returns `fail` if it believes that it does not have enough information to make a reasonable guess.

Example

```
gap> n := 3;;
gap> shift := VectorElement(CyclotomicField(n), [[[[1,0],[0,0]],
  [[0,0],[0,1]], [[0,1],[0,0]], [[1,0],[0,0]]], [1,E(n)], [1,0]]);
<Linear element on alphabet CF(3)^2 with 2-dimensional stateset>
gap> GuessVectorElement(Activity(shift,3)); last=shift;
<Linear element on alphabet CF(3)^2 with 2-dimensional stateset>
true
gap> GuessVectorElement(Inverse(Activity(shift,4)));
fail
gap> GuessVectorElement(Inverse(Activity(shift,5)));
<Linear element on alphabet CF(3)^2 with 4-dimensional stateset>
gap> IsOne(last*shift);
true
```

6.1.12 AsLinearMachine

◇ `AsLinearMachine(r, m)`

(operation)

◇ `AsLinearElement(r, m)`

(operation)

Returns: The linear machine/element associated with m .

This command accepts a domain and an ordinary machine/element, and constructs the corresponding linear machine/element, defined by extending linearly the action on $[1..d]$ to an action on r^d .

If m is a Mealy machine/element, the result is a vector machine/element. If m is a group/monoid/semigroup machine/element, the result is an algebra machine/element. To obtain explicitly a vector or algebra machine/element, see `AsVectorMachine` (6.1.13) and `AsAlgebraMachine` (6.1.14).

Example

```
gap> Display(I4Machine);
  | 1 2
---+---+-----+
a | c,2 c,1
b | a,1 b,1
c | c,1 c,2
---+---+-----+
gap> A := AsLinearMachine(Rationals,I4Machine);
<Linear machine on alphabet Rationals^2 with 3-dimensional stateset>
Correspondence(A);
[ [ 1, 0, 0 ], [ 0, 1, 0 ], [ 0, 0, 1 ] ]
gap> Display(A);
Rationals | 1 | 2 |
-----+-----+-----+
```

```

      1 | 0 0 0 | 0 0 1 |
        | 1 0 0 | 0 0 0 |
        | 0 0 1 | 0 0 0 |
-----+-----+-----+
      2 | 0 0 1 | 0 0 0 |
        | 0 1 0 | 0 0 0 |
        | 0 0 0 | 0 0 1 |
-----+-----+-----+
Output: 1 1 1
gap> B := AsLinearMachine(Rationals,AsMonoidFRMachine(I4Machine));
<Linear machine on alphabet Rationals^2 with generators [ (1)*m1, (1)*m2 ]>
gap> Correspondence(B);
MappingByFunction( <free monoid on the generators [ m1, m2 ]>,
<algebra-with-one over Rationals, with 2 generators>, function( w ) ... end )
gap> Display(B);
Rationals | 1 | 2 |
-----+-----+-----+
      1 | 0 | 1 |
        | m1 | 0 |
-----+-----+-----+
      2 | 1 | 0 |
        | m2 | 0 |
-----+-----+-----+
Output: 1 1
gap> AsLinearElement(Rationals,I4Monoid.1)*AsLinearElement(Rationals,I4Monoid.2);
<Linear element on alphabet Rationals^2 with 4-dimensional stateset>
gap> last=AsLinearElement(Rationals,I4Monoid.1*I4Monoid.2);
true

```

6.1.13 AsVectorMachine

◇ `AsVectorMachine(r, m)` (operation)
 ◇ `AsVectorElement(r, m)` (operation)

Returns: The vector machine/element associated with *m*.

This command accepts a domain and an ordinary machine/element, and constructs the corresponding linear machine/element, defined by extending linearly the action on $[1..d]$ to an action on r^d . For this command to succeed, the machine/element *m* must be finite state. For examples see `AsLinearMachine` (6.1.12).

6.1.14 AsAlgebraMachine

◇ `AsAlgebraMachine(r, m)` (operation)
 ◇ `AsAlgebraElement(r, m)` (operation)

Returns: The algebra machine/element associated with *m*.

This command accepts a domain and an ordinary machine/element, and constructs the corresponding linear machine/element, defined by extending linearly the action on $[1..d]$ to an action on r^d . For examples see `AsLinearMachine` (6.1.12).

6.1.15 AsVectorMachine (Linear machine)

◇ AsVectorMachine (m) (operation)

◇ AsVectorElement (m) (operation)

Returns: The machine/element m in vector form.

This command accepts a linear machine, and converts it to vector form. This command is not guaranteed to terminate.

Example

```
gap> A := AsLinearElement(Rationals, I4Monoid.1);
<Linear element on alphabet Rationals^2 with 2-dimensional stateset>
gap> B := AsAlgebraElement(A);
<Rationals^2 | (1)*x.1>
gap> C := AsVectorElement(B);
gap> A=B; B=C;
true
true
```

6.1.16 AsAlgebraMachine (Linear machine)

◇ AsAlgebraMachine (m) (operation)

◇ AsAlgebraElement (m) (operation)

Returns: The machine/element m in algebra form.

This command accepts a linear machine, and converts it to algebra form.

Example

```
gap> A := AsLinearElement(Rationals, I4Monoid.1);
<Linear element on alphabet Rationals^2 with 2-dimensional stateset>
gap> AsAlgebraElement(A)=AsAlgebraElement(Rationals, I4Monoid.1);
true
gap> A=AsAlgebraElement(A);
true
```

Chapter 7

Self-similar groups, monoids and semigroups

Self-similar groups, monoids and semigroups (below *FR semigroups*) are simply groups, monoids and semigroups whose elements are FR machines. They naturally act on the alphabet of their elements, and on sequences over that alphabet.

Most non-trivial calculations in FR groups are performed as follows: GAP searches through words of short length in the generating set of a FR group to find a solution to a group-theoretic question, and at the same time searches through the finite quotients to prove the inexistence of a solution. Usually the calculation ends with the answer *maybe*, which means that no definite answer, neither positive nor negative, could be found; however, the cases where the calculation actually terminates have been most useful.

The maximal length of words to consider in the search is controlled by the variable `FR_SEARCH.radius` (initially 10), and the maximal depth of the tree in which to search is controlled by the variable `FR_SEARCH.depth` (initially 6). These limits can be modified in any function call using GAP's options mechanism, e.g. in `Index(G,H:FRdepth:=5,FRradius:=5)`.

7.1 Creators for FR semigroups

The most straightforward creation method for FR groups is `Group()`, applied with FR elements as arguments. There are shortcuts to this somewhat tedious method:

7.1.1 FRGroup

◇ `FRGroup({definition, })` (operation)
◇ `FRMonoid({definition, })` (operation)
◇ `FRSemigroup({definition, })` (operation)

Returns: A new self-similar group/monoid/semigroup.

This function constructs a new FR group/monoid/semigroup, generated by group FR elements. It receives as argument any number of strings, each of which represents a generator of the object to be constructed.

Each *definition* is of the form "name=projtrans", where each of *proj* and *trans* is optional. *proj* is of the form `<w1,...,wd>`, where each *wi* is a (possibly empty) word in the names

or is 1. `trans` is either a permutation in disjoint cycle notation, or a list, representing the images of a permutation.

The option `IsMealyElement`, passed e.g. as in `FRGroup("a=(1,2)":IsMealyElement)`, asks for the resulting group to be generated by Mealy elements. The generators must of course be finite-state. Their names ("a",...) are not remembered in the constructing group (but can be set using `SetName` (**Reference: SetName**)).

Example

```
gap> FRGroup("a=(1,2)", "b=(1,2,3,4,5)"); Size(last);
<self-similar group over [ 1 .. 5 ] with 2 generators>
120
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> AssignGeneratorVariables(Dinfinity);
#I Assigned the global variables [ a, b ]
gap> Order(a); Order(b); Order(a*b);
2
2
infinity
gap> ZZ := FRGroup("t=<,t>[2,1]");
<self-similar group over [ 1 .. 2 ] with 1 generator>
tau := FRElement([[b,1],[1]],[()], [1]);
<2|f3>
gap> IsSubgroup(Dinfinity, ZZ);
false
gap> IsSubgroup(Dinfinity^tau, ZZ);
true
gap> Index(Dinfinity^tau, ZZ);
2
```

Example

```
gap> i4 := FRMonoid("s=(1,2)", "f=<s,f>[1,1]");
<self-similar monoid over [ 1 .. 2 ] with 2 generators>
gap> f := GeneratorsOfMonoid(i4){[1,2]};
gap> for i in [1..10] do Add(f, f[i]*f[i+1]); od;
gap> f[1]^2=One(m);
true
gap> f[2]^3=f[2];
true
gap> f[11]*f[10]^2=f[1]*Product(f{[5,7..11]}) *f[10];
true
gap> f[12]*f[11]^2=f[2]*Product(f{[6,8..12]}) *f[11];
true
```

Example

```
gap> i2 := FRSemigroup("f0=<f0,f0>(1,2)", "f1=<f1,f0>[2,2]");
<self-similar semigroup over [ 1 .. 2 ] with 2 generators>
gap> AssignGeneratorVariables(i2);
#I Assigned the global variables [ "f0", "f1" ]
gap> f0^2=One(i2);
true
gap> ForAll([0..10], p->(f0*f1)^p*(f1*f0)^p*f1=f1^2*(f0*f1)^p*(f1*f0)^p*f1);
true
```

7.1.2 SCGroup

◇ SCGroup(m)	(operation)
◇ SCGroupNC(m)	(operation)
◇ SCMonoid(m)	(operation)
◇ SCMonoidNC(m)	(operation)
◇ SCSemigroup(m)	(operation)
◇ SCSemigroupNC(m)	(operation)

Returns: The state-closed group/monoid/semigroup generated by the machine m .

This function constructs a new FR group/monoid/semigroup g , generated by all the states of the FR machine m . There is a bijective correspondence between `GeneratorsOfFRMachine(m)` and the generators of g , which is accessible via `Correspondence(g)` (See [Correspondence \(7.1.3\)](#)); it is a homomorphism from the stateset of m to g , or a list indicating for each state of m a corresponding generator index in the generators of g (with negatives for inverses, and 0 for identity).

In the non-NC forms, redundant (equal, trivial or mutually inverse) states are removed from the generating set of g .

Example

```
gap> b := MealyMachine([[3,2],[3,1],[3,3]],[(1,2),(),()]);; g := SCGroupNC(b);
<self-similar group over [ 1 .. 2 ] with 3 generators>
gap> Size(g);
infinity
gap> IsOne(Comm(g.2,g.2^g.1));
true
```

Example

```
gap> i4machine := MealyMachine([[3,3],[1,2],[3,3]],[(1,2),[1,1],()]);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> IsInvertible(i4machine);
false
gap> i4 := SCMonoidNC(i4machine);
<self-similar monoid over [ 1 .. 2 ] with 3 generators>
gap> f := GeneratorsOfMonoid(i4){[1,2]};;
gap> for i in [1..10] do Add(f,f[i]*f[i+1]); od;
gap> f[1]^2=One(m);
true
gap> f[2]^3=f[2];
true
gap> f[11]*f[10]^2=f[1]*Product(f{[5,7..11]})*f[10];
true
gap> f[12]*f[11]^2=f[2]*Product(f{[6,8..12]})*f[11];
true
```

Example

```
gap> i2machine := MealyMachine([[1,1],[2,1]],[(1,2),[2,2]]);
<Mealy machine on alphabet [ 1, 2 ] with 2 states>
gap> i2 := SCSemigroupNC(i2machine);
<self-similar semigroup over [ 1 .. 2 ] with 2 generators>
gap> f0 := GeneratorsOfSemigroup(i2)[1];; f1 := GeneratorsOfSemigroup(i2)[2];;
gap> f0^2=One(i2);
true
gap> ForAll([0..10],p->(f0*f1)^p*(f1*f0)^p*f1=f1^2*(f0*f1)^p*(f1*f0)^p*f1);
true
```

7.1.3 Correspondence (FR semigroup)

◇ `Correspondence(g)`

(attribute)

Returns: A correspondence between the generators of the underlying FR machine of g and g .

If g was created as the state closure of an FR machine m , this attribute records the correspondence between m and g .

If m is a group/monoid/semigroup/algebra FR machine, then `Correspondence(g)` is a homomorphism from the stateset of m to g .

If m is a Mealy or vector machine, then `Correspondence(g)` is a list, with in position i the index in the generating set of g of state number i . This index is 0 if there is no corresponding generator because the state is trivial, and is negative if there is no corresponding generator because the inverse of state number i is a generator.

See `SCGroupNC` (7.1.2), `SCGroup` (7.1.2), `SCMonoidNC` (7.1.2), `SCMonoid` (7.1.2), `SCSemigroupNC` (7.1.2), `SCSemigroup` (7.1.2), `SCAlgebraNC` (8.1.2), `SCAlgebra` (8.1.2), `SCAlgebraWithOneNC` (8.1.2), and `SCAlgebraWithOne` (8.1.2) for examples.

7.1.4 FullSCGroup

◇ `FullSCGroup(...)`

(function)

◇ `FullSCMonoid(...)`

(function)

◇ `FullSCSemigroup(...)`

(function)

Returns: A maximal state-closed group/monoid/semigroup on the alphabet a .

This function constructs a new FR group, monoid or semigroup, which contains all transformations with given properties of the tree with given alphabet.

The arguments can be, in any order: a semigroup, specifying which vertex actions are allowed; a set or domain, specifying the alphabet of the tree; an integer, specifying the maximal depth of elements; and a filter among `IsFinitaryFRElement` (5.2.10), `IsBoundedFRElement` (5.2.12), `IsPolynomialGrowthFRElement` (5.2.13) and `IsFiniteStateFRElement` (4.2.11).

This object serves as a container for all FR elements with alphabet a . Random elements can be drawn from it; they are Mealy elements with a random number of states, and with the required properties.

Example

```
gap> g := FullSCGroup([1..3]);
FullSCGroup([ 1 .. 3 ]);
gap> IsSubgroup(g, GuptaSidkiGroup);
true
gap> g := FullSCGroup([1..3], Group((1,2,3)));
FullSCGroup([ 1 .. 3 ], Group([ (1,2,3) ]))
gap> IsSubgroup(g, GuptaSidkiGroup);
true
gap> IsSubgroup(g, GrigorchukGroup);
false
gap> Random(g);
<Mealy element on alphabet [ 1, 2, 3 ] with 2 states, initial state 1>
gap> Size(FullSCGroup([1,2],3));
128
gap> g := FullSCMonoid([1..2]);
FullSCMonoid([ 1 .. 2 ])
gap> IsSubset(g, AsTrans(FullSCGroup([1..2])));
true
```

```

gap> IsSubset(g, AsTrans(GrigorchukGroup));
true
gap> g := FullSCSemigroup([1..3]);
FullSCSemigroup([ 1 .. 3 ])
gap> h := FullSCSemigroup([1..3], Semigroup(Trans([1,1,1])));
FullSCSemigroup([ 1 .. 3 ], Semigroup( [ Trans( [ 1, 1, 1 ] ) ] ))
gap> Size(h);
1
gap> IsSubset(g,h);
true
gap> g=FullSCMonoid([1..3]);
true

```

7.1.5 FRMachineFRGroup

- ◇ `FRMachineFRGroup(g)` (operation)
- ◇ `FRMachineFRMonoid(g)` (operation)
- ◇ `FRMachineFRSemigroup(g)` (operation)
- ◇ `MealyMachineFRGroup(g)` (operation)
- ◇ `MealyMachineFRMonoid(g)` (operation)
- ◇ `MealyMachineFRSemigroup(g)` (operation)

Returns: A machine describing all generators of g .

This function constructs a new group/monoid/semigroup/Mealy FR machine, with (at least) one generator per generator of g . This is done by adding all machines of all generators of g , and minimizing.

In particular, if g is state-closed, then `SCGroup(FRMachineFRGroup(g))` gives a group isomorphic to g , and similarly for monoids and semigroups.

Example

```

gap> FRMachineFRGroup(GuptaSidkiGroup);
<FR machine with alphabet [ 1 .. 3 ] on Group( [ f11, f12 ] )>
gap> Display(last);
  G   |      1      2      3
-----+-----+-----+-----+
  f11 | <id>,2    <id>,3    <id>,1
  f12 | f11,1    f11^-1,2    f12,3
-----+-----+-----+-----+

```

Example

```

gap> FRMachineFRMonoid(I4Monoid);
<FR machine with alphabet [ 1 .. 2 ] on Monoid( [ m11, m12 ], ... )>
gap> Display(last);
  M   |      1      2
-----+-----+-----+
  m11 | <id>,2    <id>,1
  m12 | m11,1    m12,1
-----+-----+-----+

```

Example

```

gap> FRMachineFRSemigroup(I2Monoid);
<FR machine with alphabet [ 1 .. 2 ] on Semigroup( [ s11, s12, s1 ] )>
gap> Display(last);
  S   |      1      2
-----+-----+-----+

```

```

-----+-----+-----+
s11 | s11,1    s11,2
s12 | s12,2    s12,1
s1  | s1,2     s12,2
-----+-----+-----+

```

7.1.6 IsomorphismFRGroup

◇ IsomorphismFRGroup(g) (operation)

◇ IsomorphismFRMonoid(g) (operation)

◇ IsomorphismFRSemigroup(g) (operation)

Returns: An isomorphism towards a group/monoid/semigroup on a single FR machine.

This function constructs a new FR group/monoid/semigroup, such that all elements of the resulting object have the same underlying group/monoid/semigroup FR machine.

Example

```

gap> phi := IsomorphismFRGroup(GuptaSidkiGroup);
[ <Mealy element on alphabet [ 1, 2, 3 ] with 2 states, initial state 1>,
  <Mealy element on alphabet [ 1, 2, 3 ] with 4 states, initial state 1> ] ->
[ <3|identity ...>, <3|f1>, <3|f1^-1>, <3|f2> ]
gap> Display(GuptaSidkiGroup.2);
| 1      2      3
---+---+---+---+
a | a,1   a,2   a,3
b | a,2   a,3   a,1
c | a,3   a,1   a,2
d | b,1   c,2   d,3
---+---+---+---+
Initial state: d
gap> Display(GuptaSidkiGroup.2^phi);
|      1      2      3
---+---+---+---+
f1 | <id>,2  <id>,3  <id>,1
f2 |  f1,1   f1^-1,2  f2,3
---+---+---+---+
Initial state: f2

```

Example

```

gap> phi := IsomorphismFRSemigroup(I2Monoid);
MappingByFunction( I2, <self-similar semigroup over [ 1 .. 2 ] with
3 generators>, <Operation "AsSemigroupFRElement"> )
gap> Display(GeneratorsOfSemigroup(I2Monoid)[3]);
| 1      2
---+---+---+
a | a,2   b,2
b | b,2   b,1
---+---+---+
Initial state: a
gap> Display(GeneratorsOfSemigroup(I2Monoid)[3]^phi);
S | 1      2
---+---+---+
s1 | s1,2   s2,2
s2 | s2,2   s2,1

```

```
-----+-----+-----+
Initial state: s1
```

Example

```
gap> phi := IsomorphismFRMonoid(I4Monoid);
MappingByFunction( I4, <self-similar monoid over [ 1 .. 2 ] with
2 generators>, <Operation "AsMonoidFRElement"> )
gap> Display(GeneratorsOfMonoid(I4Monoid)[1]);
  | 1      2
---+-----+-----+
a | b,2    b,1
b | b,1    b,2
---+-----+-----+
Initial state: a
gap> Display(GeneratorsOfMonoid(I4Monoid)[1]^phi);
M |      1      2
---+-----+-----+
m1 | <id>,2    <id>,1
---+-----+-----+
Initial state: m1
```

7.1.7 IsomorphismMealyGroup

◇ `IsomorphismMealyGroup(g)` (operation)

◇ `IsomorphismMealyMonoid(g)` (operation)

◇ `IsomorphismMealySemigroup(g)` (operation)

Returns: An isomorphism towards a group/monoid/semigroup all of whose elements are Mealy machines.

This function constructs a new FR group/monoid/semigroup, such that all elements of the resulting object are Mealy machines.

Example

```
gap> G := FRGroup("a=(1,2)", "b=<a,b>", "c=<c,b>");
<self-similar group over [ 1 .. 2 ] with 3 generators>
gap> phi := IsomorphismMealyGroup(G);
[ <2|a>, <2|b>, <2|c> ] ->
[ <Mealy element on alphabet [ 1, 2 ] with 2 states, initial state 1>,
  <Mealy element on alphabet [ 1, 2 ] with 3 states, initial state 1>,
  <Mealy element on alphabet [ 1, 2 ] with 4 states, initial state 1> ]
gap> Display(G.3);
  |      1      2
---+-----+-----+
a | <id>,2    <id>,1
b |   a,1     b,2
c |   c,1     b,2
---+-----+-----+
Initial state: c
gap> Display(G.3^phi);
  | 1      2
---+-----+-----+
a | a,1    b,2
b | c,1    b,2
c | d,2    d,1
```

```

d | d,1    d,2
---+-----+-----+
Initial state: a

```

7.1.8 FRGroupByVirtualEndomorphism

◇ `FRGroupByVirtualEndomorphism(hom[, transversal])` (operation)

Returns: A new self-similar group.

This function constructs a new FR group P , generated by group FR elements. Its first argument is a virtual endomorphism of a group G , i.e. a homomorphism from a subgroup H to G . The constructed FR group acts on a tree with alphabet a transversal of H in G (represented as $[1..d]$), and is a homomorphic image of G . The stabilizer of the first-level vertex corresponding to the trivial coset is the image of H . This function is loosely speaking an inverse of `VirtualEndomorphism` (7.2.25).

The optional second argument is a transversal of H in G , either of type `IsRightTransversal` or a list.

Furthermore, an option "MealyElement" can be passed to the function, as `FRGroupByVirtualEndomorphism(f:MealyElement)`, to require the resulting group to be generated by Mealy elements and not FR elements. The call will succeed, of course, only if the representation of G is finite-state.

The resulting FR group has an attribute `Correspondence(P)` that records a homomorphism from G to P .

The example below constructs the binary adding machine, and a non-standard representation of it.

Example

```

gap> G := FreeGroup(1);
<free group on the generators [ f1 ]>
gap> f := GroupHomomorphismByImages(Group(G.1^2), G, [G.1^2], [G.1]);
[ f1^2 ] -> [ f1 ]
gap> H := FRGroupByVirtualEndomorphism(f);
<self-similar group over [ 1 .. 2 ] with 1 generator>
gap> Display(H.1);
      |      1      2
----+-----+-----+
x1 | <id>,2    x1,1
----+-----+-----+
Initial state: x1
gap> Correspondence(H);
[ f1 ] -> [ <2|x1> ]
gap> H := FRGroupByVirtualEndomorphism(f, [G.1^0, G.1^3]);
gap> Display(H.1);
      |      1      2
----+-----+-----+
x1 | x1^-1,2    x1^2,1
----+-----+-----+
Initial state: x1
gap> H := FRGroupByVirtualEndomorphism(f:MealyElement);
<self-similar group over [ 1 .. 2 ] with 1 generator>
gap> Display(H.1);
      |      1      2
---+-----+-----+
a | b,2    a,1

```

```

b | b,1   b,2
---+-----+-----+
Initial state: a

```

7.1.9 TreeWreathProduct (FR group)

◇ `TreeWreathProduct(g, h, x0, y0)` (operation)

Returns: The tree-wreath product of groups g, h .

The tree-wreath product of two FR groups is a group generated by a copy of g and of h , in such a way that many conjugates of g commute.

More formally, assume without loss of generality that all generators of g are states of a machine m , and that all generators of h are states of a machine n . Then the tree-wreath product is generated by the images of generators of g, h in `TreeWreathProduct(m, n, x0, y0)`.

For the operation on FR machines see `TreeWreathProduct` (3.5.8)). It is described (with small variations, and in lesser generality) in [Sid05]. For example, in

Example

```

gap> w := TreeWreathProduct(AddingGroup(2), AddingGroup(2), 1, 1);
<recursive group over [ 1 .. 4 ] with 2 generators>
gap> a := w.1; b := w.2;
<Mealy element on alphabet [ 1 .. 4 ] with 3 states>
<Mealy element on alphabet [ 1 .. 4 ] with 2 states>
gap> Order(a); Order(b);
infinity
infinity
gap> ForAll([-100..100], i->IsOne(Comm(a, a^(b^i))));
true

```

the group w is the wreath product $Z \wr Z$.

7.1.10 WeaklyBranchedEmbedding

◇ `WeaklyBranchedEmbedding(g)` (operation)

Returns: A embedding of g in a weakly branched group.

This function constructs a new FR group, on alphabet the square of the alphabet of g . It is generated by the canonical copy of g and by the tree-wreath product of g with an adding machine on the same alphabet as g (see `TreeWreathProduct` (7.1.9)). The function returns a group homomorphism into this new FR group.

The main result of [SW03] is that the resulting group h is weakly branched. More precisely, h' contains $|X|^2$ copies of itself. `gap> f := WeaklyBranchedEmbedding(BabyAleshinGroup);`
`gap> Range(f);` <recursive group over [1 .. 4] with 8 generators> constructs a finitely generated branched group containing a free subgroup.

7.2 Operations for FR semigroups

7.2.1 PermGroup

◇ `PermGroup(g, l)` (operation)

◇ `EpimorphismPermGroup(g, l)` (operation)

Returns: [An epimorphism to] the permutation group of g 's action on level l .

The first function returns a permutation group on d^l points, where d is the size of g 's alphabet. It has as many generators as g , and represents the action of g on the l th layer of the tree.

The second function returns a homomorphism from g to this permutation group.

Example

```
gap> g := FRGroup("a=(1,2)", "b=<a,>"); Size(g);
<self-similar group over [ 1 .. 2 ] with 2 generators>
8
gap> PermGroup(g,2);
Group([ (1,3)(2,4), (1,2) ])
gap> PermGroup(g,3);
Group([ (1,5)(2,6)(3,7)(4,8), (1,3)(2,4) ])
gap> List([1..6], i->LogInt(Size(PermGroup(GrigorchukGroup,i)),2));
[ 1, 3, 7, 12, 22, 42 ]
gap> g := FRGroup("t=<,t>(1,2)"); Size(g);
<self-similar group over [ 1 .. 2 ] with 1 generator>
infinity
gap> pi := EpimorphismPermGroup(g,5);
MappingByFunction( <self-similar group over [ 1 .. 2 ] with 1 generator,
of size infinity>, Group([ (1,17,9,25,5,21,13,29,3,19,11,27,7,23,15,31,
2,18,10,26,6,22,14,30,4,20,12,28,8,24,16,32) ]), function( w ) ... end )
gap> Order(g.1);
infinity
gap> Order(g.1^pi);
32
```

7.2.2 PcGroup

◇ **PcGroup(g, l)**

(operation)

◇ **EpimorphismPcGroup(g, l)**

(operation)

Returns: [An epimorphism to] the pc group of g 's action on level l .

The first function returns a polycyclic group representing the action of g on the l th layer of the tree. It converts the permutation group `PermGroup(g, l)` to a Pc group, in which computations are often faster.

The second function returns a homomorphism from g to this pc group.

Example

```
gap> g := PcGroup(GrigorchukGroup,7); time;
<pc group with 5 generators>
3370
gap> NormalClosure(g,Group(g.3)); time;
<pc group with 79 generators>
240
gap> g := PermGroup(GrigorchukGroup,7); time;
<permutation group with 5 generators>
3
gap> NormalClosure(g,Group(g.3)); time;
<permutation group with 5 generators>
5344
gap> g := FRGroup("t=<,t>(1,2)"); Size(g);
<self-similar group over [ 1 .. 2 ] with 1 generator>
infinity
gap> pi := EpimorphismPcGroup(g,5);
```

```
MappingByFunction( <self-similar group over [ 1 .. 2 ] with
1 generator, of size infinity>, Group([ f1, f2, f3, f4, f5 ]), function( w ) ... end )
gap> Order(g.1);
infinity
gap> Order(g.1^pi);
32
```

7.2.3 TransMonoid

- ◇ TransMonoid(g , l) (operation)
- ◇ TransformationMonoid(g , l) (operation)
- ◇ EpimorphismTransMonoid(g , l) (operation)
- ◇ EpimorphismTransformationMonoid(g , l) (operation)

Returns: [An epimorphism to] the transformation monoid of g 's action on level l .

The first function returns a transformation monoid on d^l points, where d is the size of g 's alphabet. It has as many generators as g , and represents the action of g on the l th layer of the tree.

The second function returns a homomorphism from g to this transformation monoid.

Example

```
gap> i4 := SCMonoid(MealyMachine([[3,3],[1,2],[3,3]],[(1,2),[1,1],()]]);
<self-similar monoid over [ 1 .. 2 ] with 3 generators>
gap> g := TransMonoid(i4,6);
<monoid with 3 generators>
gap> List([1..6],i->Size(TransMonoid(i4,i)));
[ 4, 14, 50, 170, 570, 1882 ]
gap> Collected(List(g,RankOfTrans));
[ [ 1, 64 ], [ 2, 1280 ], [ 4, 384 ], [ 8, 112 ], [ 16, 32 ], [ 32, 8 ], [ 64, 2 ] ]
gap> pi := EpimorphismTransMonoid(i4,9);
MappingByFunction( <self-similar monoid over [ 1 .. 2 ] with 3 generators>,
<monoid with 3 generators>, function( w ) ... end )
gap> f := GeneratorsOfMonoid(i4){[1,2]};
gap> for i in [1..10] do Add(f,f[i]*f[i+1]); od;
gap> Product(f{[3,5,7,9,11]})=f[11]*f[10];
false
gap> Product(f{[3,5,7,9,11]})^pi=(f[11]*f[10])^pi;
true
```

7.2.4 TransSemigroup

- ◇ TransSemigroup(g , l) (operation)
- ◇ TransformationSemigroup(g , l) (operation)
- ◇ EpimorphismTransSemigroup(g , l) (operation)
- ◇ EpimorphismTransformationSemigroup(g , l) (operation)

Returns: [An epimorphism to] the transformation semigroup of g 's action on level l .

The first function returns a transformation semigroup on d^l points, where d is the size of g 's alphabet. It has as many generators as g , and represents the action of g on the l th layer of the tree.

The second function returns a homomorphism from g to this transformation semigroup.

Example

```
gap> i2 := SCSemigroup(MealyMachine([[1,1],[2,1]],[(1,2),[2,2]]));
<self-similar semigroup over [ 1 .. 2 ] with 2 generators>
gap> g := TransSemigroup(i2,6);
```

```

<semigroup with 2 generators>
gap> List([1..6], i->Size(TransSemigroup(i2,i)));
[ 4, 14, 42, 114, 290, 706 ]
gap> Collected(List(g, RankOfTrans));
[ [ 1, 64 ], [ 2, 384 ], [ 4, 160 ], [ 8, 64 ], [ 16, 24 ], [ 32, 8 ], [ 64, 2 ] ]
gap> f0 := GeneratorsOfSemigroup(i2)[1];; f1 := GeneratorsOfSemigroup(i2)[2];;
gap> pi := EpimorphismTransSemigroup(i2,10);
MappingByFunction( <self-similar semigroup over [ 1 .. 2 ] with
2 generators>, <semigroup with 2 generators>, function( w ) ... end )
gap> (f1*(f1*f0)^10)=(f1*f0)^10;
false
gap> (f1*(f1*f0)^10)^pi=((f1*f0)^10)^pi;
true

```

7.2.5 EpimorphismGermGroup

◇ `EpimorphismGermGroup(g , l)` (operation)

◇ `EpimorphismGermGroup(g)` (operation)

Returns: A homomorphism to a polycyclic group.

This function returns an epimorphism to a polycyclic group, encoding the action on the first l levels of the tree and on the germs below. If l is omitted, it is assumed to be 0.

Since the elements of g are finite automata, they map periodic sequences to periodic sequences. The action on the periods, and in the immediate vicinity of them, is called the *germ action* of g . This function returns the natural homomorphism from g to the wreath product of this germ group with the quotient of g acting on the l th layer of the tree.

The germ group, by default, is abelian. If it is finite, this function returns a homomorphism to a Pc group; otherwise, a homomorphism to a polycyclic group.

The GrigorchukEvilTwin (10.1.11) is, for now, the only example with a hand-coded, non-abelian germ group.

Example

```

gap> EpimorphismGermGroup(GrigorchukGroup,0);
MappingByFunction( GrigorchukGroup, <pc group of size 4 with 2 generators>,
function( g ) ... end )
gap> List(GeneratorsOfGroup(GrigorchukGroup), x->x^last);
[ <identity> of ..., f1, f1*f2, f2 ]
gap> StructureDescription(Image(last2));
"C2 x C2"
gap> g := FRGroup("t=<,t>(1,2)", "m=<,m^-1>(1,2)");;
gap> EpimorphismGermGroup(g,0);
MappingByFunction( <state-closed, bounded group over [ 1, 2 ] with 2
generators>, Pcp-group with orders [ 0, 0 ], function( x ) ... end )
gap> EpimorphismGermGroup(g,1);; Range(last); Image(last2);
Pcp-group with orders [ 2, 0, 0, 0, 0 ]
Pcp-group with orders [ 2, 0, 0, 0 ]

```

7.2.6 StabilizerImage

◇ `StabilizerImage(g , v)` (operation)

Returns: The group of all states at v of elements of g .

This function constructs a new FR group, containing all states at vertex v (which can be an integer or a list) of elements of g .

The result is g itself precisely if g is recurrent (see `IsRecurrentFRSemigroup` (7.2.10)).

Example

```
gap> G := FRGroup("t=<,t>(1,2)", "u=<,u^-1>(1,2)", "b=<u,t>");
<self-similar group over [ 1 .. 2 ] with 3 generators>
gap> Stabilizer(G,1);
<self-similar group over [ 1 .. 2 ] with 5 generators>
gap> GeneratorsOfGroup(last);
[ <2|u*t^-1>, <2|b>, <2|t^2>, <2|t*u>, <2|t*b*t^-1> ]
gap> StabilizerImage(G,1);
<self-similar group over [ 1 .. 2 ] with 5 generators>
gap> GeneratorsOfGroup(last);
[ <2|identity ...>, <2|u>, <2|t>, <2|u^-1>, <2|t> ]
```

7.2.7 LevelStabilizer

◇ `LevelStabilizer(g , n)`

(operation)

Returns: The fixator of the n th level of the tree.

This function constructs the normal subgroup of g that fixes the n th level of the tree.

Example

```
gap> G := FRGroup("t=<,t>(1,2)", "a=(1,2)");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> LevelStabilizer(G,2);
<self-similar group over [ 1 .. 2 ] with 9 generators>
gap> Index(G,last);
8
gap> IsNormal(G,last2);
true
```

7.2.8 IsStateClosedFRSemigroup

◇ `IsStateClosedFRSemigroup(g)`

(property)

Returns: true if all states of elements of g belong to g .

This function tests whether g is a *state-closed* group, i.e. a group such that all states of all elements of g belong to g .

The smallest state-closed group containing g is computed with `StateClosure` (7.2.9).

Example

```
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> AssignGeneratorVariables(Dinfinity);
#I Assigned the global variables [ a, b ]
gap> IsStateClosedFRSemigroup(Group(a));
IsStateClosedFRSemigroup(Group(b));
IsStateClosedFRSemigroup(Dinfinity);
true
false
true
```

7.2.9 StateClosure

◇ StateClosure(g)

(operation)

Returns: The smallest state-closed group containing g .

This function computes the smallest group containing all states of all elements of g , i.e. the smallest group containing g and for which IsStateClosedFRSemigroup (7.2.8) returns true.

Example

```
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> AssignGeneratorVariables(Dinfinity);
#I Assigned the global variables [ a, b ]
gap> StateStateClosure(Group(a))=Dinfinity; StateClosure(Group(b))=Dinfinity;
false
true
```

7.2.10 IsRecurrentFRSemigroup

◇ IsRecurrentFRSemigroup(g)

(property)

Returns: true if g is a recurrent group.

This function returns true if g is a *recurrent* group, i.e. if, for every vertex v , all elements of g appear as states at v of elements fixing v .

Example

```
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> AssignGeneratorVariables(Dinfinity);
#I Assigned the global variables [ a, b ]
gap> IsRecurrentFRSemigroup(Group(a)); IsRecurrentFRSemigroup(Group(b));
false
false
gap> IsRecurrentFRSemigroup(Dinfinity);
true
```

7.2.11 IsLevelTransitive (FR group)

◇ IsLevelTransitive(g)

(property)

Returns: true if g is a level-transitive group.

This function returns true if g is a *level-transitive* group, i.e. if the action of g is transitive at every level of the tree on which it acts.

Example

```
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> AssignGeneratorVariables(Dinfinity);
#I Assigned the global variables [ a, b ]
gap> IsLevelTransitive(Group(a)); IsLevelTransitive(Group(b));
IsLevelTransitive(Dinfinity);
false
false
true
```

7.2.12 IsInfinitelyTransitive

◇ `IsInfinitelyTransitive(g)`

(property)

Returns: true if g is infinitely transitive.

This function returns true if g is an *infinitely transitive* group. This means that g is the state-closed group of a bireversible Mealy machine (see `IsBireversible` (5.2.7)), that this Mealy machine has an involution on its alphabet (see `AlphabetInvolution` (5.2.6)), and that the action of the set of reduced words of any given length over the alphabet (where "reduced" means no successive letters related by the involution) is transitive.

This notion is of fundamental importance for the study of lattices in a product of trees.

Example

```
gap> !!!
```

7.2.13 IsFinitaryFRSemigroup

◇ `IsFinitaryFRSemigroup(g)`

(property)

◇ `IsWeaklyFinitaryFRSemigroup(g)`

(property)

◇ `IsBoundedFRSemigroup(g)`

(property)

◇ `IsPolynomialGrowthFRSemigroup(g)`

(property)

◇ `IsFiniteStateFRSemigroup(g)`

(property)

Returns: true if all elements of g have the required property.

This function returns true if all elements of g have the required property, as FR elements; see `IsFinitaryFRElement` (5.2.10), `IsWeaklyFinitaryFRElement` (5.2.23), `IsBoundedFRElement` (5.2.12), `IsPolynomialGrowthFRElement` (5.2.13) and `IsFiniteStateFRElement` (4.2.11).

Example

```
gap> G := FRGroup("a=(1,2)", "b=<a,b>", "c=<c,b>", "d=<d,d>(1,2)");
<self-similar group over [ 1 .. 2 ] with 4 generators>
gap> L := [Group(G.1), Group(G.1, G.2), Group(G.1, G.2, G.3), G];
gap> List(L, IsFinitaryFRSemigroup);
[ true, false, false, false ]
gap> List(L, IsBoundedFRSemigroup);
[ true, true, false, false ]
gap> List(L, IsPolynomialGrowthFRSemigroup);
[ true, true, true, false ]
gap> List(L, IsFiniteStateFRSemigroup);
[ true, true, true, true ]
```

7.2.14 Degree (FR semigroup)

◇ `Degree(g)`

(attribute)

◇ `DegreeOfFRSemigroup(g)`

(attribute)

◇ `Depth(g)`

(attribute)

◇ `DepthOfFRSemigroup(g)`

(attribute)

Returns: The maximal degree/depth of elements of g .

This function returns the maximal degree/depth of elements of g ; see `Degree` (5.2.9) and `Depth` (5.2.11).

Example

```
gap> G := FRGroup("a=(1,2)", "b=<a,b>", "c=<c,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
```

```
gap> Degree(Group(G.1)); Degree(Group(G.1,G.2)); Degree(G);
0
1
2
gap> Depth(Group(G.1)); Depth(Group(G.1,G.2)); Depth(G);
1
infinity
infinity
```

7.2.15 HasOpenSetConditionFRSemigroup

◇ **HasOpenSetConditionFRSemigroup(e)** (property)

Returns: true if g has the open set condition.

This function returns true if all elements of g have the *open set condition*, see HasOpenSetConditionFRElement (5.2.25).

Example

```
gap> HasOpenSetConditionFRSemigroup(GrigorchukGroup);
false
gap> HasOpenSetConditionFRSemigroup(BinaryAddingGroup);
true
```

7.2.16 IsContracting

◇ **IsContracting(g)** (property)

Returns: true if g is a contracting semigroup.

This function returns true if g is a *contracting* semigroup, i.e. if there exists a finite subset n of g such that the LimitStates (4.2.10) of every element of g belong to n .

The minimal such n can be computed with NucleusOfFRSemigroup (7.2.17).

Example

```
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> IsContracting(Dinfinity);
true
```

7.2.17 NucleusOfFRSemigroup

◇ **NucleusOfFRSemigroup(g)** (attribute)

Returns: The nucleus of the contracting semigroup g .

This function returns the *nucleus* of the contracting semigroup g , i.e. the smallest subset n of g such that the LimitStates (4.2.10) of every element of g belong to n .

This function returns fail if no such n exists. Usually, it loops forever without being able to decide whether n is finite or infinite. It succeeds precisely when IsContracting(g) succeeds.

Example

```
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> NucleusOfFRSemigroup(Dinfinity);
[ <2|identity ...>, <2|b>, <2|a> ]
```

7.2.18 NucleusMachine (FR semigroup)

◇ NucleusMachine(g)

(attribute)

Returns: The nucleus machine of the contracting semigroup g .

This function returns the *nucleus* of the contracting semigroup g , see NucleusOfFRSemigroup (7.2.17), in the form of a Mealy machine.

Since all states of the nucleus are elements of the nucleus, the transition and output function may be restricted to the nucleus, defining a Mealy machine. Finitely generated recurrent groups are generated by their nucleus machine.

This function returns fail if no such n exists. Usually, it loops forever without being able to decide whether n is finite or infinite. It succeeds precisely when IsContracting(g) succeeds.

Example

```
gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> M := NucleusMachine(Dinfinity);
<Mealy machine on alphabet [ 1, 2 ] with 3 states>
gap> Display(M);
  | 1      2
---+-----+-----+
a | a,1    a,2
b | c,1    b,2
c | a,2    a,1
---+-----+-----+
gap> Dinfinity=SCGroup(M);
true
```

7.2.19 BranchingSubgroup

◇ BranchingSubgroup(g)

(operation)

Returns: A branching subgroup of g .

This function searches for a subgroup k of g , such that k contains $k \times \cdots \times k$.

It searches for elements in larger and larger balls in g , calling FindBranchingSubgroup (7.2.20).

Example

```
gap> K := BranchingSubgroup(GrigorchukGroup);
<self-similar group over [ 1 .. 2 ] with 9 generators>
gap> IsBranchingSubgroup(K);
true
gap> IsBranched(GrigorchukGroup);
true
gap> Index(GrigorchukGroup, K);
16
```

7.2.20 FindBranchingSubgroup

◇ FindBranchingSubgroup(g , l , r)

(operation)

Returns: A branching subgroup of g .

This function searches for a subgroup k of g , such that k contains $k \times \cdots \times k$.

The second argument l specifies the level at which branching must occur; i.e. asks to search for a subgroup k such that g contains k^{d^l} where d is the size of the alphabet. If $l=\text{infinity}$, the resulting k will be a regularly branched subgroup.

The third argument r specifies the radius to explore in \mathcal{G} and all branching subgroups at levels smaller than l for elements with all level-1 states trivial except one.

Example

```
gap> FindBranchingSubgroup(GrigorchukGroup,1,4);
<self-similar group over [ 1 .. 2 ] with 8 generators>
gap> Index(GrigorchukGroup,last);
8
gap> FindBranchingSubgroup(GrigorchukGroup,2,4);
<self-similar group over [ 1 .. 2 ] with 6 generators>
gap> Index(GrigorchukGroup,last);
16
gap> FindBranchingSubgroup(GrigorchukGroup,3,4);
<self-similar group over [ 1 .. 2 ] with 9 generators>
gap> Index(GrigorchukGroup,last);
16
```

7.2.21 IsBranched (FR group)

◇ IsBranched(\mathcal{G})

(property)

Returns: true if \mathcal{G} has a finite-index branching subgroup.

This function returns true if \mathcal{G} has a finite-index subgroup k , such that k contains $k \times \cdots \times k$.

Example

```
<Example><![CDATA[
gap> K := BranchingSubgroup(GrigorchukGroup);
<self-similar group over [ 1 .. 2 ] with 9 generators>
gap> IsBranchingSubgroup(K);
true
gap> IsBranched(GrigorchukGroup);
true
gap> Index(GrigorchukGroup,K);
16
```

7.2.22 IsBranchingSubgroup (FR semigroup)

◇ IsBranchingSubgroup(k)

(property)

Returns: true if k is a branching subgroup.

This function returns true if k contains $k \times \cdots \times k$.

Example

```
gap> K := BranchingSubgroup(GrigorchukGroup);
<self-similar group over [ 1 .. 2 ] with 9 generators>
gap> IsBranchingSubgroup(K);
true
gap> IsBranched(GrigorchukGroup);
true
gap> Index(GrigorchukGroup,K);
16
```

7.2.23 TopVertexTransformations

◇ TopVertexTransformations(\mathcal{G})

(attribute)

Returns: The transformations at the root under the action of \mathcal{G} .

This function returns the permutation group, or the transformation group/semigroup/monoid, of all activities of all elements under the root vertex of the tree on which g acts.

It is a synonym for `PermGroup(g, 1)` or `TransMonoid(g, 1)` or `TransSemigroup(g, 1)`.

Example

```
gap> TopVertexTransformations(GrigorchukGroup);
Group([ (), (1,2) ])
gap> IsTransitive(last,AlphabetOfFRSemigroup(GrigorchukGroup));
true
gap> TopVertexTransformations(FullSCMonoid([1..3]));
<monoid with 3 generators>
gap> Size(last);
27
```

7.2.24 VertexTransformations (FR semigroup)

◇ `VertexTransformations(g)`

(attribute)

Returns: The transformations at all vertices under the action of g .

This function returns the permutation group, or the transformation group/monoid/semigroup, of all activities of all elements under all vertices of the tree on which g acts.

This is the smallest group/monoid/semigroup P such that g is a subset of `FullSCGroup(AlphabetOfFRSemigroup(g), P)` or `FullSCMonoid(AlphabetOfFRSemigroup(g), P)` or `FullSCSemigroup(AlphabetOfFRSemigroup(g), P)`.

Example

```
gap> VertexTransformations(GuptaSidkiGroup);
Group([ (), (1,2,3), (1,3,2) ])
gap> TopVertexTransformations(Group(GuptaSidkiGroup.2));
Group(())
gap> VertexTransformations(Group(GuptaSidkiGroup.2));
Group([ (), (1,2,3), (1,3,2) ])
```

7.2.25 VirtualEndomorphism

◇ `VirtualEndomorphism(g, v)`

(operation)

Returns: The virtual endomorphism at vertex v .

This function returns the homomorphism from `Stabilizer(g, v)` to g , defined by computing the state at v . It is loosely speaking an inverse of `FRGroupByVirtualEndomorphism` (7.1.8).

Example

```
gap> A := SCGroup(MealyMachine([[2,1],[2,2]],[(1,2),()]]);
<self-similar group over [ 1 .. 2 ] with 1 generator>
gap> f := VirtualEndomorphism(A,1);
MappingByFunction( <self-similar group over [ 1 .. 2 ] with
1 generator>, <self-similar group over [ 1 .. 2 ] with
1 generator>, function( g ) ... end )
gap> ((A.1)^2)^f=A.1;
true
gap> B := FRGroupByVirtualEndomorphism(f);
<self-similar group over [ 1 .. 2 ] with 1 generator>
gap> A=B;
true
```

◇ EpimorphismFromFpGroup(g, l) (operation)

Currently this command is implemented through an ad hoc method for `BinaryKneadingGroup` (10.1.2), `GrigorchukGroup` (10.1.9) and `GrigorchukOverGroup` (10.1.10).

7.2.27 IsomorphismSubgroupFpGroup

The second form returns an isomorphism to an L-presented group (see [Bar03a] and [EH07]. It requires the package NQL.

```

Example
gap> f := IsomorphismSubgroupFpGroup(BasilicaGroup);
MappingByFunction( BasilicaGroup, Group([ a^-1, a*t^-1*a^-1*t*a^-1
]), function( g ) ... end, function( w ) ... end )

```

```

gap> Range(f);
Group([ a^-1, a*t^-1*a^-1*t*a^-1 ])
gap> c := Comm(BasilicaGroup.1,BasilicaGroup.2);
<Mealy element on alphabet [ 1, 2 ] with 9 states, initial state 1>
gap> c^f;
t^-2*a*t^-1*a*t*a^-2*t*a*t^-2*a*t^-1*a*t*a^-1*t*a*t^-1*a*t^-2*
a^-1*t*a*t^-1*a*t^-1*a^-1*t*a^-1*t^5*a*t^-1*a^-1*t*a^-1
gap> PreImageElm(f,last);
<Mealy element on alphabet [ 1, 2 ] with 9 states, initial state 1>
gap> last=c;
true

```

7.3 Properties for infinite groups

7.3.1 IsTorsionGroup

◇ **IsTorsionGroup(g)**

(property)

Returns: true if g is a torsion group.

This function returns true if g is a torsion group, i.e. if every element in g has finite order; and false if g contains an element of infinite order.

This method is quite rudimentary, and is not guaranteed to terminate. At the minimum, g should be a group in which `Order()` succeeds in computing element orders; e.g. a bounded group in Mealy machine format.

Example

```

gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>":IsMealyElement);
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> IsTorsionGroup(Dinfinity);
false
gap> IsTorsionGroup(GrigorchukGroup); IsTorsionGroup(GuptaSidkiGroup);
true
true
gap> IsTorsionGroup(FabrykowskiGuptaGroup);
false

```

7.3.2 IsTorsionFreeGroup

◇ **IsTorsionFreeGroup(g)**

(property)

Returns: true if g is a torsion-free group.

This function returns true if g is a torsion-free group, i.e. if no element in g has finite order; and false if g contains an element of finite order.

This method is quite rudimentary, and is not guaranteed to terminate. At the minimum, g should be a group in which `Order()` succeeds in computing element orders; e.g. a bounded group in Mealy machine format.

Example

```

gap> Dinfinity := FRGroup("a=(1,2)", "b=<a,b>":IsMealyElement);
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> IsTorsionFreeGroup(Dinfinity);
false
gap> IsTorsionFreeGroup(BasilicaGroup);
true

```

7.3.3 IsAmenableGroup

◇ `IsAmenableGroup(g)`

(property)

Returns: true if *g* is an amenable group.

Amenable groups, introduced by von Neumann [vN29], are those groups that admit a finitely additive, translation-invariant measure.

Example

```
gap> IsAmenableGroup(FreeGroup(2));
false
gap> IsAmenableGroup(BasilicaGroup);
true
```

7.3.4 IsVirtuallySimpleGroup

◇ `IsVirtuallySimpleGroup(g)`

(property)

Returns: true if *g* admits a finite-index simple subgroup.

Example

```
true
```

7.3.5 IsResiduallyFinite

◇ `IsResiduallyFinite(obj)`

(property)

Returns: true if *obj* is residually finite.

An object is *residually finite* if it can be approximated arbitrarily well by finite quotients; i.e. if for every $g \neq h \in X$ there exists a finite quotient $\pi : X \rightarrow Q$ such that $g^\pi \neq h^\pi$.

Example

```
gap> IsResiduallyFinite(FreeGroup(2));
true
gap> IsResiduallyFinite(BasilicaGroup);
true
```

7.3.6 IsSQUniversal

◇ `IsSQUniversal(obj)`

(property)

Returns: true if *obj* is SQ-universal.

An object *obj* is *SQ-universal* if every countable object of the same category as *obj* is a subobject of a quotient of *obj*.

Example

```
gap> IsSQUniversal(FreeGroup(2));
true
```

7.3.7 IsJustInfinite

◇ `IsJustInfinite(obj)`

(property)

Returns: true if *obj* is just-infinite.

An object *obj* is *just-infinite* if *obj* is infinite, but every quotient of *obj* is finite.

Example

```
gap> IsJustInfinite(FreeGroup(2));  
false  
gap> IsJustInfinite(FreeGroup(1));  
true  
gap> IsJustInfinite(GrigorchukGroup); time  
true  
8284
```

Chapter 8

Algebras

Self-similar algebras and algebras with one (below *FR algebras*) are simply algebras [with one] whose elements are linear FR machines. They naturally act on the alphabet of their elements, which is a vector space.

Elements may be added, subtracted and multiplied. They can be vector or algebra linear elements; the vector elements are in general preferable, for efficiency reasons.

Finite-dimensional approximations of self-similar algebras can be computed; they are given as matrix algebras.

8.1 Creators for FR algebras

The most straightforward creation method for FR algebras is `Algebra()`, applied with linear FR elements as arguments. There are shortcuts to this somewhat tedious method:

8.1.1 FRAlgebra

◇ `FRAlgebra(ring, {definition, })` (operation)

◇ `FRAlgebraWithOne(ring, {definition, })` (operation)

Returns: A new self-similar algebra [with one].

This function constructs a new FR algebra [with one], generated by linear FR elements. It receives as argument any number of strings, each of which represents a generator of the object to be constructed.

ring is the acting domain of the vector space on which the algebra will act.

Each *definition* is of the form `"name=[[...],...,[...]]"` or of the form `"name=[[...],...,[...]]:out"`, namely a matrix whose entries are algebraic expressions in the names, possibly using 0,1, optionally followed by a scalar. The matrix entries specify the decomposition of the element being defined, and the optional scalar specifies the output of that element, by default assumed to be one.

The option `IsVectorElement`, passed e.g. as in `FRAlgebra(Rationals, "a=[[a,1],[a,0]]":IsVectorElement)` asks for the resulting algebra to be generated by vector elements. The generators must of course be finite-state. Their names ("a",...) are not remembered in the constructing algebra (but can be set using `SetName` (**Reference: SetName**)).

Example

```
gap> m := FRAlgebra(Rationals, "a=[[1,a],[a,0]]");
<self-similar algebra on alphabet Rationals^2 with 1 generator>
```

```
gap> Display(Activity(m.1,2));
[ [ 1, 0, 1, 1 ],
  [ 0, 1, 1, 0 ],
  [ 1, 1, 0, 0 ],
  [ 1, 0, 0, 0 ] ]
```

8.1.2 SCAlgebra

◇ SCAlgebra(*m*) (operation)

◇ SCAlgebraWithOne(*m*) (operation)

◇ SCAlgebraNC(*m*) (operation)

◇ SCAlgebraWithOneNC(*m*) (operation)

Returns: The state-closed algebra [with one] generated by the machine *m*.

This function constructs a new FR algebra [with one] *a*, generated by all the states of the FR machine *m*. There is a bijective correspondence between `GeneratorsOfFRMachine(m)` and the generators of *a*, which is accessible via `Correspondence(a)` (See `Correspondence` (7.1.3)); it is a homomorphism from the stateset of *m* to *a*, or a list indicating for each state of *m* a corresponding generator index in the generators of *a* (with 0 for identity).

In the non-NC forms, redundant (equal, zero or one) states are removed from the generating set of *a*.

Example

```
gap> a := SCAlgebra(AsLinearMachine(Rationals,I4Machine));
<self-similar algebra on alphabet Rationals^2 with 3 generators>
gap> a.1 = AsLinearElement(Rationals,I4Monoid.1);
true
```

8.1.3 BranchingIdeal

◇ BranchingIdeal(*A*) (operation)

Returns: An ideal *I* that contains matrices over itself.

Example

```
gap> !!!
```

8.2 Operations for FR algebras

8.2.1 MatrixQuotient

◇ MatrixQuotient(*a*, *l*) (operation)

◇ EpimorphismMatrixQuotient(*a*, *l*) (operation)

Returns: The matrix algebra of *a*'s action on level *l*.

The first function returns the matrix algebra generated by the activities of *a* on level *l* (see the examples in 6.1.6). The second function returns an algebra homomorphism from *a* to the matrix algebra.

Example

```
gap> a := ThinnedAlgebraWithOne(GF(2),GrigorchukGroup);
<self-similar algebra-with-one on alphabet GF(2)^2 with 4 generators>
gap> List([0..4],i->Dimension(MatrixQuotient(a,i)));
[ 1, 2, 6, 22, 78 ]
```

8.2.2 ThinnedAlgebra

◇ `ThinnedAlgebra(r , g)`

(operation)

◇ `ThinnedAlgebraWithOne(r , g)`

(operation)

Returns: The thinned algebra [with one] associated with g .

The first function returns the thinned algebra of a FR group/monoid/semigroup g , over the domain r . This is the linear envelope of g in its natural action on sequences.

The embedding of g in its thinned algebra is returned by `Embedding(g , a)`.

Example

```
gap> a := ThinnedAlgebraWithOne(GF(2), GrigorchukGroup);
<self-similar algebra on alphabet GF(2)^2 with 5 generators>
gap> a.1 = GrigorchukGroup.1^Embedding(GrigorchukGroup, a);
true
gap> Dimension(VectorSpace(GF(2), [One(a), a.2, a.3, a.4]));
3
```

8.2.3 Nillity

◇ `Nillity(x)`

(operation)

Returns: The smallest n such that $x^n = 0$.

This command computes the nillity of x , i.e. the smallest n such that $x^n = 0$. The command is of course not guaranteed to terminate.

Chapter 9

Iterated monodromy groups

Iterated monodromy machines are a special class of group FR machines (see Section 3) with attribute `IMGRelator` (9.1.2). This attribute records a cyclic ordering of the generators of the machine whose product is trivial.

The interpretation is the following: the machine encodes a *Thurston map*, i.e. a post-critically finite topological branched self-covering of the sphere S^2 . Generators of the machine correspond to loops in the fundamental group of the sphere (punctured at post-critical points), that circle once counter-clockwise around a post-critical point. For more details on the connection between self-similar groups and Thurston maps, see [Nek05].

IMG FR elements are a bit different from group FR elements: while we said a group FR element is trivial if and only if its action on sequences is trivial, we say that an IMG FR element g is trivial if there exists an integer N such that unfolding N times the recursion for g yields only trivial states (as elements of the underlying free group).

9.1 Creators and operations for IMG FR machines

9.1.1 IMGFRMachine (FR machine)

◇ `IMGFRMachine(m [, w])` (operation)

Returns: An IMG FR machine.

This function creates a new IMG FR machine, starting from a group FR machine m . If a state w is specified, it is used as IMG relator; otherwise, if some ordering of the generators is trivial, it is used as a relator; in other cases, an additional generator is added to the machine in such a way that a product of generators is trivial.

A standard FR machine can be recovered from an IMG FR machine by `AsGroupFRMachine` (3.3.4), `AsMonoidFRMachine` (3.3.4), and `AsSemigroupFRMachine` (3.3.4).

!!!

 Example

9.1.2 IMGRelator

◇ `IMGRelator(m)` (attribute)

Returns: The relator of the IMG FR machine.

This attribute stores the product of generators that is trivial. In essence, it records an ordering of the generators whose product is trivial in the punctured sphere's fundamental group.

9.1.3 Mating

◇ `Mating(m1, m2 [, w1, w2])`

(operation)

Returns: An IMG FR machine.

This function mates two IMG FR machines. The arguments *w1*, *w2* are IMG FR elements that represent adding elements; they may be omitted if *m1*, *m2* contain pre-specified adding machines (through the attribute `AddingElement` (10.1.4)). The elements *w1* and *w2* must satisfy the same recursion.

The mating is defined as follows: one removes a disc around the adding machine in *m1* and *m2*; one applies complex conjugation to *m2*; and one glues the hollowed spheres along their boundary circle.

Example

!!!

9.1.4 PolynomialFRMachine

◇ `PolynomialFRMachine(d, per, pre)`

(operation)

◇ `PolynomialIMGMachine(d, per, pre)`

(operation)

◇ `PolynomialMealyMachine(d, per, pre)`

(operation)

Returns: An IMG FR machine.

This function creates a group, IMG or Mealy machine that describes a topological polynomial. The polynomial is described symbolically in the language of *external angles*. For more details, see [DH84] and [DH85] (in the quadratic case), [BFH92] (in the preperiodic case), and [Poi] (in the general case).

d is the degree of the polynomial. *per* and *pre* are lists of angles or preangles. In what follows, angles are rational numbers, considered modulo 1. Each entry in *per* or *pre* is either a rational (interpreted as an angle), or a list of angles $[a_1, \dots, a_i]$ such that $da_1 = \dots = da_i$.

Example

```
gap> PolynomialIMGMachine(2, [0], []); # the adding machine
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1, f2 ] )/[ f2*f1 ]>
gap> Display(last);
G |      1      2
----+-----+-----+
f1 | <id>,2      f1,1
f2 |  f2,2      <id>,1
----+-----+-----+
Relator: f2*f1
gap> Display(PolynomialIMGMachine(2, [1/3], [])); # the Basilica
G |      1      2
----+-----+-----+
f1 | f1^-1,2      f2*f1,1
f2 |  f1,1      <id>,2
f3 |  f3,2      <id>,1
----+-----+-----+
Relator: f3*f2*f1
gap> Display(PolynomialIMGMachine(2, [], [1/6])); # z^2+I
G |      1      2
----+-----+-----+
f1 | f1^-1*f2^-1,2      f2*f1,1
f2 |      f1,1      f3,2
```

```

f3 |          f2,1    <id>,2
f4 |          f4,2    <id>,1
-----+-----+-----+
Relator: f4*f3*f2*f1
gap> PolynomialIMGMachine(3,[[0,1/3],[5/9,8/9]],[]);
<FR machine with alphabet [ 1 .. 3 ] on Group( [ f1, f2, f3 ] )/[ f3*f2*f1 ]>
gap> PolynomialIMGMachine(3,[[0,1/3]],[[5/9,8/9]]);
<FR machine with alphabet [ 1 .. 3 ] on Group( [ f1, f2, f3, f4 ] )/[ f4*f3*f2*f1 ]>

```

The following construct the examples in Poirier's paper:

```

PoirierExamples := function(arg)
  if arg=[1] then
    return PolynomialIMGMachine(2,[1/7],[]);
  elif arg=[2] then
    return PolynomialIMGMachine(2,[],[1/2]);
  elif arg=[3,1] then
    return PolynomialIMGMachine(2,[],[5/12]);
  elif arg=[3,2] then
    return PolynomialIMGMachine(2,[],[7/12]);
  elif arg=[4,1] then
    return PolynomialIMGMachine(3,[[3/4,1/12],[1/4,7/12]],[]);
  elif arg=[4,2] then
    return PolynomialIMGMachine(3,[[7/8,5/24],[5/8,7/24]],[]);
  elif arg=[4,3] then
    return PolynomialIMGMachine(3,[[1/8,19/24],[3/8,17/24]],[]);
  elif arg=[5] then
    return PolynomialIMGMachine(3,[[3/4,1/12],[3/8,17/24]],[]);
  elif arg=[6,1] then
    return PolynomialIMGMachine(4,[],[[1/4,3/4],[1/16,13/16],[5/16,9/16]]);
  elif arg=[6,2] then
    return PolynomialIMGMachine(4,[],[[1/4,3/4],[3/16,15/16],[7/16,11/16]]);
  elif arg=[7] then
    return PolynomialIMGMachine(5,[[0,4/5],[1/5,2/5,3/5]],[[1/5,4/5]]);
  elif arg=[9,1] then
    return PolynomialIMGMachine(3,[[0,1/3],[5/9,8/9]],[]);
  elif arg=[9,2] then
    return PolynomialIMGMachine(3,[[0,1/3]],[[5/9,8/9]]);
  fi;
end;

```

9.1.5 DBRationalIMGGroup

◇ DBRationalIMGGroup(sequence, or, rational, map)

(function)

Returns: An IMG group from Dau's database.

This function returns the iterated monodromy group from a database of groups associated to quadratic rational maps. This database has been compiled by Dau Truong Tan [Tan02].

When called with no arguments, this command returns the database contents in raw form.

The arguments can be a sequence; the first integer is the size of the postcritical set, the second argument is an index for the postcritical graph, and sometimes a third argument distinguishes between maps with same post-critical graph.

If the argument is a rational map, the command returns the IMG group of that map, assuming its `CanonicalQuadraticRational` (9.1.8) form exists in the database.

Example

```
gap> DBRationalIMGGroup(z^2-1);
IMG((z-1)^2)
gap> DBRationalIMGGroup(z^2+1); # not post-critically finite
fail
gap> DBRationalIMGGroup(4,1,1);
IMG((z/h+1)^2|2h^3+2h^2+2h+1=0,h~-0.64)
```

9.1.6 ValueRational

◇ `ValueRational(f , x)`

(function)

Returns: The value of f at x .

This function is almost identical to `Value(f , x)`. It accepts infinity as an argument, and may return infinity as a value.

Example

```
gap> z := Indeterminate(Rationals,"z");;
gap> ValueRational(1/z,infinity);
0
gap> ValueRational(1/z,0);
infinity
gap> ValueRational(1/z,1/2);
2
```

9.1.7 CriticalValuesQuadraticRational

◇ `CriticalValuesQuadraticRational(f)`

(function)

Returns: The critical values of f .

This function returns, as a list, the values of f at places where the derivative of f vanishes.

Example

```
gap> z := Indeterminate(Rationals,"z");;
gap> CriticalValuesQuadraticRational(z^2);
[ 0, infinity ]
gap> CriticalValuesQuadraticRational(z^2+1);
[ 1, infinity ]
gap> CriticalValuesQuadraticRational((z^2+1)/(z^2-1));
[ -1, 1 ]
gap> CriticalValuesQuadraticRational((z^2+1)/(z^2-z-1));
[ 2/5*E(5)-2/5*E(5)^2-2/5*E(5)^3+2/5*E(5)^4, -2/5*E(5)+2/5*E(5)^2+2/5*E(5)^3-2/5*E(5)^4 ]
```

9.1.8 CanonicalQuadraticRational

◇ `CanonicalQuadraticRational(f)`

(function)

Returns: The canonical forms of the quadratic rational map f .

This function puts the quadratic rational map f in canonical form, that is, in form $((az + b)/(cz + d))^2$, such that its critical values are 0 and infinity. Furthermore, it attempts to make $f(\text{infinity})=1$, and if this is impossible to make $f(0)=1$.

The command returns the set of all maps with these properties.

Example

```
gap> z := Indeterminate(Rationals, "z");;
gap> CanonicalQuadraticRational(z^2);
[ z^2 ]
gap> CanonicalQuadraticRational(z^2+1);
[ (z^2)/(z^2+2*z+1), z^2+2*z+1 ]
gap> CanonicalQuadraticRational((z^2+1)/(z^2-1));
[ (1/2*z^2+z+1/2)/(1/2*z^2-z+1/2), (-1/2*z^2+z-1/2)/(-1/2*z^2-z-1/2) ]
```

9.1.9 PostCriticalMachine

◇ **PostCriticalMachine**(*f*)

(function)

Returns: The Mealy machine of *f*'s post-critical orbit.

This function constructs a Mealy machine *P* on the alphabet [1], which describes the post-critical set of *f*. It is in fact an oriented graph with constant out-degree 1. It is most conveniently passed to Draw (5.2.1).

The attribute Correspondence(*P*) is the list of values associated with the stateset of *P*.

Example

```
gap> z := Indeterminate(Rationals, "z");;
gap> m := PostCriticalMachine(z^2);
<Mealy machine on alphabet [ 1 ] with 2 states>
gap> Display(m);
| 1
---+-----+
a | a,1
b | b,1
---+-----+
gap> Correspondence(m);
[ 0, infinity ]
gap> m := PostCriticalMachine(z^2-1);; Display(m); Correspondence(m);
| 1
---+-----+
a | c,1
b | b,1
c | a,1
---+-----+
[ -1, infinity, 0 ]
```

9.2 Spiders

9.2.1 RationalFunction

◇ **RationalFunction**(*m*)

(operation)

Returns: A rational function.

!!!

Example

!!!

9.2.2 IMGFRMachine (rational function)

◇ IMGFRMachine(m)

(operation)

Returns: An IMG FR machine.

!!!

Example

!!!

Chapter 10

Examples

FR predefines a large collection of machines and groups. The groups are, whenever possible, defined as state closures of corresponding Mealy machines.

10.1 Examples of groups

10.1.1 FullBinaryGroup

◇ FullBinaryGroup	(global variable)
◇ FiniteDepthBinaryGroup(1)	(function)
◇ FinitaryBinaryGroup	(global variable)
◇ BoundedBinaryGroup	(global variable)
◇ PolynomialGrowthBinaryGroup	(global variable)
◇ FiniteStateBinaryGroup	(global variable)

These are the finitary, bounded, polynomial-growth, finite-state, or unrestricted groups acting on the binary tree. They are respectively shortcuts for `FullSCGroup([1..2])`, `FullSCGroup([1..2],1)`, `FullSCGroup([1..2],IsFinitaryFRSemigroup)`, `FullSCGroup([1..2],IsBoundedFRSemigroup)`, `FullSCGroup([1..2],IsPolynomialGrowthFRSemigroup)`, and `FullSCGroup([1..2],IsFiniteStateFRSemigroup)`.

They may be used to draw random elements, or to test membership.

10.1.2 BinaryKneadingGroup

◇ BinaryKneadingGroup(<i>angle/ks</i>)	(function)
◇ BinaryKneadingMachine(<i>angle/ks</i>)	(function)

Returns: The [machine generating the] iterated monodromy group of a quadratic polynomial.

The first function constructs a Mealy machine whose state closure is the binary kneading group.

The second function constructs a new FR group G , which is the iterated monodromy group of a quadratic polynomial, either specified by its angle or by its kneading sequence(s).

If the argument is a (rational) angle, the attribute `Correspondence(G)` is a function returning, for any rational, the corresponding generator of G .

If there is one argument, which is a list or a string, it is treated as the kneading sequence of a periodic (superattracting) polynomial. The sequence is implicitly assumed to end by `'*'`. The attribute `Correspondence(G)` is a list of the generators of G .

If there are two arguments, which are lists or strings, they are treated as the preperiod and period of the kneading sequence of a preperiodic polynomial. The last symbol of the arguments must differ. The attribute `Correspondence(G)` is a pair of lists of generators; `Correspondence(G)[1]` is the preperiod, and `Correspondence(G)[2]` is the period. The attribute `KneadingSequence(G)` returns the kneading sequence, as a pair of strings representing preperiod and period respectively.

As particular examples, `BinaryKneadingMachine()` is the adding machine; `BinaryKneadingGroup()` is the adding machine; and `BinaryKneadingGroup("1")` is `BasilicaGroup` (10.1.3).

Example

```
gap> BinaryKneadingGroup()=AddingGroup(2);
true
gap> BinaryKneadingGroup(1/3)=BasilicaGroup;
true
gap> g := BinaryKneadingGroup([0,1],[0]);
BinaryKneadingGroup("01","0")
gap> ForAll(Correspondence(g)[1],IsFinitaryFRElement);
true
gap> ForAll(Correspondence(g)[2],IsFinitaryFRElement);
false
gap> ForAll(Correspondence(g)[2],IsBoundedFRElement);
true
```

10.1.3 BasilicaGroup

◇ `BasilicaGroup`

(global variable)

The *Basilica group*. This is a shortcut for `BinaryKneadingGroup("1")`. It is the first-discovered amenable group that is not subexponentially amenable, see [BV05] and [GŽ02].

Example

```
gap> IsBoundedFRSemigroup(BasilicaGroup);
true
gap> pi := EpimorphismFromFreeGroup(BasilicaGroup); F := Source(pi);;
[ x1, x2 ] -> [ a, b ]
gap> sigma := GroupHomomorphismByImages(F,F,[F.1,F.2],[F.2,F.1^2]);
[ x1, x2 ] -> [ x2, x1^2 ]
gap> ForAll([0..10],i->IsOne(Comm(F.2,F.2^F.1)^(sigma^i*pi)));
true
```

10.1.4 AddingGroup

◇ `AddingGroup(n)`

(function)

◇ `AddingMachine(n)`

(function)

◇ `AddingElement(n)`

(function)

The second function constructs the adding machine on the alphabet $[1..n]$. This machine has a trivial state 1, and a non-trivial state 2. It implements the operation "add 1 with carry" on sequences.

The third function constructs the Mealy element on the adding machine, with initial state 2.

The first function constructs the state-closed group generated by the adding machine on $[1..n]$. This group is isomorphic to the Integers.

Example

```

gap> Display(AddingElement(3));
  | 1      2      3
---+-----+-----+-----+
a | a,1    a,2    a,3
b | a,2    a,3    b,1
---+-----+-----+-----+
Initial state: b
gap> Activity(FRElement(AddingMachine(3),2),2);
(1,4,7,2,5,8,3,6,9)
gap> G := AddingGroup(3);
<self-similar group over [ 1 .. 3 ] with 1 generator>
gap> Size(G);
infinity
gap> IsRecurrent(G);
true
gap> IsLevelTransitive(G);
true

```

10.1.5 BinaryAddingGroup

- ◇ BinaryAddingGroup (global variable)
- ◇ BinaryAddingMachine (global variable)
- ◇ BinaryAddingElement (global variable)

These are respectively the same as `AddingGroup(2)`, `AddingMachine(2)` and `AddingElement(2)`.

10.1.6 MixerGroup

- ◇ MixerGroup($A, B, f[, g]$) (function)
- ◇ MixerMachine($A, B, f[, g]$) (function)

Returns: A Mealy "mixer" machine/group.

The second function constructs a Mealy "mixer" machine m . This is a machine determined by a permutation group A , a finitely generated group B , and a matrix of homomorphisms from B to A . If A acts on $[1..d]$, then each row of f contains at most $d - 1$ homomorphisms. The optional last argument is an endomorphism of B . If absent, it is treated as the identity map on B .

The states of the machine are 1, followed by some elements a of A , followed by as many copies of some elements b of B as there are rows in f . The elements in B that are taken is the smallest sublist of B containing its generators and closed under g . The elements in A that are taken are the generators of A and all images of all taken elements of B under maps in f .

The transitions from a are towards 1 and the outputs are the permutations in A . The transitions from b are periodically given by f , completed by trivial elements, and finally by b^g ; the output of b is trivial.

This construction is described in more detail in [BŠ01] and [BGŠ03].

Correspondence(m) is a list, with in first position the subset of the states that correspond to A , in second position the states that correspond to the first copy of B , etc.

The first function constructs the group generated by the mixer machine. For examples see `GrigorchukGroups` (10.1.8), `NeumannGroup` (10.1.19), `GuptaSidkiGroups` (10.1.17), and

OtherSpinalGroup (10.1.21).

Example

```
gap> grigorchukgroup := MixerGroup(Group((1,2)),Group((1,2)),
  [[IdentityMapping(Group((1,2))],[IdentityMapping(Group((1,2))],[[]]]));
<self-similar group over [ 1 .. 2 ] with 4 generators>
gap> IdGroup(Group(grigorchukgroup.1,grigorchukgroup.2));
[ 32, 18 ]
```

10.1.7 SunicGroup

◇ SunicGroup(*phi*) (function)
 ◇ Sunicmachine(*phi*) (function)

Returns: The Sunic machine associated with the polynomial *phi*.

A "Sunic machine" is a special kind of MixerMachine (10.1.6), in which the group *A* is a finite field $GF(q)$, the group *B* is an extension $A[x]/(\phi)$, where ϕ is a monic polynomial; there is a map $f: B \rightarrow A$, given say by evaluation; and there is an endomorphism of $g: B \rightarrow B$ given by multiplication by ϕ .

These groups were described in [Šun07]. In particular, the case $q = 2$ and $\phi = x^2 + x + 1$ gives the original GrigorchukGroup (10.1.9).

Example

```
gap> x := Indeterminate(GF(2));;
gap> g := SunicGroup(x^2+x+1);
SunicGroup(x^2+x+Z(2)^0)
gap> g = GrigorchukGroup;
true
```

10.1.8 GrigorchukMachines

◇ GrigorchukMachines(*omega*) (function)
 ◇ GrigorchukGroups(*omega*) (function)

Returns: One of the Grigorchuk groups.

This function constructs the Grigorchuk machine or group associated with the infinite sequence *omega*, which is assumed (pre)periodic; *omega* is either a periodic list (see PeriodicList (12.1.6)) or a plain list describing the period. Entries in the list are integers in $[1..3]$.

These groups are MixerGroup (10.1.6)s. The most famous example is GrigorchukGroups([1,2,3]), which is also called GrigorchukGroup (10.1.9).

These groups are all 4-generated and infinite. They are described in [Gri84]. GrigorchukGroups([1]) is infinite dihedral. If *omega* contains at least 2 different digits, GrigorchukGroups([1]) has intermediate word growth. If *omega* contains all 3 digits, GrigorchukGroups([1]) is torsion.

The growth of GrigorchukGroups([1,2]) has been studied in [Ers04].

Example

```
gap> G := GrigorchukGroups([1]);
<self-similar group over [ 1 .. 2 ] with 4 generators>
gap> Index(G,DerivedSubgroup(G)); IsAbelian(DerivedSubgroup(G));
4
true
gap> H := GrigorchukGroups([1,2]);
<self-similar group over [ 1 .. 2 ] with 4 generators>
```

```
gap> Order(H.1*H.2);
8
gap> Order(H.1*H.4);
infinity
gap> IsSubgroup(H,G);
true
```

10.1.9 GrigorchukMachine

◇ GrigorchukMachine

(global variable)

◇ GrigorchukGroup

(global variable)

This is Grigorchuk's first group, introduced in [Gri80]. It is a 4-generated infinite torsion group, and has intermediate word growth. It could have been defined as `FRGroup("a=(1,2)", "b=<a,c>", "c=<a,d>", "d=<,b>")`, but is rather defined using Mealy elements.

The command `EpimorphismFromFpGroup(GrigorchukGroup,n)` will will construct an approximating presentation for the Grigorchuk group, as proven in [Lys85]. Adding the relations `Image(sigma^(n-2), (a*d)^2)`, `Image(sigma^(n-1), (a*b)^2)` and `Image(sigma^(n-2), (a*c)^4)` yields the quotient acting on 2^n points, as a finitely presented group.

10.1.10 GrigorchukOverGroup

◇ GrigorchukOverGroup

(global variable)

This is a group strictly containing the Grigorchuk group (see `GrigorchukGroup` (10.1.9)). It also has intermediate growth (see [BG02], but it contains elements of infinite order. It could have been defined as `FRGroup("a=(1,2)", "b=<a,c>", "c=<,d>", "d=<,b>")`, but is rather defined using Mealy elements.

Example

```
gap> IsSubgroup(GrigorchukOverGroup,GrigorchukGroup);
true
gap> Order(Product(GeneratorsOfGroup(GrigorchukOverGroup)));
infinity
gap> GrigorchukGroup.2=GrigorchukSuperGroup.2*GrigorchukSuperGroup.3;
true
```

The command `EpimorphismFromFpGroup(GrigorchukOverGroup,n)` will will construct an approximating presentation for the Grigorchuk overgroup, as proven in [Bar03a].

10.1.11 GrigorchukEvilTwin

◇ GrigorchukEvilTwin

(global variable)

This is a group with same closure as the Grigorchuk group (see `GrigorchukGroup` (10.1.9)), but not isomorphic to it. It could have been defined as `FRGroup("a=(1,2)", "x=<y,a>", "y=<a,z>", "z=<,x>")`, but is rather defined using Mealy elements.

Example

```
gap> AbelianInvariants(GrigorchukEvilTwin);
[ 2, 2, 2, 2 ]
gap> AbelianInvariants(GrigorchukGroup);
[ 2, 2, 2 ]
gap> PermGroup(GrigorchukGroup, 8) = PermGroup(GrigorchukEvilTwin, 8);
true
```

10.1.12 BrunnerSidkiVieiraGroup

◇ BrunnerSidkiVieiraGroup

(global variable)

◇ BrunnerSidkiVieiraMachine

(global variable)

This machine is the sum of two adding machines, one in standard form and one conjugated by the element d described below. The group that it generates is described in [BSV99]. It could have been defined as `FRGroup("tau=<,tau>(1,2)", "mu=<,mu^-1>(1,2)")`, but is rather defined using Mealy elements.

Example

```
gap> V := FRGroup("d=<e,e>(1,2)", "e=<d,d>");
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> Elements(V);
[ <2|identity ...>, <2|e>, <2|d>, <2|e*d> ]
gap> AssignGeneratorVariables(BrunnerSidkiVieiraGroup);
#I Assigned the global variables [ "tau", "mu", "" ]
gap> List(V, x->tau^x)=[tau,mu,mu^-1,tau^-1];
true
```

10.1.13 AleshinGroups

◇ AleshinGroups(l)

(function)

◇ AleshinMachines(l)

(function)

Returns: The Aleshin machine with `Length(l)` states.

This function constructs the bireversible machines introduced by Aleshin in [Ale83]. The argument l is a list of permutations, either $()$ or $(1, 2)$. The groups that they generate are constructed as `AleshinGroups`.

If $l = [(1, 2), (1, 2), ()]$, this is `AleshinGroup` (10.1.14). More generally, if $l = [(1, 2), (1, 2), (), \dots, ()]$ has odd length, this is a free group of rank `Length(l)`, see [VV06].

If $l = [(1, 2), (1, 2), \dots]$ has even length and contains an even number of $()$'s, then this is also a free group of rank `Length(l)`, see [SVV06].

If $l = [(), (), (1, 2)]$, this is `BabyAleshinGroup` (10.1.15). more generally, if $l = [(), (), \dots]$ has even length and contains an even number of $(1, 2)$'s, then this is the free product of `Length(l)` copies of the order-2 group.

10.1.14 AleshinGroup

◇ AleshinGroup

(global variable)

◇ AleshinMachine

(global variable)

This is the first example of non-abelian free group. It is the group generated by `AleshinMachine([(1,2),(1,2),()])`. It could have been defined as `FRGroup("a=<b,c>(1,2)", "b=<c,b>(1,2)", "c=<a,a>")`, but is rather defined using Mealy elements.

10.1.15 BabyAleshinGroup

◇ `BabyAleshinGroup` (global variable)
 ◇ `BabyAleshinMachine` (global variable)

There are only two connected, transitive bireversible machines on a 2-letter alphabet, with 3 generators: `AleshinMachine(3)` and the baby Aleshin machine.

The group generated by this machine is abstractly the free product of three C_2 's, see [Nek05, 1.10.3]. It could have been defined as `FRGroup("a=<b,c>", "b=<c,b>", "c=<a,a>(1,2)")`, but is rather defined here using Mealy elements.

Example

```
gap> K := Kernel(GroupHomomorphismByImagesNC(BabyAleshinGroup, Group((1,2)),
      GeneratorsOfGroup(BabyAleshinGroup), [(1,2), (1,2), (1,2)]));
<self-similar group over [ 1 .. 2 ] with 4 generators>
gap> Index(BabyAleshinGroup, K);
2
gap> IsSubgroup(AleshinGroup, K);
true
```

10.1.16 SidkiFreeGroup

◇ `SidkiFreeGroup` (global variable)

This is a group suggested by Sidki as an example of a non-abelian state-closed free group. Nothing is known about that group: whether it is free as conjectured; whether generator a is state-closed, etc. It is defined as `FRGroup("a=<a^2, a^t>", "t=<,t>(1,2)")]>`.

10.1.17 GuptaSidkiGroups

◇ `GuptaSidkiGroups(n)` (function)
 ◇ `GeneralizedGuptaSidkiGroups(n)` (function)
 ◇ `GuptaSidkiMachines(n)` (function)

Returns: The Gupta-Sidki machine on an n -letter alphabet.

This function constructs the machines introduced by Gupta and Sidki in [GS83]. They generate finitely generated infinite torsion groups: the exponent of every element divides some power of n . The special case $n = 3$ is defined as `GuptaSidkiGroup(10.1.18)` and `GuptaSidkiMachine(10.1.18)`.

For $n > 3$, there are (at least) two natural ways to generalize the Gupta-Sidki construction: the original one involves the recursion `"t=<a, a^-1, 1, ..., 1, t>"`, while the second (called here ‘generalized’) involves the recursion `"t=<a, a^2, ..., a^-1, t>"`. A finite L-presentation for the latter is implemented. It is not as computationally efficient as the L-presentation of the normal closure of t (a subgroup of index p), which is an ascending L-presented group. The inclusion of that subgroup may be recovered via `EmbeddingOfAscendingSubgroup(GuptaSidkiGroup)`.

10.1.18 GuptaSidkiGroup

- ◇ `GuptaSidkiGroup` (global variable)
- ◇ `GuptaSidkiMachine` (global variable)

This is an infinite, 2-generated, torsion 3-group. It could have been defined as `FRGroup("a=(1,2,3)", "t=<a, a^-1, t>")`, but is rather defined using Mealy elements.

10.1.19 NeumannGroup

- ◇ `NeumannGroup(P)` (function)
- ◇ `NeumannMachine(P)` (function)

Returns: The Neumann machine/group on the permutation group P .

The first function constructs the Neumann machine associated to the permutation group P . It is a shortcut for `MixerMachine(P, P, [[IdentityMapping(P)])`.

The second function constructs the Neumann group on the permutation group P . These groups were first considered in [Neu86]. In particular, `NeumannGroup(PSL(3,2))` is a group of non-uniform exponential growth (see [Bar03b]), and `NeumannGroup(Group((1,2,3)))` is `FabrykowskiGuptaGroup` (10.1.20).

The attribute `Correspondence(G)` is set to a list of homomorphisms from P to the A and B copies of P .

10.1.20 FabrykowskiGuptaGroup

- ◇ `FabrykowskiGuptaGroup` (global variable)
- ◇ `FabrykowskiGuptaGroups(p)` (function)

This is an infinite, 2-generated group of intermediate word growth. It was studied in [FG85] and [FG91]. It could have been defined as `FRGroup("a=(1,2,3)", "t=<a, , t>")`, but is rather defined using Mealy elements. It has a torsion-free subgroup of index 3 and is branched.

The natural generalization, replacing 3 by p , is constructed by the second form. It is a specific case of Neumann group (see `NeumannGroup` (10.1.19)), for which an ascending L-presentation is known.

10.1.21 OtherSpinalGroup

- ◇ `OtherSpinalGroup` (global variable)

This is an infinite, 2-generated group, which was studied in [BG02]. It has a torsion-free subgroup of index 3, and is virtually branched but not branched. It could have been defined as `FRGroup("a=(1,2,3)", "t=<a, a, t>")`, but is rather defined using Mealy elements.

10.1.22 GammaPQMachine

- ◇ `GammaPQMachine(p, q)` (function)
- ◇ `GammaPQGroup(p, q)` (function)

Returns: The quaternion-based machine / SC group.

The first function constructs a bireversible (see `IsBireversible` (5.2.7)) Mealy machine based on quaternions, see [BM00a] and [BM00b]. This machine has $p + 1$ states indexed by integer quaternions of norm p , and an alphabet of size $q + 1$ indexed by quaternions of norm q . These quaternions are congruent to $1 \pmod{2}$ or $i \pmod{2}$ depending on whether the odd prime p or q is 1 or 3 (mod 4).

The structure of the machine is such that there is a transition from (q, a) to (q', a') precisely when $qa' = \pm q'a$. In particular, the relations of the `StructuralGroup` (3.5.1) hold up to a sign, when the alphabet/state letters are substituted for the appropriate quaternions.

The quaternions themselves can be recovered through `Correspondence` (3.5.11), which is a list with in first position the quaternions of norm p and in second those of norm q .

The second function constructs the quaternion lattice that is the `StructuralGroup` (3.5.1) of that machine. It has actions on two trees, given by `VerticalAction` (10.5.2) and `HorizontalAction` (10.5.2); the ranges of these actions are groups generated by automata, which are infinitely-transitive (see `IsInfinitelyTransitive` (7.2.12)) and free by [GM05, Proposition 3.3]; see also [Ale83].

10.1.23 HanoiGroup

◇ `HanoiGroup(n)` (function)

Returns: The Hanoi group on an n pegs.

This function constructs the Hanoi group on n pegs. Generators of the group correspond to moving a peg, and tree vertices correspond to peg configurations. This group is studied in [GŠ06].

10.1.24 DahmaniGroup

◇ `DahmaniGroup` (global variable)

This is an example of a non-contracting weakly branched group. It was first studied in [Dah05]. It could have been defined as `FRGroup("a=<c, a>(1,2)", "b=<b, a>(1,2)", "c=<b, c>")`, but is rather defined using Mealy elements.

It has relators abc , $[a^2c, [a, c]]$, $[cab, a^{-1}c^{-1}ab]$ and $[ac^2, c^{-1}b^{-1}c^2]$ among others.

It admits an endomorphism on its derived subgroup. Indeed

`FRElement(1, Comm(a, b)) = Comm(c^{-1}, b/a)`, `FRElement(1, Comm(a, c)) = Comm(a/b, c)`,
`FRElement(1, Comm(b, c)) = Comm(c, (a/b)^c)`.

10.1.25 MamaghaniGroup

◇ `MamaghaniGroup` (global variable)

This group was studied in [Mam03]. It is fractal, but not contracting. It could have been defined as `FRGroup("a=<, b>(1,2)", "b=<a, c>", "c=<a, a^{-1}>(1,2)"]>`, but is rather defined using Mealy elements. It partially admits branching on its subgroup `Subgroup(G, [a^2, (a^2)^b, (a^2)^c])`, and, setting $x = \text{Comm}(a^2, b)$, on `Subgroup(G, [x, x^a, x^b, x^{(b*a)}, x^{(b/a)}])`. One has `FRElement(1, x) = (x^{-1})^b/x`.

10.1.26 WeierstrassGroup

◇ `WeierstrassGroup` (global variable)

This is the iterated monodromy group associated with the Weierstrass \wp -function.

Some relators in the group: $(atbt)^4$, $((atbt)(bt)^4n)^4$, $((atbt)^2(bt)^4n)^2$.

Set $x = [a, t]$, $y = [b, t]$, $z = [c, t]$, and $w = [x, y]$. Then $G' = \langle x, y, z \rangle$ of index 8, and $\gamma_3 = \langle [\{x, y, z\}, \{a, b, c\}] \rangle$ of index 32, and $\gamma_4 = G'' = \langle w \rangle^G$, of index 256, and $G'' > (G'')^4$ since $[[t^a, t], [t^b, t]] = (w, 1, 1, 1)$.

The Schreier graph is obtained in the complex plane as the image of a $2^n \times 2^n$ lattice in the torus, via Weierstrass's \wp -function.

The element at has infinite order.

$[c, t, b][b, t, c][a, t, c][c, t, a]$ has order 2, and belongs to G'' ; so there exist elements of arbitrary large finite order in the group.

10.1.27 FRAffineGroup

◇ FRAffineGroup($d, R, u[, transversal]$)

(operation)

Returns: The d -dimensional affine group over R .

This function constructs a new FR group G , which is finite-index subgroup of the d -dimensional affine group over R_u , the local ring over R in which all non-multiples of u are invertible. Since no generators of G are known, G is in fact returned as a full SC group; only its attribute Correspondence(G), which is a homomorphism from $GL_{d+1}(R_u)$ to G , is relevant.

The affine group can also be described as a subgroup of $GL_{d+1}(R_u)$, consisting of those matrices M with $M_{i,d+1} = 0$ and $M_{d+1,d+1} = 1$. The finite-index subgroup is defined by the conditions $u|M_{i,j}$ for all $j < i$.

The only valid arguments are $R = \text{Integers}$ and $R = \text{PolynomialRing}(S)$ for a finite ring S . The alphabet of the affine group is R/RuR ; an explicit transversal of RuR be specified as last argument.

The following examples construct the "Baumslag-Solitar group" $\mathbb{Z}[\frac{1}{2}] \rtimes_2 \mathbb{Z}$ first introduced in [BS62], the "lamplighter group" $(\mathbb{Z}/2)\wr\mathbb{Z}$, and a 2-dimensional affine group. Note that the lamplighter group may also be defined via CayleyGroup (10.1.28).

Example

```
gap> A := FRAffineGroup(1, Integers, 3);
<self-similar group over [ 1 .. 3 ]>
gap> f := Correspondence(A);
MappingByFunction( ( Integers^
[ 2, 2 ] ), <self-similar group over [ 1 .. 3 ]>, function( mat ) ... end )
gap> BaumslagSolitar := Group([[2,0],[0,1]]^f, [[1,0],[1,1]]^f);
<self-similar group over [ 1 .. 3 ] with 2 generators>
gap> BaumslagSolitar.2^BaumslagSolitar.1=BaumslagSolitar.2^2;
true
gap> R := PolynomialRing(GF(2));
gap> A := FRAffineGroup(1, R, R.1);
gap> f := Correspondence(A);
gap> Lamplighter := Group(([[1+R.1,0],[0,1]]*One(R))^f, ([[1,0],[1,1]]*One(R))^f);
<self-similar group over [ 1 .. 2 ] with 2 generators>
gap> Lamplighter = CayleyGroup(Group((1,2)));
true
gap> StructureDescription(Group(Lamplighter.2, Lamplighter.2^Lamplighter.1));
"C2 x C2"
gap> ForAll([1..10], i->IsOne(Comm(Lamplighter.2, Lamplighter.2^(Lamplighter.1^i))));
true
gap> A := FRAffineGroup(2, Integers, 2);
gap> f := Correspondence(A);
```

```

gap> a := [[1,4,0],[2,3,0],[1,0,1]];
[ [ 1, 4, 0 ], [ 2, 3, 0 ], [ 1, 0, 1 ] ]
gap> b := [[1,2,0],[4,3,0],[0,1,1]];
[ [ 1, 2, 0 ], [ 4, 3, 0 ], [ 0, 1, 1 ] ]
gap> Display(b^f);
      |   1       2
-----+-----+-----+
      a |  b,1    c,2
      b |  d,2    e,1
      c |  a,2    f,1
      ...
      bh | cb,1   be,2
      ca | bd,1   bf,2
      cb | ae,2   bh,1
      -----+-----+-----+
Initial state:  a
gap> a^f*b^f=(a*b)^f;
true

```

10.1.28 CayleyGroup

- ◇ CayleyGroup(G) (function)
- ◇ CayleyMachine(G) (function)
- ◇ LamplighterGroup(G) (operation)

Returns: The Cayley machine/group of the group G .

The *Cayley machine* of a group G is a machine with alphabet and stateset equal to G , and with output and transition functions given by multiplication in the group, in the order `state*letter`.

The second function constructs a new FR group CG , which acts on $[1..Size(G)]$. Its generators are in bijection with the elements of G , and have as output the corresponding permutation of G induced by right multiplication, and as transitions all elements of G ; see `CayleyMachine`. This construction was introduced in [SS05].

If G is an abelian group, CG is the wreath product $G \wr \mathbb{Z}$; it is created by the constructor `LamplighterGroup(IsFRGroup, G)`.

The attribute `Correspondence(CG)` is a list. Its first entry is a homomorphism from G into CG . Its second entry is the generator of CG that has trivial output. CG is generated `Correspondence(CG)[2]` and the image of `Correspondence(CG)[1]`.

In the example below, recall the definition of `Lamplighter` in the example of `FRAffineGroup` (10.1.27).

```

----- Example -----
gap> L := CayleyGroup(Group((1,2)));
CayleyGroup(Group( [ (1,2) ] ))
gap> L=LamplighterGroup(IsFRGroup,CyclicGroup(2));
true
gap> (1,2)^Correspondence(L)[1];
<Mealy element on alphabet [ 1, 2 ] with 2 states, initial state 1>
gap> IsFinitaryFRElement(last); Display(last2);
true
      |   1       2
-----+-----+-----+
      a | b,2    b,1

```

```

b | b,1   b,2
---+-----+-----+
Initial state: a

```

10.2 Examples of semigroups

10.2.1 I2Machine

◇ I2Machine (global variable)
 ◇ I2Monoid (global variable)

The Mealy machine I_2 , and the monoid that it generates. This is the smallest Mealy machine generating a monoid of intermediate word growth; see [BRS06].

For sample calculations in this monoid see SCSemigroup (7.1.2).

10.2.2 I4Machine

◇ I4Machine (global variable)
 ◇ I4Monoid (global variable)

The Mealy machine generating I_4 , and the monoid that it generates. This is a very small Mealy machine generating a monoid of intermediate word growth; see [BR05].

For sample calculations in this monoid see SCSemigroup (7.1.2).

10.3 Examples of algebras

10.3.1 PSZAlgebra

◇ PSZAlgebra(k) (function)

This function creates an associative algebra A , over the field k of positive characteristic, generated by two derivations u, v . This algebra has polynomial growth, and is not nilpotent. Petrogradsky showed in [Pet06] that the Lie subalgebra of $\text{PSZAlgebra}(\text{GF}(2))$ generated by $v, [u, v]$ is nil; this result was generalized by Shestakov and Zelmanov in [SZ08] to arbitrary k .

Example

```

gap> a := PSZAlgebra(2);
PSZAlgebra(GF(2))
gap> Nillity(a.1); Nillity(a.2);
2
4
gap> IsNilpotentElement(LieBracket(a.1,a.2));
true
gap> DecompositionOffRElement(LieBracket(a.1,a.2))=DiagonalMat([a.2,a.2]);
true

```

10.3.2 GrigorchukThinnedAlgebra

◇ GrigorchukThinnedAlgebra(k)

(function)

This function creates the associative envelope A , over the field k , of Grigorchuk's group GrigorchukGroup (10.1.9). !!!

Example

```
gap> !!!
```

10.3.3 GuptaSidkiThinnedAlgebra

◇ GuptaSidkiThinnedAlgebra(k)

(function)

This function creates the associative envelope A , over the field k , of Gupta-Sidki's group GuptaSidkiGroup (10.1.18). !!!

Example

```
gap> !!!
```

10.3.4 SidkiFreeAlgebra

◇ SidkiFreeAlgebra(k)

(function)

!!!

Example

```
gap> !!!
```

10.4 Bacher's determinant identities

In his paper [Bac07], Roland Bacher exhibits striking formulas for determinants of matrices obtained from binomial coefficients.

The general construction is as follows: let P be an infinite matrix, and let $P(n)$ be its upper $n \times n$ corner. To evaluate $\det P(n)$, decompose $P = LDR$ where L, D, R are respectively lower triangular, diagonal, and upper triangular, with 1's on the diagonals of L and R . Then that determinant is the product of the first n entries of D .

Bacher considers some natural examples of matrices arising from binomial coefficients, and notes that the matrix P is the limit of a convergent vector element (see IsConvergent (6.1.8)). He also notes that the decomposition $P = LDR$ may be achieved within vector elements.

As a first example, consider the $n \times n$ matrix $P(n)$ with coefficients $P_{s,t} = \binom{s+t}{s} \pmod{2}$. Here and below, indices start at 0. Let also $ds(n)$ denote the digit-sum of the integer n . Then

$$\det(P(n)) = \begin{cases} (-1)^{n/2} & \text{if } n \text{ is even,} \\ (-1)^{(n-1)/2+ds((n-1)/2)} & \text{if } n \text{ is odd.} \end{cases}$$

For the proof, note that P is a convergent infinite matrix; it may be presented as a self-similar linear element by `FRAgebra("P=[[P,P], [P,0]]")`. It then suffices to construct an LR decomposition of P within FR vector elements, following Bacher:

Example

```
gap> AssignGeneratorVariables(FRAgebra(Rationals,
  "P=[ [P,P], [P,0] ]", "L=[ [L,0], [L,L] ]", "D=[ [D,0], [0,-D] ]"));
gap> L*D*TransposedFRElement(L)=P;
true
```

and to analyse the elements of the diagonal matrix D .

For a more complicated example, let v_2 denote 2-valuation of a rational, and construct the $n \times n$ matrix $V(n)$ with coefficients $V_{s,t} = t^{v_2(\binom{s+t}{s})}$. Then

$$\det(V(n)) = \det(P(n)) \prod_{k=1}^{n-1} (1 - f(k)i),$$

where $f(k)$ is the regular paper-folding sequence defined by $f(2^n) = 1$ and $f(2^n + a) = -f(2^n - a)$ for $1 \leq a < 2^n$.

This is again proved by noticing that V is a corner in a self-similar element, namely

Example

```
gap> AssignGeneratorVariables(FRAgebra(GaussianRationals,
  "V1=[ [V1,V2], [V2,E(4)*V1] ]",
  "V2=[ [V1,-E(4)*V1+(1+E(4))*V2], [-E(4)*V1+(1+E(4))*V2,-V1] ]");
gap> Activity(V1,3)=
  List([0..7],s->List([0..7],t->E(4)^ValuationInt(Binomial(s+t,s),2)));
true
```

The LR decomposition of $V = V1$ can be checked as follows:

Example

```
gap> AssignGeneratorVariables(FRAgebra(GaussianRationals,
  "L1=[ [L1,0], [L3,L4] ]",
  "L2=[ [0,-E(4)*L2], [-L1+L3,-E(4)*L2-E(4)*L4] ]:0",
  "L3=[ [L1,L2], [-E(4)*L1+(1+E(4))*L3,L2+(1+E(4))*L4] ]",
  "L4=[ [L1,0], [(1-E(4))*L1+E(4)*L3,L4] ]",
  "D1=[ [D1,0], [0,D2] ]",
  "D2=[ [D3,0], [0,2*D1-D2+2*D3] ]:-1+E(4)",
  "D3=[ [D3,0], [0,-D2] ]:-1+E(4)");
gap> L1*D1*TransposedFRElement(L1)=V1;
true
```

The LR decomposition can also, in favourable situations, be discovered by FR through the command `LDUDecompositionFRElement` (6.1.10). This approach will be followed below.

For the next example, consider "Beeblebrox reduction" $\beta(4k \pm 1) = \pm 1, \beta(2k) = 0$, and construct the $n \times n$ matrix $Z(n)$ (named after Zaphod Beeblebrox) with coefficients $Z_{s,t} = \beta(\binom{s+t}{s})$. Then

$$\det(Z(n)) = \prod_{k=1}^{n-1} g(k),$$

where $g(\sum a_i 2^i) = (-1)^{a_0 3^{\#\{i: a_i = a_{i+1} = 1\} - \#\{i: a_i \neq a_{i+1} = 1\}}}$ with all $a_i \in \{0, 1\}$.

This is again proved by noticing that Z is a corner in a self-similar element, namely

Example

```
gap> beta := n->Jacobi(-1,n)*(n mod 2);;
gap> Zaphod := GuessVectorElement(List([0..7],i->List([0..7],j->beta(Binomial(i+j,j)))));
```

```

<Linear element on alphabet Rationals^2 with 3-dimensional stateset>
gap> Display(Zaphod);
Rationals |      1      |      2      |
-----+-----+-----+
      1 |  1  0  0 |  0  1  0 |
        |  1  0  0 |  0  1  0 |
        |  1  0  0 |  0 -1  0 |
-----+-----+-----+
      2 |  0  0  1 |  0  0  0 |
        |  0  0 -1 |  0  0  0 |
        |  0  0  1 |  0  0  0 |
-----+-----+-----+
Output:  1  1  1
Initial state:  1  0  0
gap> LDUDecompositionFRElement(guessZ);
[ <Linear element on alphabet Rationals^2 with 4-dimensional stateset>,
  <Linear element on alphabet Rationals^2 with 2-dimensional stateset>,
  <Linear element on alphabet Rationals^2 with 4-dimensional stateset> ]
gap> Display(last[2]);
Rationals |      1      |      2      |
-----+-----+-----+
      1 |  1  0 |  0  0 |
        |  3  0 |  0  0 |
-----+-----+-----+
      2 |  0  0 |  0  1 |
        |  0  0 |  0 1/3 |
-----+-----+-----+
Output:  1 -1
Initial state:  1  0

```

and now the recursion read on this diagonal self-similar matrix gives immediately Bacher's recursion for $\det(Z(n))$.

Bacher notes that the group generated by $a = L_1, b = L_2/2, c = L_3, d = L_4$ in the last example may be of interest. A quick check produces the following relations (slightly rewritten):

Example

```

gap> AssignGeneratorVariables(FRAgebra(Rationals,
  "a=[a,0],[c,d]", "b=[-1/3*a,2*b],[1/3*c,d]",
  "c=[a,2*b],[c,d]", "d=[a,0],[1/3*c,d]"));
gap> g := Group(List([a,b,c,d], x->Activity(x,3)));
<matrix group with 4 generators>
gap> FindShortGroupRelations(g,10);
[ b*d^-1*c*a^-1,
  c*a^-1*c*a^-1,
  c*a*d^-1*a^-1*d^2*a^-1*b^-1,
  c*a*d^-1*c^-1*b*d*a^-1*b^-1,
  c*d*a^-2*d*a*d^-1*b^-1,
  c*a^2*d^-1*a^-2*d*a*d*a^-2*b^-1,
  d^2*a*d^-2*b^-1*c*a*d*a^-3,
  c*d*a*d^-2*a^-1*d*a*d*a^-2*b^-1 ]

```

Consider next the "triangular Beeblebrox matrix" with entries $L_{s,t} = \beta(\binom{s}{t})$. The recurrence is now given by

Example

```
gap> A := FRAgebra(Rationals,
  "L1=[[L1,0],[L2,L3]]",
  "L2=[[L1,0],[L2,-L3]]",
  "L3=[[L1,0],[-L2,L3]]");
<self-similar algebra on alphabet Rationals^2 with 3 generators>
```

and it is striking that A is a graded algebra, with L_1, L_2, L_3 homogeneous of degree 1, and each homogeneous component is 3-dimensional; all of L_1, L_2, L_3 are invertible (with inverses have degree -1), and generate a group that admits a faithful 3×3 linear representation. As a final example, Bacher considers the "Jacobi character" $\chi(8\mathbb{Z} \pm 1) = 1, \chi(8\mathbb{Z} \pm 3) = -1, \chi(2\mathbb{Z}) = 0$, and the associated matrix $J_{s,t} = \chi\left(\binom{s+t}{s}\right)$. He gives an easily-computed, but complicated formula for $\det(J(n))$. We can recover this formula, as before, by "guessing" an LR decomposition for J , which is self-similar and convergent:

Example

```
gap> chi := function(x)
  if x mod 8 in [1,7] then return 1;
  elif x mod 8 in [3,5] then return -1;
  else return 0; fi;
end;;
gap> m := List([0..63], i->List([0..63], j->chi(Binomial(i+j,j))));;
gap> J := GuessVectorElement(m,2);
<Linear element on alphabet Rationals^2 with 9-dimensional stateset>
gap> LDUdecompositionFRElement(J);
[ <Linear element on alphabet Rationals^2 with 20-dimensional stateset>,
  <Linear element on alphabet Rationals^2 with 4-dimensional stateset>,
  <Linear element on alphabet Rationals^2 with 20-dimensional stateset> ]
gap> time;
26869
gap> Display(last2[2]);
Rationals |      1      |      2      |
-----+-----+-----+
      1 |  1  0  0  0 |  0  0  0  0 |
        |  0  0  1  0 |  0  0  0  0 |
        |  3  0  0  0 |  0  0  0  0 |
        |  0  0  3  0 |  0  0  0  0 |
-----+-----+-----+
      2 |  0  0  0  0 |  0  1  0  0 |
        |  0  0  0  0 |  0  0  0  1 |
        |  0  0  0  0 |  0 1/3  0  0 |
        |  0  0  0  0 |  0  0  0 1/3 |
-----+-----+-----+
Output:  1 -1  3 -1/3
Initial state:  1  0  0  0
```

10.5 VH groups

[!!! introduction to do]

10.5.1 VHStructure

◇ `VHStructure(g)`

(operation)

◇ `IsVHGroup(g)`

(filter)

Returns: A VH-structure for the group g .

A *VH-structure* on a group g is a partition of the generators in two sets V, H such that every relator of g is of the form $vhv'h'$, and such that for all $v \in V, h \in H$ there exist unique $v' \in V, h' \in H$ such that $vhv'h' = 1$.

The VH structure is stored as a record with fields `v, h` containing lists of generators, and integer matrices `transitions, output` such that `transitions[v][h'] = v'` and `output[v][h'] = h`.

The filter recognizes groups with a VH structure.

Example

true

10.5.2 VerticalAction

◇ `VerticalAction(g)`

(attribute)

◇ `HorizontalAction(g)`

(attribute)

Returns: A homomorphism to an FR group.

A group with VH structure admits a *vertical action* of its subgroup $\langle V \rangle$; this is the group generated by the automaton `MealyMachine(trans, out)`. The function returns the group homomorphism from the subgroup $\langle V \rangle$ to that FR group.

The horizontal action is that of the dual automaton (see `DualMachine` (5.2.3)).

Example

true

10.5.3 VHGroup

◇ `VHGroup(l1, l2, ...)`

(function)

Returns: A new VH group.

This function constructs the VH group specified by the squares `l1, l2, ...`. Each `li` is a list of length 4, of the form `[v, h, v', h']`. Here the entries are indices of vertical, respectively horizontal generators, if positive; and their inverses if negative.

Example

true

10.5.4 IsIrreducibleVHGroup

◇ `IsIrreducibleVHGroup(g)`

(property)

Returns: Whether g is an irreducible lattice.

A VH group is *irreducible* if its projections on both trees is dense.

Example

true

10.5.5 MaximalSimpleSubgroup

◇ `MaximalSimpleSubgroup(g)`

(property)

Returns: A maximal simple subgroup of g , if possible.

A VH group is never simple, but in favourable cases it admits a finite-index simple subgroup, see [BM97]. This function attempts to construct such a subgroup. It returns `fail` if no such subgroup can be found.

Example

```
true
```

Chapter 11

FR implementation details

FR creates new categories for the various objects considered in the package. The first category is `FRObject`; all objects are in this category, and have an `Alphabet` method.

There are two categories below: `FRMachine` and `FRElement`. An `FRMachine` must have a `StateSet`, and methods for `Output` and a `Transition`. An `FRElement` must have an underlying `FRMachine` and `InitialState`, and `Output` and a `Transition` that use the initial state.

A self-similar group is simply a collections category of FR elements which is also a group.

11.1 The family of FR objects

All FR objects have an associated `AlphabetOfFRObject` (11.1.3).

11.1.1 FRMFamily

◇ `FRMFamily(obj)` (operation)

Returns: the family of FR machines on alphabet *obj*.

The family of an FR object is the arity of the tree on which elements cat act; in other words, there is one family for each alphabet.

11.1.2 FREFamily

◇ `FREFamily(obj)` (operation)

Returns: the family of FR elements on alphabet *obj*.

The family of an FR object is the arity of the tree on which elements cat act; in other words, there is one family for each alphabet.

The argument may be an FR machine, an alphabet, or a family of FR machines.

11.1.3 AlphabetOfFRObject

◇ `AlphabetOfFRObject(obj)` (operation)

Returns: the alphabet associated with *obj*.

This command applies to the family of any FR object, or to the object themselves. Alphabets are returned as lists, and in practice are generally of the form `[1..n]`.

11.1.4 AsPermutation (FR object)

◇ `AsPermutation(o)` (method)

This method takes as argument an FR object `o`: machine, element, or group, and produces an equivalent object whose outputs are permutations. In particular, it converts Mealy machines from domain representation to int representation.

If this is not possible, the method returns `fail`.

11.1.5 AsTransformation (FR object)

◇ `AsTransformation(o)` (method)

This method takes as argument an FR object `o`: machine, element, or group, and produces an equivalent object whose outputs are transformations. In particular, it converts Mealy machines from domain representation to int representation.

Since transformations can never be inverted by GAP, even when they are invertible, this function returns a monoid when applied to a full SC group.

11.2 Filters for FRObjects

11.2.1 IsGroupFRMachine

◇ `IsGroupFRMachine(obj)` (property)

◇ `IsMonoidFRMachine(obj)` (property)

◇ `IsSemigroupFRMachine(obj)` (property)

Returns: `true` if `obj` is an FR machine whose stateset is a free group/monoid/semigroup.

This function is the acceptor for those functionally recursive machines whose stateset (accessible via `StateSet` (3.4.1)) is a free group, monoid or semigroup. The generating set of its stateset is accessible via `GeneratorsOfFRMachine` (3.4.2).

11.2.2 IsFRMachineStrRep

◇ `IsFRMachineStrRep(obj)` (filter)

Returns: `true` if `obj` is a standard (group,monoid,semigroup) FR machine.

There is a free object `free`, of rank N , a list `transitions` of length N , each entry a list, indexed by the alphabet, of elements of `free`, and a list `output` of length N of transformations or permutations of the alphabet.

11.2.3 IsMealyMachine

◇ `IsMealyMachine(obj)` (filter)

Returns: `true` if `obj` is a Mealy machine.

This function is the acceptor for the *Mealy machine* subcategory of *FR machines*.

11.2.4 IsMealyElement

◇ IsMealyElement(*obj*)

(filter)

Returns: true if *obj* is a Mealy element.

This function is the acceptor for the *Mealy element* subcategory of *FR elements*.

11.2.5 IsMealyMachineIntRep

◇ IsMealyMachineIntRep(*obj*)

(filter)

Returns: true if *obj* is a Mealy machine in integer representation.

A Mealy machine in *integer* representation has components *nrstates*, *transitions*, *output* and optionally *initial*.

Its *stateset* is $[1..nrstates]$, its *transitions* is a matrix with *transitions*[*s*][*x*] the transition from state *s* with input *x*, its *output* is a list of transformations or permutations, and its *initial state* is an integer.

11.2.6 IsMealyMachineDomainRep

◇ IsMealyMachineDomainRep(*obj*)

(filter)

Returns: true if *obj* is a Mealy machine in domain representation.

A Mealy machine in *domain* representation has components *states*, *transitions*, *output* and optionally *initial*.

Its *states* is a domain, its *transitions* is a function with *transitions*(*s*, *x*) the transition from state *s* with input *x*, its *output* is a function with *output*(*s*, *x*) the output from input *x* in state *s*, and its *initial state* is an element of *states*.

11.2.7 IsVectorFRMachineRep

◇ IsVectorFRMachineRep(*obj*)

(filter)

Returns: true if *obj* is a vector machine

A *vector machine* is a representation of a linear machine by a finite-dimensional vector space (implicit in the structure), a transition tensor (represented as a matrix of matrices), and an output vector (represented as a list).

11.2.8 IsAlgebraFRMachineRep

◇ IsAlgebraFRMachineRep(*obj*)

(filter)

Returns: true if *obj* is an algebra machine

An *algebra machine* is a representation of a linear machine by a finitely generated free algebra, a tensor of transitions, indexed by generator index and two alphabet indices, and an output vector, indexed by a generator index.

The transition tensor's last two entries are the 0 and 1 matrix over the free algebra, and the output tensor's last two entries are the 0 and 1 elements of the left acting domain.

11.2.9 IsLinearFRMachine

◇ IsLinearFRMachine(*obj*)

(filter)

Returns: true if *obj* is a linear machine.

This function is the acceptor for the *linear machine* subcategory of *FR machines*.

11.2.10 IsLinearFRElement

◇ IsLinearFRElement(*obj*)

(filter)

Returns: true if *obj* is a linear element.

This function is the acceptor for the *linear element* subcategory of *FR elements*.

11.2.11 IsFRElement

◇ IsFRElement(*obj*)

(filter)

Returns: true if *obj* is an FR element.

This function is the acceptor for the *functionally recursive element* category.

It implies that *obj* has an underlying FR machine, may act on sequences, and has a recursive DecompositionOfFRElement (4.2.5).

11.2.12 IsFRObject

◇ IsFRObject(*obj*)

(filter)

Returns: true if *obj* is an FR machine or element.

This function is the acceptor for the most general FR category (which splits up as IsFRMachine (11.2.13) and IsFRElement (11.2.11)).

It implies that *obj* has an attribute AlphabetOfFRObject (11.1.3).

11.2.13 IsFRMachine

◇ IsFRMachine(*obj*)

(filter)

Returns: true if *obj* is an FR machine.

This function is the acceptor for the *functionally recursive machine* category. It splits up as IsGroupFRMachine (11.2.1), IsSemigroupFRMachine (11.2.1), IsMonoidFRMachine (11.2.1) and IsMealyMachine (11.2.3).

It implies that *obj* has attributes StateSet (3.4.1), GeneratorsOfFRMachine (3.4.2), and WreathRecursion (3.4.5); the last two are usually not used for Mealy machines.

11.2.14 IsInvertible

◇ IsInvertible(*m*)

(property)

Returns: true if *m* is an invertible FR machine.

This function accepts invertible FR machines, i.e. machines *machine* such that $(machine, q)$ is an invertible transformation of the alphabet for all *q* in the stateset of *machine*.

Example

```
gap> m := FRMachine([[[[]], [[]]], [(1,2)]];
<FR machine with alphabet [ 1 .. 2 ] on Group( [ f1 ] )>
gap> IsInvertible(m);
true
gap> m := FRMachine([[[[]], [[]]], [[1,1]]];
<FR machine with alphabet [ 1 .. 2 ] on Monoid( [ m1 ], ... )>
gap> IsInvertible(m);
false
```

11.2.15 IsFRGroup

◇ IsFRGroup(*obj*) (filter)

◇ IsFRMonoid(*obj*) (filter)

◇ IsFRSemigroup(*obj*) (filter)

Returns: true if *obj* is a FR group/monoid/semigroup.

These functions accept *self-similar groups/monoids/semigroups*, i.e. groups/monoids/semigroups whose elements are FR elements.

11.2.16 IsFRAlgebra

◇ IsFRAlgebra(*obj*) (filter)

◇ IsFRAlgebraWithOne(*obj*) (filter)

Returns: true if *obj* is a FR algebra [with one].

These functions accept *self-similar algebras [with one]*, i.e. algebras whose elements are linear FR elements.

11.3 Some of the algorithms implemented

Few calculations with infinite groups can be guaranteed to terminate — and especially to terminate within reasonable time. This section describes some of the algorithms implemented in FR.

11.3.1 FRMachineRWS

◇ FRMachineRWS(*m*) (attribute)

Returns: A record containing a rewriting system for *m*.

Elements of an FR machine are compared using a rewriting system, which records all known relations among states of the machine.

Example

```
gap> n := FRMachine(["a","b"],[[[]],[2]],[[],[1]],[(1,2),()]);
<FR machine with alphabet [ 1 .. 2 ] on Group( [ a, b ] )>
gap> FRMachineRWS(n);
rec( rws := Knuth Bendix Rewriting System for Monoid( [ a^-1, a, b^-1, b
], ... ) with rules
  [ [ a^-1*a, <identity ...> ], [ a*a^-1, <identity ...> ],
    [ b^-1*b, <identity ...> ], [ b*b^-1, <identity ...> ] ],
  tzrules := [ [ [ 1, 2 ], [ ] ], [ [ 2, 1 ], [ ] ], [ [ 3, 4 ], [ ] ],
    [ [ 4, 3 ], [ ] ] ], letterrep := function( w ) ... end,
  pi := function( w ) ... end, reduce := function( w ) ... end,
  addgprule := function( w ) ... end, commit := function( ) ... end,
  restart := function( ) ... end )
```

11.3.2 Order of FR elements

The order of an FR element *e* is computed as follows: the tree is traversed recursively, filling it as follows. For each cycle of *e* on the first level, the product of the states on that cycle are computed. The method continues recursively with that product, remembering the order of the cycle. Once a state reappears in the traversal, FR determines if one instance of the state is in the subtree of the other, and if so whether the top one was raised to a non-trivial power to yield the second one as a state. If this

happens, then e has infinite order. Otherwise, the least common multiple of the powers that appeared in the traversal is returned.

This method is guaranteed to succeed if e is a bounded element. To improve chances of success, FR first computes whether e acts by vertex transformations belonging to an abelian group; and if so, if e is conjugate to an adding machine. In that case too, e has infinite order.

11.3.3 Membership in semigroups

The following algorithm is used to determine whether a Mealy element belongs to a self-similar group. The corresponding problem of membership of an FR element in a state-closed self-similar group can be much simpler, because an FR element has an associated FR machine, all of whose states belong to the group.

Assume the group is given by generators. FR attempts to express the given Mealy element as a product of generators. At the same time, it constructs epimorphisms to finite groups. It is hoped that one of these two processes will stop.

This amounts, in fact, to the following. Consider a group G acting on a tree. It has a natural, profinite closure \bar{G} . The algorithm then attempts either to write an element x as a product of generators of G , or to show that x does not belong to \bar{G} .

There are groups G such that $\bar{G} \setminus G$ contains Mealy machines. For these, the above algorithm will not terminate.

An additional refinement is implemented for bounded groups (see `IsBoundedFRSemigroup` (7.2.13)). The `Germ`s (5.2.24) of an element are computed, and compared to the germs of elements in the group.

Finally, for a group that possesses self-similar data (see Section 11.3.5), very fast methods are implemented to recognize and express an FR element as a product of generators.

11.3.4 Order of groups

The order of an FR group is computed as follows: if all generators are finitary, then enumeration will succeed in computing the order. If the action of the group is primitive, and it comes from a bireversible automaton, then the Thompson-Wielandt theorem is tested against. This theorem states that, in our context (a group acting on a rooted tree, coming from a larger group acting transitively), if the group is finite then the stabilizer of a sphere of radius 2 is a p -group; see [BM00a, Proposition 2.1.1]. Then, FR attempts to find whether the group is level-transitive (in which case it would be infinite). Finally, it attempts to enumerate the group's elements, testing at the same time whether these elements have infinite order.

Needless to say, none except the first few steps are guaranteed to succeed.

11.3.5 Images and preimages of some groups in f.p. and l.p. groups

Contracting, branched groups admit finite L-presentations (see [Bar03a]), that is, presentations by finitely many generators, relators and endomorphisms; the (usual) relators are the images of the given relators under iteration by all endomorphisms.

Using the package NQL, it is possible to construct infinite nilpotent quotients of self-similar groups, and perform fast computations in them.

It is possible to construct, algorithmically, such an L-presentation from a self-similar groups; however, this algorithm has not been implemented yet, mainly because efficiency issues would make

it usable only in very few cases.

For groups with an isomorphism to an L-presented group (constructed by `IsomorphismLpGroup` (7.2.27)), a fast method expresses group elements as words in the L-presented group's generators. It proceeds recursively on the decomposition of the element, mapping elements that are expressible by short words over the nucleus (usually length 1; length 3 is needed for the `BrunnerSidkiVieiraGroup` (10.1.12)) to their value in the L-presented group, and using the presentation's endomorphism to construct words with appropriate decompositions.

In particular, the algorithm will stop, returning `fail`, if during the recursion it reaches an element x such that x is a state of x but x does not belong to the nucleus.

11.3.6 Comparison of FR, Mealy, vector, and algebra elements

FR and Mealy elements can be compared quite efficiently, as long as they are distinct. The algorithm runs as follows: let the two elements be x and y . Considering both in turn, FR constructs the first entries of minimal Mealy elements expressing x and y ; as soon as an output entry is distinct for x and for y , the status of $x < y$ is determined; and similarly for transition entries. Finally, if either of x or y is finite-state and the entries were identical up to that step, then the element with smallest stateset is considered smaller.

In this way, FR and Mealy elements can efficiently be compared. For Mealy elements, it suffices to follow their internal data; while for FR elements, this amounts to constructing Mealy elements approximating them to a sufficient precision so that they can be compared as such.

The algorithm first tries to test its arguments for equality; this test is not guaranteed to succeed.

A similar algorithm applies for linear elements. Here, one constructs vector element approximations; and compares, for ever-increasing values of i , first the output vectors of basis state i ; then the transitions from state i to state j , for all $j \in \{1, \dots, i\}$; then the transitions from state j to state i for all $j \in \{1, \dots, i-1\}$.

11.3.7 Inverses of linear elements

It is probably difficult to compute the inverse of a vector element. The following approach is used: to compute the inverse of x , large (scalar) matrix approximations of x are computed; they are inverted using linear algebra; a vector element representing this inverse is guessed; and the guess is checked. As long as that check fails, larger approximations are computed.

Needless to say, this method need not succeed; for there are vector elements that are invertible, but whose inverse is not a vector element. A good test example appears in [Bac07]: consider the infinite matrix with 1's on the diagonal, and ω below the diagonal. This element admits an inverse if and only if ω is a root of unity. The complexity of the inverse grows as the degree of ω grows. Here is an illustration:

Example

```
gap> bacher := function(n)
  local f;
  f := CyclotomicField(n);
  return VectorElement(f, One(f) * [[[[[1, 0], [0, 0]],
    [[0, 0], [0, 1]]], [[0, 1], [0, 0]], [[1, 0], [0, 0]]], [One(f), E(n)], [One(f), Zero(f)]]);
end;;
gap> Inverse(bacher(3));
<Linear element on alphabet CF(3)^2 with 4-dimensional stateset>
6 gap> Inverse(bacher(5));
<Linear element on alphabet CF(5)^2 with 6-dimensional stateset>
```

n	1	2	3	4	5	6	7	8	9	10
dimension		2	4	4	6	3	5	5	8	5
n	11	12	13	14	15	16	17	18	19	20
dimension	?	5	?	4	6	6	?	7	?	7
n	22	24	26	28	30	32	34	36	38	40
dimension	?	6	?	6	?	7	?	?	?	?

Table: Dimension of states of inverse

Chapter 12

Miscellanea

12.1 Helpers

12.1.1 maybe

◇ `maybe` (global variable)

Some methods in FR search for an answer, either positive or negative, but fail to find one in reasonable time. They then return the value `maybe`, which is a boolean that is neither true nor false.

12.1.2 ReturnMaybe

◇ `ReturnMaybe(arg)` (function)

This function, similar to `ReturnTrue` or `ReturnFalse`, returns the value `maybe` (12.1.1).

12.1.3 TensorSum

◇ `TensorSum(objects, ...)` (function)

This function is similar in syntax to `DirectProduct` (**Reference: DirectProduct**), and delegates to `TensorSumOp`; its meaning depends on context, see e.g. `TensorSumOp` (3.5.4).

12.1.4 TensorProductX

◇ `TensorProductX(objects, ...)` (function)

This function is similar in syntax to `DirectProduct` (**Reference: DirectProduct**), and delegates to `TensorProductOp`; its meaning depends on context, see e.g. `TensorProductOp` (3.5.5).

12.1.5 DirectSum

◇ `DirectSum(objects, ...)` (function)

This function is similar in syntax to `DirectProduct` (**Reference: DirectProduct**), and delegates to `DirectSumOp`; its meaning depends on context, see e.g. `DirectSumOp` (3.5.6).

12.1.6 PeriodicList

◇ <code>PeriodicList(preperiod[, period])</code>	(operation)
◇ <code>PeriodicList(list, i)</code>	(operation)
◇ <code>PeriodicList(list, f)</code>	(operation)
◇ <code>CompressedPeriodicList(preperiod[, period])</code>	(operation)
◇ <code>CompressedPeriodicList(list, i)</code>	(operation)
◇ <code>PrePeriod(list)</code>	(operation)
◇ <code>Period(list)</code>	(operation)

These functions manipulate *periodic lists*, i.e. lists of infinite length such that elements follow a periodic order after some point.

The first command creates a periodic list, specified by its preperiod and period, which must both be lists. If the period is absent, this is actually a finite list.

The second command creates a periodic list by decreeing that the entries after the end of the list start again at position i .

The third command creates a list by applying function f to all elements of l .

The fourth and fifth command compress the newly created periodic list, see `CompressPeriodicList` (12.1.7).

The sixth and seventh commands return respectively the preperiod and period of a periodic list.

Example

```
gap> l := PeriodicList([1], [2, 3, 4]);
[ 1, / 2, 3, 4 ]
gap> l[5];
2
gap> Add(l, 100, 3); l;
[ 1, 2, 100, / 3, 4, 2 ]
gap> Remove(l, 5);
4
gap> l;
[ 1, 2, 100, 3, / 2, 3, 4 ]
gap> PrePeriod(l);
[ 1, 2, 100, 3 ]
gap> Period(l);
[ 2, 3, 4 ]
```

12.1.7 CompressPeriodicList

◇ <code>CompressPeriodicList(l)</code>	(operation)
--	-------------

This function compresses a periodic list, in replacing the period by a minimal period, and shortening the preperiod. No value is returned, but the list l is modified. It remains equal (under $=$) to the original list.

Example

```
gap> l := PeriodicList([1], [2, 3, 4, 2, 3, 4]);
[ 1, / 2, 3, 4, 2, 3, 4 ]
gap> Add(l, 4, 5); l;
[ 1, 2, 3, 4, 4, / 2, 3, 4, 2, 3, 4 ]
gap> CompressPeriodicList(l);
```

```
gap> l;
[ 1, 2, 3, 4, / 4, 2, 3 ]
```

12.1.8 IsConfinal

◇ **IsConfinal**(*l*, *m*) (operation)

Returns: true if *l* and *m* are eventually equal.

This function tests whether two lists are *confinal*, i.e. whether, after removal of the same suitable number of elements from both lists, they become equal.

Example

```
gap> l := PeriodicList([1],[2,3,2,3]);
[ 1, / 2, 3, 2, 3 ]
gap> m := PeriodicList([0,1],[3,2]);
[ 0, 1, / 3, 2 ]
gap> IsConfinal(l,m);
true
```

12.1.9 ConfinalityClass

◇ **ConfinalityClass**(*l*) (operation)

Returns: The strictly periodic list with same tail as *l*.

There exists a unique periodic list, with no preperiod, which is confinal (see **IsConfinal** (12.1.8)) to *l*. This strictly periodic list is returned by this command.

Example

```
gap> l := PeriodicList([1],[2,3,2,3]);
[ 1, / 2, 3, 2, 3 ]
gap> ConfinalityClass(l);
[/ 3, 2 ]
```

12.1.10 LargestCommonPrefix

◇ **LargestCommonPrefix**(*c*) (operation)

Returns: The longest list that is a prefix of all elements of *c*.

This command computes the longest (finite or periodic) list which is a prefix of all elements of *c*. The argument *c* is a collection of finite and periodic lists.

Example

```
gap> LargestCommonPrefix([PeriodicList([1],[2,3,2,3]), [1,2,3,4]]);
[ 1, 2, 3 ]
```

12.1.11 WordGrowth

◇ **WordGrowth**(*g*, *rec*(...)) (function)

◇ **OrbitGrowth**(*g*, *point*[, *limit*]) (function)

◇ **Ball**(*g*, *radius*) (function)

◇ **Sphere**(*g*, *radius*) (function)

Returns: The word growth of the semigroup *g*.

This function computes the first terms of growth series associated with the semigroup g . The argument g can actually be a group/monoid/semigroup, or a list representing that semigroup's generating set.

The behaviour of `WordGrowth` is controlled via options passed in the second argument, which is a record. They can be combined when reasonable, and are:

limit:=n to specify a limit radius;

sphere:=radius to return the sphere of the specified radius, unless a radius was specified in **limit**, in which case the value is ignored;

spheres:=maxradius to return the list of spheres of radius between 0 and the specified limit;

spheresizes:=maxradius to return the list sizes of spheres of radius between 0 and the specified limit;

ball:=radius to return the ball of the specified radius;

balls:=maxradius to return the list of balls of radius between 0 and the specified limit;

ballsizes:=maxradius to return the list sizes of balls of radius between 0 and the specified limit;

indet:=z to return the **spheresizes**, as a polynomial in z (or the first indeterminate if z is not a polynomial);

draw:=filename to create a rendering of the Cayley graph of g . Edges are given colours according to the cyclic ordering "red", "blue", "green", "gray", "yellow", "cyan", "orange", "purple". If **filename** is a string, the graph is appended, in dot format, to that file. Otherwise, the output is converted to Postscript using the program `neato` from the `graphviz` package, and displayed in a separate X window using the program `display`. This works on UNIX systems.

It is assumed, but not checked, that `graphviz` and `display` are properly installed on the system.

point:=p to compute the growth of the orbit of p under g , rather than the growth of g .

track:=true to keep track of a word in the generators that gives the element. This affects the "ball", "balls", "sphere" and "spheres" commands, where the result returned is a 3-element list: the first entry is the original results; the second entry is a homomorphism from a free group/monoid/semigroup; and the third entry contains the words corresponding to the first entry via the homomorphism.

If the first argument is an integer n and not a record, the command is interpreted as `WordGrowth(...,rec(spheresizes:=n))`.

`WordGrowth(...,rec(draw:=true))` may be abbreviated as `Draw(...)`;
`WordGrowth(...,rec(ball:=n))` may be abbreviated as `Ball(...,n)`;
`WordGrowth(...,rec(sphere:=n))` may be abbreviated as `Sphere(...,n)`;

Example

```
gap> WordGrowth(GrigorchukGroup,4);
[ 1, 4, 6, 12, 17 ]
gap> WordGrowth(GrigorchukGroup,rec(limit:=4,indet:=true));
17*x_1^4+12*x_1^3+6*x_1^2+4*x_1+1
```

```

gap> WordGrowth(GrigorchukGroup, rec(limit:=1, spheres:=true));
[ [ <Mealy element on alphabet [ 1, 2 ] with 1 state, initial state 1> ],
  [ d, b, c, a ] ]
gap> WordGrowth(GrigorchukGroup, rec(point:=[2,2,2]));
[ 1, 1, 1, 1, 1, 1, 1, 1 ]
gap> OrbitGrowth(GrigorchukGroup, [1,1,1]);
[ 1, 2, 2, 1, 1, 1 ]
gap> WordGrowth(GrigorchukGroup, rec(spheres:=4, point:=PeriodicList([], [2])));
[ [ [ / 2 ] ], [ [ 1, / 2 ] ], [ [ 1, 1, / 2 ] ], [ [ 2, 1, / 2 ] ],
  [ [ 2, 1, 1, / 2 ] ] ]
gap> WordGrowth([(1,2), (2,3)], rec(spheres:=infinity, track:=true));
[ [ [ ], [ (2,3), (1,2) ], [ (), (1,2,3), (1,3,2) ], [ (1,3) ] ],
  MappingByFunction( <free semigroup on the generators [ s1, s2 ]>, <group>, function( w ) ... end
    [ [ ], [ s2, s1 ], [ s2^2, s2*s1, s1*s2 ], [ s2*s1*s2 ] ] ]

```

Note that the orbit growth of $[/2]$ is constant 1, while that of $[/1]$ is constant 2. The following code would find the point with maximal orbit growth of a semigroup acting on the integers (for example, constructed with `PermGroup (7.2.1)`):

```

MaximalOrbitGrowth := function(g)
  local maxpt, growth, max;
  maxpt := LargestMovedPoint(g);
  growth := List([1..maxpt], n->WordGrowth(g:point:=n));
  max := Maximum(growth);
  return [max, Filtered([1..maxpt], n->growth[n]=max)];
end;

```

12.1.12 ShortGroupRelations

◇ `ShortGroupRelations(g , n)` (operation)

◇ `ShortMonoidRelations(g , n)` (operation)

Returns: A list of relations between words over g , of length at most n .

This function assumes that g is a list of monoid elements. it searches for products of at most n elements over g that are equal.

In its first form, it returns a list of words in a free group f of rank the length of g , that are trivial in g . The first argument may be a group, in which case its symmetric generating set is considered.

In its second form, it returns a list of pairs $[l, r]$, where l and r are words in a free monoid f of rank the length of g , that are equal in g . The first argument may be a monoid, in which case its monoid generating set is considered.

This command does not construct all such pairs; rather, it returns a small set, in the hope that it may serve as a presentation for the monoid generated by g .

The first element of the list returned is actually not a relation: it is a homomorphism from f to [the group/monoid generated by] g .

Example

```

gap> ShortGroupRelations(GrigorchukGroup, 10);
[ [ x1, x2, x3, x4 ] -> [ a, b, c, d ],
  x1^2, x2^2, x3^2, x4^2, x2*x3*x4, x4*x1*x4*x1*x4*x1*x4*x1,
  x3*x1*x3*x1*x3*x1*x3*x1*x3*x1*x3*x1*x3*x1 ]
gap> ShortGroupRelations(GuptaSidkiGroup, 9);
[ [ x1, x2 ] -> [ x, gamma ],

```

12.1.13 ShortGroupWordInSet

◇ ShortSemigroupWordInSet(g, s, n) (operation)

The function returns a list of words in the free group/monoid/semigroup; the first entry of the list is a homomorphism from the free group/monoid/semigroup to \mathcal{G} .

12.1.14 SurfaceBraidFpGroup

◇ `PureSurfaceBraidFpGroup(n, q, p)` (function)

The pure surface braid group is the kernel of the natural map from the surface braid group to the symmetric group on n points, defined by sending a_i, b_i, z to the identity and s_i to the transposition $(i, i+1)$.

12.1.15 CharneyBraidFpGroup

Returns: The braid group on n strands.

This function creates a finitely presented group, isomorphic to the braid group on n strands (on the disc). It is isomorphic to `SurfaceBraidFpGroup(n, 0, 1)`, but has a different presentation, due to Charney ([Cha95]), with one generator per non-trivial permutation of n points.

12.1.16 **ArtinRepresentation**

◇ `ArtinRepresentation(n)` (function)

Returns: The braid group's representation on `FreeGroup(n)`.

This function creates a Artin's representatin, a homomorphism from the braid group on n strands (on the disc) into the automorphism group of a free group of rank n .

12.1.17 **StringByInt**

◇ `StringByInt(n[, b])` (function)

Returns: A string representing n in base b .

This function converts a positive integer to string. It accepts an optional second argument, which is a base in which to print n . By default, b is 2.

12.1.18 **PositionTower**

◇ `PositionTower(t, x)` (function)

Returns: The largest index such that `t[i]` contains x .

This function assumes t is a descending tower of domains, such as that constructed by `LowerCentralSeries`. It returns the largest integer i such that `t[i]` contains x ; in case the tower ends precisely with x , the value `infinity` is returned.

x can be an element or a subdomain of `t[1]`.

12.1.19 **CoefficientsInAbelianExtension**

◇ `CoefficientsInAbelianExtension(x, b, G)` (function)

Returns: The coefficients in b of the element x , modulo G .

If b is a list of group elements b_1, \dots, b_k , and $H = \langle G, b_1, \dots, b_k \rangle$ contains G as a normal subgroup, and H/G is abelian and $x \in H$, then this function computes exponents e_1, \dots, e_k such that $\prod b_i^{e_i} G = xG$.

12.1.20 **MagmaEndomorphismByImagesNC**

◇ `MagmaEndomorphismByImagesNC(f, im)` (function)

Returns: An endomorphism of f .

This function constructs an endomorphism of the group, monoid or semi-group f specified by sending generator number i to the i th entry in im . It is a shortcut for a call to `GroupHomomorphismByImagesNC` or `MagmaHomomorphismByFunctionNC(..., MappedWord(...))`.

12.1.21 **MagmaHomomorphismByImagesNC**

◇ `MagmaHomomorphismByImagesNC(f, g, im)` (function)

Returns: An homomorphism from f to g .

This function constructs a homomorphism of the group, monoid or semi-group f specified by sending generator number i to the i th entry in im . It is a shortcut for a call to `GroupHomomorphismByImagesNC` or `MagmaHomomorphismByFunctionNC(..., MappedWord(...))`.

12.1.22 NewFIFO

◇ `NewFIFO([l])` (operation)
 ◇ `Add(f, i)` (operation)
 ◇ `Append(f, l)` (operation)

These functions create and extend FIFOs, i.e. first-in first-out data structures.

The first command creates a FIFO, with an optional list initializing it.

The second and third commands add an element, or append a list, to the FIFO.

Elements are removed via `NextIterator(f)`, and the FIFO is tested for emptiness via `IsDoneIterator(f)`. Thus, a typical use is the following code, which tests in breadth-first manner that all numbers in `[1..1000]` have a successor which is prime:

Example

```
gap> f := NewFIFO([1..1000]);
<iterator>
gap> for i in f do if not IsPrime(i) then Add(f,i+1); fi; od;
```

12.1.23 ProductIdeal

◇ `ProductIdeal(a, b)` (function)
 ◇ `ProductBOIIdeal(a, b)` (function)

Returns: the product of the ideals a and b .

The first command computes the product of the left ideal a and the right ideal b . If they are not appropriately-sided ideals, the command first attempts to convert them.

The second command assumes that the ring of these ideals has a basis made of invertible elements. It is then much easier to compute the product.

12.1.24 DimensionSeries

◇ `DimensionSeries(a[, n])` (function)

Returns: A nested list of ideals in the algebra-with-one a .

This command computes the powers of the augmentation ideal of a , and returns their list. The list stops when the list becomes stationary.

The optional second argument gives a limit to the number of terms to put in the series.

Example

```
gap> a := ThinnedAlgebraWithOne(GF(2), GrigorchukGroup);
<self-similar algebra-with-one on alphabet GF(2)^2 with 4 generators>
gap> q := MatrixQuotient(a, 3);
<algebra-with-one of dimension 22 over GF(2)>
gap> l := DimensionSeries(q);
[ <two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (5 generators)>,
  <two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (dimension 21)>,
  <two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (dimension 18)>,
  <two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (dimension 14)>]
```

```

<two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (dimension 10)>,
<two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (dimension 6)>,
<two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (dimension 3)>,
<two-sided ideal in <algebra-with-one of dimension 22 over GF(2)>, (dimension 1)>,
<algebra of dimension 0 over GF(2)> ]

```

12.1.25 Trans

◇ `Trans(list, ...)`

(function)

This function creates a new transformation, in the family `TRANS_FAMILY`. These objects behave quite as usual transformations (see `Transformation` (**Reference: Transformation**)); the differences are that these transformations do not have a bounded set on which they operate; they are all part of one family, and act on `PosInt`. The other difference is that, when they are invertible, these transformations are simply permutations.

If one argument is passed, it is a list of images, as in `PermList` (**Reference: PermList**). If two arguments are passed and both are lists, they are the source and range, as in `PermListList` (**Reference: PermListList**). Finally, if two arguments are passed and the second is a function, the first argument is treated as the source and the range is computed with this function.

Transformations are printed, and converted to strings, as "`<x,y,...>`", where the `x,y,...` denote the images of `1,2,...` under the transformation; the shortest possible list is printed.

Example

```

gap> Trans();
<>
gap> Trans([1,,2]);
<1,2,2>
gap> 3^last;
2
gap> Trans([1,3,3]);
<1,3>
gap> Trans([10,11],[11,12]);
<1,2,3,4,5,6,7,8,9,11,12>
gap> Trans([10,11],x->x^2);
<1,2,3,4,5,6,7,8,9,100,121>

```

12.2 User settings

12.2.1 InfoFR

◇ `InfoFR`

(info class)

This is an `Info` class for the package `FR`. The command `SetInfoLevel(InfoFR,1);` switches on the printing of some information during the computations of certain `FR` functions; in particular all automatic conversions between `FR` machines and `Mealy` machines.

The command `SetInfoLevel(InfoFR,2);` requests a little more information, and in particular prints intermediate results in potentially long calculations such as `NucleusOfFRSemigroup` (7.2.17).

The command `SetInfoLevel(InfoFR,3);` ensures that `FR` will print information every few seconds or so. This is useful to gain confidence that the program is not stuck due to a programming bug

by the author of FR.

12.2.2 FR_SEARCH

◇ FR_SEARCH

(global variable)

This variable controls the search mechanism in FR groups. It is a record with in particular entries `radius` and `depth`.

`radius` limits the search in FR groups to balls of that radius in the generating set. For example, the command `x in G` will initiate a search in `G` to attempt to express `x` as a reasonably short word in the generators of `G`.

`depth` limits the level of the tree on which quotients of FR groups should be considered. Again for the command `x in G`, deeper and deeper quotients will be considered, in the hope of finding a quotient of `G` to which `x` does not belong.

A primitive mechanism is implemented to search alternatively for a quotient disproving `x in G` and a word proving `x in G`.

When the limits are reached and the search was unsuccessful, an interactive `Error()` is raised, to let the user increase their values.

Specific limits can be passed to any command via the options `FRdepth` and `FRradius`, as for example in `Size(G:FRdepth:=3,FRradius:=5)`.

References

- [Ale83] S. V. Aleshin. A free group of finite automata. *Vestnik Moskov. Univ. Ser. I Mat. Mekh.*, (4):12–14, 1983. [12](#), [102](#), [105](#)
- [Bac07] R. Bacher. Determinants related to binomial coefficients modulo 2 and 4. arXiv:math/0708.1430, 2007. [109](#), [121](#)
- [Bar03a] L. Bartholdi. Endomorphic presentations of branch groups. *J. Algebra*, 268(2):419–443, 2003. [84](#), [101](#), [120](#)
- [Bar03b] L. Bartholdi. A Wilson group of non-uniformly exponential growth. *C. R. Math. Acad. Sci. Paris*, 336(7):549–554, 2003. [104](#)
- [Bel04] P. Bellingeri. On presentations of surface braid groups. *J. Algebra*, 274(2):543–563, 2004. [128](#)
- [BFH92] B. Bielefeld, Y. Fisher, and J. Hubbard. The classification of critically preperiodic polynomials as dynamical systems. *J. Amer. Math. Soc.*, 5(4):721–762, 1992. [92](#)
- [BG02] L. Bartholdi and R. I. Grigorchuk. On parabolic subgroups and Hecke algebras of some fractal groups. *Serdica Math. J.*, 28(1):47–90, 2002. [101](#), [104](#)
- [BGN03] L. Bartholdi, R. Grigorchuk, and V. Nekrashevych. From fractal groups to fractal sets. In *Fractals in Graz 2001*, Trends Math., pages 25–118. Birkhäuser, Basel, 2003. [11](#)
- [BGŠ03] L. Bartholdi, R. I. Grigorchuk, and Z. Šuník. Branch groups. In *Handbook of algebra*, Vol. 3, pages 989–1112. North-Holland, Amsterdam, 2003. [11](#), [99](#)
- [BM97] M. Burger and S. Mozes. Finitely presented simple groups and products of trees. *C. R. Acad. Sci. Paris Sér. I Math.*, 324(7):747–752, 1997. [114](#)
- [BM00a] M. Burger and S. Mozes. Groups acting on trees: from local to global structure. *Inst. Hautes Études Sci. Publ. Math.*, (92):113–150 (2001), 2000. [105](#), [120](#)
- [BM00b] M. Burger and S. Mozes. Lattices in product of trees. *Inst. Hautes Études Sci. Publ. Math.*, (92):151–194 (2001), 2000. [105](#)
- [BR05] L. Bartholdi and I. I. Reznikov. A mealy machine of growth $n^{2.4401}$. arXiv:math.GR/0506203, 2005. [108](#)
- [BRS06] L. Bartholdi, I. I. Reznikov, and V. I. Sushchansky. The smallest Mealy automaton of intermediate growth. *J. Algebra*, 295(2):387–414, 2006. [108](#)

- [BS62] G. Baumslag and D. Solitar. Some two-generator one-relator non-Hopfian groups. *Bull. Amer. Math. Soc.*, 68:199–201, 1962. [106](#)
- [BŠ01] L. Bartholdi and Z. Šuník. On the word and period growth of some groups of tree automorphisms. *Comm. Algebra*, 29(11):4923–4964, 2001. [99](#)
- [BSV99] A. M. Brunner, S. Sidki, and A. C. Vieira. A just nonsolvable torsion-free group defined on the binary tree. *J. Algebra*, 211(1):99–114, 1999. [102](#)
- [BV05] L. Bartholdi and B. Virág. Amenability via random walks. *Duke Math. J.*, 130(1):39–56, 2005. [12](#), [98](#)
- [Cha95] R. Charney. Geodesic automation and growth functions for Artin groups of finite type. *Math. Ann.*, 301(2):307–324, 1995. [129](#)
- [Dah05] F. Dahmani. An example of non-contracting weakly branch automaton group. In *Geometric methods in group theory*, volume 372 of *Contemp. Math.*, pages 219–224. Amer. Math. Soc., Providence, RI, 2005. [105](#)
- [DH84] A. Douady and J. H. Hubbard. *Étude dynamique des polynômes complexes. Partie I*, volume 84 of *Publications Mathématiques d’Orsay [Mathematical Publications of Orsay]*. Université de Paris-Sud, Département de Mathématiques, Orsay, 1984. [92](#)
- [DH85] A. Douady and J. H. Hubbard. *Étude dynamique des polynômes complexes. Partie II*, volume 85 of *Publications Mathématiques d’Orsay [Mathematical Publications of Orsay]*. Université de Paris-Sud, Département de Mathématiques, Orsay, 1985. With the collaboration of P. Lavaurs, Tan Lei and P. Sentenac. [92](#)
- [EH07] B. Eick and R. Hartung. A nilpotent quotient algorithm for l-presented groups. submitted, 2007. [84](#)
- [Ers04] A. Erschler. Boundary behavior for groups of subexponential growth. *Ann. of Math. (2)*, 160(3):1183–1210, 2004. [100](#)
- [FG85] J. Fabrykowski and N. Gupta. On groups with sub-exponential growth functions. *J. Indian Math. Soc. (N.S.)*, 49(3-4):249–256 (1987), 1985. [104](#)
- [FG91] J. Fabrykowski and N. Gupta. On groups with sub-exponential growth functions. II. *J. Indian Math. Soc. (N.S.)*, 56(1-4):217–228, 1991. [104](#)
- [GM05] Y. Glasner and S. Mozes. Automata and square complexes. *Geom. Dedicata*, 111:43–64, 2005. [105](#)
- [Gri80] R. I. Grigorčuk. On Burnside’s problem on periodic groups. *Funktsional. Anal. i Prilozhen.*, 14(1):53–54, 1980. [12](#), [101](#)
- [Gri84] R. I. Grigorchuk. Degrees of growth of finitely generated groups and the theory of invariant means. *Izv. Akad. Nauk SSSR Ser. Mat.*, 48(5):939–985, 1984. [100](#)
- [GS83] N. Gupta and S. Sidki. On the Burnside problem for periodic groups. *Math. Z.*, 182(3):385–388, 1983. [12](#), [103](#)

- [GŠ06] R. Grigorchuk and Z. Šunić. Asymptotic aspects of Schreier graphs and Hanoi Towers groups. *C. R. Math. Acad. Sci. Paris*, 342(8):545–550, 2006. [105](#)
- [GŽ02] R. I. Grigorchuk and A. Žuk. On a torsion-free weakly branch group defined by a three state automaton. *Internat. J. Algebra Comput.*, 12(1-2):223–246, 2002. International Conference on Geometric and Combinatorial Methods in Group Theory and Semigroup Theory (Lincoln, NE, 2000). [12](#), [98](#)
- [Lys85] I. G. Lysénok. A set of defining relations for the Grigorchuk group. *Mat. Zametki*, 38(4):503–516, 634, 1985. [101](#)
- [Mam03] M. J. Mamaghani. A fractal non-contracting class of automata groups. *Bull. Iranian Math. Soc.*, 29(2):51–64, 92, 2003. [105](#)
- [MNS00] O. Macedońska, V. Nekrashevych, and V. Sushchansky. Commensurators of groups and reversible automata. *Dopov. Nats. Akad. Nauk Ukr. Mat. Prirodozn. Tekh. Nauki*, (12):36–39, 2000. [45](#), [46](#)
- [Nek05] V. Nekrashevych. *Self-similar groups*, volume 117 of *Mathematical Surveys and Monographs*. American Mathematical Society, Providence, RI, 2005. [21](#), [91](#), [103](#)
- [Neu86] P. M. Neumann. Some questions of Edjvet and Pride about infinite groups. *Illinois J. Math.*, 30(2):301–316, 1986. [104](#)
- [Pet06] V. M. Petrogradsky. Examples of self-iterating Lie algebras. *J. Algebra*, 302(2):881–886, 2006. [108](#)
- [Poi] A. Poirier. On postcritically finite polynomials, part 1: critical portraits. Stony Brook IMS 1993/5. [92](#)
- [Sid00] S. Sidki. Automorphisms of one-rooted trees: growth, circuit structure, and acyclicity. *J. Math. Sci. (New York)*, 100(1):1925–1943, 2000. Algebra, 12. [46](#)
- [Sid05] S. Sidki. Tree-wreathing applied to generation of groups by finite automata. *Internat. J. Algebra Comput.*, 15(5-6):1205–1212, 2005. [26](#), [73](#)
- [SS05] P. V. Silva and B. Steinberg. On a class of automata groups generalizing lamplighter groups. *Internat. J. Algebra Comput.*, 15(5-6):1213–1234, 2005. [107](#)
- [Šun07] Z. Šunić. Hausdorff dimension in a family of self-similar groups. *Geom. Dedicata*, 124:213–236, 2007. [100](#)
- [SVV06] B. Steinberg, M. Vorobets, and Y. Vorobets. Automata over a binary alphabet generating free groups of even rank. arXiv:math.GR/0610033, 2006. [102](#)
- [SW03] S. Sidki and J. S. Wilson. Free subgroups of branch groups. *Arch. Math. (Basel)*, 80(5):458–463, 2003. [73](#)
- [SZ08] I. P. Shestakov and E. Zelmanov. Some examples of nil Lie algebras. *J. Eur. Math. Soc. (JEMS)*, 10(2):391–398, 2008. [108](#)
- [Tan02] D. T. Tan. Quadratische morphismen. Diplomarbeit at ETHZ, under the supervision of R. Pink, 2002. [93](#)

- [vN29] J. von Neumann. Zur allgemeinen Theorie des Masses. *Fund. Math.*, 13:73–116 and 333, 1929. (= Collected works, vol. I, pages 599–643). [86](#)
- [VV06] M. Vorobets and Y. Vorobets. On a series of finite automata defining free transformation groups. arXiv:math.GR/0604328, 2006. [102](#)

Index

- *, [24](#)
 - PROD, [39](#)
- \+, [23](#)
- \[\]
- ELMLIST, [39](#)
- \^
 - POW, [38](#)
- \{\}
- ELMSLIST, [39](#)
- Activities, [60](#)
- Activity, [34](#)
- ActivityInt, [34](#)
- ActivityPerm, [34](#)
- ActivitySparse, [59](#)
- ActivityTransformation, [34](#)
- Add
 - FIFO, [130](#)
- AddingElement, [98](#)
- AddingGroup, [98](#)
- AddingMachine, [98](#)
- AleshinGroup, [102](#)
- AleshinGroups, [102](#)
- AleshinMachine, [102](#)
- AleshinMachines, [102](#)
- AlgebraElement, [57](#)
- AlgebraElementNC, [57](#)
- AlgebraMachine, [57](#)
- AlgebraMachineNC, [57](#)
- AllMealyMachines, [42](#)
- AlphabetInvolution, [45](#)
- AlphabetOfFRObject, [115](#)
- Append
 - FIFO, [130](#)
- ArtinRepresentation, [129](#)
- AsAlgebraElement, [63](#)
 - Linear machine, [64](#)
- AsAlgebraMachine, [63](#)
 - Linear machine, [64](#)
- AsGroupFRElement, [32](#)
- AsGroupFRMachine, [19](#)
- AsIntMealyElement, [51](#)
- AsIntMealyMachine, [51](#)
- AsLinearElement, [62](#)
- AsLinearMachine, [62](#)
- AsLpGroup, [84](#)
- AsMealyElement, [51](#)
- AsMealyMachine
 - FR machine, [50](#)
 - List, [50](#)
- AsMonoidFRElement, [32](#)
- AsMonoidFRMachine, [19](#)
- AsPermutation
 - FR object, [116](#)
- AsSemigroupFRElement, [32](#)
- AsSemigroupFRMachine, [19](#)
- AsSubgroupFpGroup, [84](#)
- AsTransformation
 - FR object, [116](#)
- AsVectorElement, [63](#)
 - Linear machine, [64](#)
- AsVectorMachine, [63](#)
 - Linear machine, [64](#)
- BabyAleshinGroup, [103](#)
- BabyAleshinMachine, [103](#)
- Ball, [125](#)
- BasilicaGroup, [98](#)
- BinaryAddingElement, [99](#)
- BinaryAddingGroup, [99](#)
- BinaryAddingMachine, [99](#)
- BinaryKneadingGroup, [97](#)
- BinaryKneadingMachine, [97](#)
- BoundedBinaryGroup, [97](#)
- BranchingIdeal, [89](#)
- BranchingSubgroup, [81](#)
- BrunnerSidkiVieiraGroup, [102](#)
- BrunnerSidkiVieiraMachine, [102](#)

- CanonicalQuadraticRational, [94](#)
- CayleyGroup, [107](#)
- CayleyMachine, [107](#)
- ChangeFRMachineBasis, [20](#)
- CharneyBraidFpGroup, [128](#)
- CoefficientsInAbelianExtension, [129](#)
- ComposeElement
 - elementcoll,perm**, [30](#)
- CompressedPeriodicList, [124](#)
 - period, looping point**, [124](#)
- CompressPeriodicList, [124](#)
- ConfinalityClass, [125](#)
- ConfinalityClasses, [52](#)
- Correspondence
 - FR machine**, [27](#)
 - FR semigroup**, [68](#)
- CriticalValuesQuadraticRational, [94](#)
- DahmaniGroup, [105](#)
- DBRationalIMGGroup, [93](#)
- DecompositionOfFRElement, [35](#)
- Degree
 - FR element**, [46](#)
 - FR semigroup**, [79](#)
- DegreeOfFRElement, [46](#)
- DegreeOfFRMachine, [46](#)
- DegreeOfFRSemigroup, [79](#)
- Depth
 - FR element**, [47](#)
 - FR semigroup**, [79](#)
- DepthOfFRElement, [47](#)
- DepthOfFRMachine, [47](#)
- DepthOfFRSemigroup, [79](#)
- DiagonalElement, [31](#)
- DimensionSeries, [130](#)
- DirectProductOp
 - FR Machines**, [25](#)
- DirectSum, [123](#)
- DirectSumOp
 - FR Machines**, [25](#)
- Draw, [43](#)
- DualMachine, [44](#)
- EpimorphismFromFpGroup, [84](#)
- EpimorphismGermGroup, [76](#)
 - EGG0**, [76](#)
- EpimorphismMatrixQuotient, [89](#)
- EpimorphismPcGroup, [74](#)
- EpimorphismPermGroup, [73](#)
- EpimorphismTransformationMonoid, [75](#)
- EpimorphismTransformationSemigroup, [75](#)
- EpimorphismTransMonoid, [75](#)
- EpimorphismTransSemigroup, [75](#)
- FabrykowskiGuptaGroup, [104](#)
- FabrykowskiGuptaGroups, [104](#)
- FindBranchingSubgroup, [81](#)
- FinitaryBinaryGroup, [97](#)
- FiniteDepthBinaryGroup, [97](#)
- FiniteStateBinaryGroup, [97](#)
- FixedRay
 - FR element**, [49](#)
- FixedStates, [37](#)
- FRAffineGroup, [106](#)
- FRAlgebra, [88](#)
- FRAlgebraWithOne, [88](#)
- FRFamily, [115](#)
- FRElement
 - [list,]list,list,list**, [29](#)
 - machine/element,list**, [30](#)
 - semigroup,list,list,list**, [29](#)
- FRElementNC
 - family,free,listlist,list,assocword**, [28](#)
- FRGroup, [65](#)
- FRGroupByVirtualEndomorphism, [72](#)
- FRMachine
 - [list,]list,list**, [17](#)
 - semigroup,list,list**, [17](#)
- FRMachineFRGroup, [69](#)
- FRMachineFRMonoid, [69](#)
- FRMachineFRSemigroup, [69](#)
- FRMachineNC
 - family,free,listlist,list**, [17](#)
- FRMachineRWS, [119](#)
- FRMFamily, [115](#)
- FRMonoid, [65](#)
- FR_SEARCH, [132](#)
- FRSemigroup, [65](#)
- FullBinaryGroup, [97](#)
- FullSCGroup, [68](#)
- FullSCMonoid, [68](#)
- FullSCSemigroup, [68](#)
- GammaPQGroup, [104](#)

- GammaPQMachine, 104
- GeneralizedGuptaSidkiGroups, 103
- GeneratorsOfFRMachine, 21
- Germes, 53
- GrigorchukEvilTwin, 101
- GrigorchukGroup, 101
- GrigorchukGroups, 100
- GrigorchukMachine, 101
- GrigorchukMachines, 100
- GrigorchukOverGroup, 101
- GrigorchukThinnedAlgebra, 109
- GuessMealyElement, 54
- GuessVectorElement, 62
- GuptaSidkiGroup, 104
- GuptaSidkiGroups, 103
- GuptaSidkiMachine, 104
- GuptaSidkiMachines, 103
- GuptaSidkiThinnedAlgebra, 109
- HanoiGroup, 105
- HasOpenSetConditionFRElement, 53
- HasOpenSetConditionFRSemigroup, 80
- HorizontalAction, 113
- I2Machine, 108
- I2Monoid, 108
- I4Machine, 108
- I4Monoid, 108
- IMGFRMachine
 - FR machine, 91
 - rational function, 96
- IMGRelator, 91
- InfoFR, 131
- InitialState, 38
- IsAlgebraFRMachineRep, 117
- IsAmenableGroup, 86
- IsAntisymmetricFRElement, 60
- IsBireversible, 46
- IsBoundedFRElement, 47
- IsBoundedFRMachine, 47
- IsBoundedFRSemigroup, 79
- IsBranched
 - FR group, 82
- IsBranchingSubgroup
 - FR semigroup, 82
- IsConfinal, 125
- IsContracting, 80
- IsConvergent, 60
- IsDiagonalFRElement, 60
- IsFinitaryFRElement, 47
- IsFinitaryFRMachine, 47
- IsFinitaryFRSemigroup, 79
- IsFiniteStateFRElement, 37
- IsFiniteStateFRMachine, 37
- IsFiniteStateFRSemigroup, 79
- IsFRAlgebra, 119
- IsFRAlgebraWithOne, 119
- IsFRElement, 118
- IsFRGroup, 119
- IsFRMachine, 118
- IsFRMachineStrRep, 116
- IsFRMonoid, 119
- IsFRObject, 118
- IsFRSemigroup, 119
- IsGroupFRMachine, 116
- IsInfinitelyTransitive, 79
- IsInvertible, 118
- IsIrreducibleVHGroup, 113
- IsJustInfinite, 86
- IsLevelTransitive
 - FR element, 49
 - FR group, 78
- IsLinearFRElement, 118
- IsLinearFRMachine, 117
- IsLowerTriangularFRElement, 60
- IsMealyElement, 117
- IsMealyMachine, 116
- IsMealyMachineDomainRep, 117
- IsMealyMachineIntRep, 117
- IsMinimized, 45
- IsMonoidFRMachine, 116
- IsomorphismFRGroup, 70
- IsomorphismFRMonoid, 70
- IsomorphismFRSemigroup, 70
- IsomorphismLpGroup, 84
- IsomorphismMealyGroup, 71
- IsomorphismMealyMonoid, 71
- IsomorphismMealySemigroup, 71
- IsomorphismSubgroupFpGroup, 84
- IsPolynomialGrowthFRElement, 48
- IsPolynomialGrowthFRMachine, 48
- IsPolynomialGrowthFRSemigroup, 79
- IsRecurrentFRSemigroup, 78
- IsResiduallyFinite, 86

- IsReversible, [45](#)
- IsSemigroupFRMachine, [116](#)
- IsSQUniversal, [86](#)
- IsStateClosedFRSemigroup, [77](#)
- IsSymmetricFRElement, [60](#)
- IsTorsionFreeGroup, [85](#)
- IsTorsionGroup, [85](#)
- IsUpperTriangularFRElement, [60](#)
- IsVectorFRMachineRep, [117](#)
- IsVHGroup, [113](#)
- IsVirtuallySimpleGroup, [86](#)
- IsWeaklyFinitaryFRElement, [52](#)
- IsWeaklyFinitaryFRSemigroup, [79](#)
- LamplighterGroup, [107](#)
- LargestCommonPrefix, [125](#)
- LDUdecompositionFRElement, [61](#)
- LevelStabilizer, [77](#)
- LimitMachine, [53](#)
- LimitStates, [37](#)
- MagmaEndomorphismByImagesNC, [129](#)
- MagmaHomomorphismByImagesNC, [129](#)
- MamaghaniGroup, [105](#)
- Mating, [92](#)
- MatrixQuotient, [89](#)
- MaximalSimpleSubgroup, [114](#)
- maybe, [123](#)
- MealyElement
 - [list,]listlist,list,int, [40](#)
 - domain,domain,function,function,obj, [41](#)
- MealyElementNC
 - family,listlist,list,int, [42](#)
- MealyMachine
 - [list,]listlist,list, [40](#)
 - domain,domain,function,function, [41](#)
- MealyMachineFRGroup, [69](#)
- MealyMachineFRMonoid, [69](#)
- MealyMachineFRSemigroup, [69](#)
- MealyMachineNC
 - family,listlist,list, [42](#)
- Minimized
 - FR machine, [27](#)
 - Mealy machine, [44](#)
- MixerGroup, [99](#)
- MixerMachine, [99](#)
- NestedMatrixCoefficient, [59](#)
- NestedMatrixState, [59](#)
- NeumannGroup, [104](#)
- NeumannMachine, [104](#)
- NewFIFO, [130](#)
- Nillity, [90](#)
- NormOfBoundedFRElement, [53](#)
- NucleusMachine
 - FR machine, [54](#)
 - FR semigroup, [81](#)
- NucleusOfFRSemigroup, [80](#)
- OrbitGrowth, [125](#)
- OtherSpinalGroup, [104](#)
- Output
 - FR element, [33](#)
 - FR machine,state, [22](#)
 - FR machine,state,letter, [22](#)
- PcGroup, [74](#)
- Period, [124](#)
- PeriodicList, [124](#)
 - list, function, [124](#)
 - period, looping point, [124](#)
- PermGroup, [73](#)
- PolynomialFRMachine, [92](#)
- PolynomialGrowthBinaryGroup, [97](#)
- PolynomialIMGMachine, [92](#)
- PolynomialMealyMachine, [92](#)
- Portrait, [35](#)
- PortraitInt, [35](#)
- PositionTower, [129](#)
- PostCriticalMachine, [95](#)
- PrePeriod, [124](#)
- ProductBOIIdeal, [130](#)
- ProductIdeal, [130](#)
- PSZAlgebra, [108](#)
- PureSurfaceBraidFpGroup, [128](#)
- RationalFunction, [95](#)
- ReturnMaybe, [123](#)
- SCAlgebra, [89](#)
- SCAlgebraNC, [89](#)
- SCAlgebraWithOne, [89](#)
- SCAlgebraWithOneNC, [89](#)
- SCGroup, [67](#)
- SCGroupNC, [67](#)
- SCMonoid, [67](#)

- SCMonoidNC, [67](#)
- SCSemigroup, [67](#)
- SCSemigroupNC, [67](#)
- ShortGroupRelations, [127](#)
- ShortGroupWordInSet, [128](#)
- ShortMonoidRelations, [127](#)
- ShortMonoidWordInSet, [128](#)
- ShortSemigroupWordInSet, [128](#)
- SidkiFreeAlgebra, [109](#)
- SidkiFreeGroup, [103](#)
- Signatures, [48](#)
- Sphere, [125](#)
- StabilizerImage, [76](#)
- State, [36](#)
- StateClosure, [78](#)
- StateGrowth, [46](#)
- States, [36](#)
- StateSet
 - FR element**, [35](#)
 - FR machine**, [21](#)
- StringByInt, [129](#)
- StructuralGroup, [23](#)
- StructuralMonoid, [23](#)
- StructuralSemigroup, [23](#)
- SubFRMachine, [26](#)
- SunicGroup, [100](#)
- Sunicmachine, [100](#)
- SurfaceBraidFpGroup, [128](#)
- TensorProductOp
 - FR Machines**, [24](#)
- TensorProductX, [123](#)
- TensorSum, [123](#)
- TensorSumOp
 - FR Machines**, [24](#)
- ThinnedAlgebra, [90](#)
- ThinnedAlgebraWithOne, [90](#)
- TopElement, [52](#)
- TopVertexTransformations, [82](#)
- Trans, [131](#)
- TransformationMonoid, [75](#)
- TransformationSemigroup, [75](#)
- Transition
 - FR element,input**, [34](#)
 - FR machine,state,input**, [22](#)
 - Linear machine**, [58](#)
- Transitions, [58](#)
- TransMonoid, [75](#)
- TransposedFRElement, [60](#)
- TransSemigroup, [75](#)
- TreeWreathProduct
 - FR group**, [73](#)
 - FR machine**, [26](#)
- UnderlyingFRMachine, [18](#)
- ValueRational, [94](#)
- VectorElement, [56](#)
- VectorElementNC, [56](#)
- VectorMachine, [56](#)
- VectorMachineNC, [56](#)
- VertexElement, [31](#)
- VertexTransformations
 - FR semigroup**, [83](#)
- VertexTransformationsFRElement, [49](#)
- VertexTransformationsFRMachine, [49](#)
- VerticalAction, [113](#)
- VHGroup, [113](#)
- VHStructure, [113](#)
- VirtualEndomorphism, [83](#)
- WeaklyBranchedEmbedding, [73](#)
- WeierstrassGroup, [105](#)
- WordGrowth, [125](#)
- WreathRecursion, [22](#)